

XTREME POWER CONVERSION S70i

Line Interactive UPS // 230VAC

For more information, visit www.xpcc.com/s70i



Equip your office with reliable battery backup and protection from power outages

Power quality disturbances including voltage fluctuations, over voltage, under voltage, and voltage blackouts occur unexpectedly. In the event of any of these common power problems, the S70i UPS activates to protect all connected critical loads—ranging from your computer to your business telephone system.

The S70i streamlines installation to just a few simple steps, allowing backup power protection right out of the box. The smart LCD screen offers real-time monitoring of UPS parameters while shutdown and monitoring software enables UPS and remote device control over your network.

PRODUCT SNAPSHOT

- › Available models: 1000VA, 1500VA
- › Smart LCD display
- › Automatic voltage regulation (AVR)
- › RoHS compliant
- › Primary applications: home or small office, desktop computers, routers, and switches
- › 2 years electronics, 2 years battery warranty

FEATURES

Ease of use—plug-and-play functionality means the UPS is ready to start backing up your equipment right out of the box

Smart LCD display—monitor UPS vitals and manage all power devices in your network via USB

USB communications & software CD—enables plug and play communications between servers, desktops, and the UPS; offers seamless installation with Windows, Mac, Solaris, and Linux operating systems

Sleek design—modern and compact, perfect for use in any home office or small office setting

Longer battery life—wide operating voltage range means less use of batteries, making them last longer

Battery runtime—capable of up to 146 minutes of battery backup

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/s70i

MODEL NUMBER		S70i-1000	S70i-1500
CAPACITY	Power rating	1000VA (600W)	1500VA (900W)
INPUT	Voltage	220/230/240VAC	
	Frequency	50/60Hz	
OUTPUT	Voltage	230VAC	
	Waveform	Sine wave (normal), simulated sine wave (battery mode)	
	Frequency	50/60Hz auto sensing	
	Transfer time	4ms (typical)	
BATTERY	Battery type	Sealed, maintenance-free lead acid	
	Battery quantity and size	(2) 12V 7AH	(2) 12V 9AH
	Recharge	4–6 hours to 90% capacity	
	Runtime at 50% load	Up to 10 min	
PHYSICAL	UPS dimensions (W x D x H)	5.7 x 13.8 x 6.3 in	5.7 x 15.6 x 8.1 in
	Shipping dimensions	7.5 x 17.4 x 10 in	9.1 x 19.3 x 11.3 in
	UPS weight	17.6 lbs	24.5 lbs
	Shipping weight	19.4 lbs	27.1 lbs
	Line cord	6ft, IEC C13 to Schuko	
	Receptacles	(4) IEC C13	(6) IEC C13
	Cooling	Convection cooled	Fan cooled
ENVIRONMENT	Operating temperature	32–104°F (0–40°C)	
	Humidity	0–90%	
	Altitude	11,500 ft above sea level	
INDICATORS & ALARMS	LCD display	AC mode, battery mode, load/battery level, input/output voltage, overload fault, low battery	
	Data line protection	RJ45	
APPROVALS		CE, RoHS	
WARRANTY		2 years electronics and battery	
COMMUNICATIONS INTERFACE		USB	
INCLUDED IN BOX		Shutdown and monitoring software, USB cable, user manual, detachable line cord	



X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com