

J40 Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Ultra-Slim Surge PDU

Protect digital signage from spikes and surges with ultra-slim J40 surge PDU

- > Primary applications: digital signage, kiosks, gaming machines, and Point of Sale (POS)
- > MOV over voltage and over temperature protection
- > Power reset button to allow manual cycling of power
- > Remote power switch provides remote reset on/off, and scheduling on J40SP
- SNMP protocal (J40SP)
- > Easily mounts to wall or ceiling in any orientation
- > Optional detachable offset, right angle 5–15P power cord provides flexible installation
- > 5 year warranty (USA and Canada)

J40 Series

	Model	Part Number	Description	List Price	Input	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
	J40	90000463	10A 120V Surge PDU	\$210.00	IEC C14 inlet	(3) 5–15R	2.0 lbs	8.07" x 3.35" x 1.22"
_	J40SP	90000765	10A 120V Switched Surge PDU with Ethernet Switch	\$549.00	IEC C14 inlet	(3) 5–15R	3.75 lbs	8.07" x 7.87" x 1.22"
	J40i	90000477	10A 230V Surge PDU	\$210.00	IEC C14 inlet	(3) IEC C13	2.0 lbs	8.07" x 7.87" x 1.22"

J40 Input Cords

Model	Description	List Price	Unit Weight			
XPC-515P-3RA	3ft line cord with offset, right angle 5–15P	\$22.00	0.5 lbs			
XPC-515P-6RA	6ft line cord with offset, right angle 5–15P	\$22.00	0.5 lbs			
Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/ Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years						

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/ battery. Telephone technical support. Depot exchange. Ground shipment one way.

electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

