

J60C Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Ion UPS 600VA

120VAC or 230VAC

Protect critical servers and network devices from spikes, surges and power outages with short depth 1U J60C UPS

- › Lithium batteries provide protection for up to 10 years and 2000 discharges
- › LCD display provides input/ output voltage, load level and battery capacity
- › Power outage protection – up to 6 minutes at full load
- › 8.5" depth for tight spaces
- › 1U rack, tower or wall mounting
- › UL, CE, RoHs
- › 5 years electronics, 5 years battery warranty (USA & Canada)



J60C Series UPS 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60C-600	90001061	600VA/360W 120V UPS	\$835.00	IEC C13 to 5-15P, 3 ft	(5) 5-15R receptacles (4 battery backup + 1 surge only)	7.8 lbs	17.3 x 8.5 x 1.7 in

J60Ci Series UPS 230VAC 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60Ci-600	90001062	600VA/360W 230V UPS	\$835.00	IEC C14 inlet	(5) C13 receptacles (4 battery backup + 1 surge only)	7.8 lbs	17.3 x 8.5 x 1.7 in

J60C Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with J60C-600	\$379.00	5-15P, 12ft	(6) 5-15R front (4) 5-15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5-15P, 12ft	(14) 5-15R	3.5 lbs	19.0" x 3.5" x 1.75"

BATTERY RUNTIMES

System Load (watts)	30	40	80	120	160	200	240	280	320	360
J60C/J60Ci-600	86	64	35	23	17	14	11	9	8	6

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/ battery. Telephone technical support. Depot exchange. Ground shipment one way.

Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.