

# XTREME POWER CONVERSION J60C

Lithium UPS // 120VAC or 230VAC

For more information, visit [www.xpcc.com/j60c](http://www.xpcc.com/j60c)



## Power protection with short-depth J60C Lithium-ion UPS

Xtreme Power J60C provides the benefits of lithium-ion battery technology in a 8.5" depth 1U UPS. Ideal for short depth racks and provides extra space for cable management.

J60C Lithium-ion batteries last 3x longer than typical lead acid batteries. Up to 10 years life lowers the cost of ownership by minimizing UPS maintenance.

Remote UPS management and control with optional Web/SNMP card. LCD display adds local UPS status and metering.

J60C provides protection to: Small Edge, Retail, Banks, Healthcare and Education. J60C supports IDF/MDF closets, back office and network equipment.

For higher capacity and longer runtime Lithium-ion UPS, reference [www.xpcc.com/xtreme-power-lithium-ups/](http://www.xpcc.com/xtreme-power-lithium-ups/)

### PRODUCT SNAPSHOT

- › 600VA 1U Rack Mount UPS
- › 120VAC UL and 230VAC CE models
- › 6 Minutes Full Load Runtime
- › 5 year warranty (USA and Canada)
- › Tower, wall, and rack mount configurations available
- › UL, CE, RoHS, TAA compliant

### FEATURES

**Short depth UPS**—8.5" depth suitable for shallow racks and other space constrained applications

**Long Life Battery**—LiFePO4 batteries provide protection for up to 10 years or 2000 discharges

**Smart LCD display**—vital monitoring and precise information from the front panel

**Output Power Control**—optional Web/SNMP card provides remote on/off control of J60C output power to reboot loads

**UPS Management and Control**—optional Web/SNMP card

**Environmental Monitoring**—optional Environmental Monitoring Device provides temperature and humidity monitoring (requires Web/SNMP)

**Highest Efficiency**—J60C operates at up to 98% efficiency saving utility costs and reducing heat output

# MODEL SELECTION GUIDE

For more information, visit [www.xpcc.com/J60C](http://www.xpcc.com/J60C)

MODEL NUMBER		J60C-600	J60Ci-600
CAPACITY	Power rating	600VA (360W)	600VA (360W)
INPUT	Voltage	120VAC	230VAC
	Frequency	50/60Hz	
OUTPUT	Voltage	120VAC	230VAC
	Waveform	Sine wave (normal), simulated sine wave (battery mode)	
	Frequency	50/60Hz	
	Power Conditioning	Noise Filtering and Surge Suppression	
	Transfer time	2-6 ms (typical)	
BATTERY	Battery type	Lithium Iron Phosphate (LiFePo4)	
	Battery quantity and size	(16) LiFePO4 18650 cells, 4400mAh	
PHYSICAL	Dimensions (W x D x H)	17.2 x 8.5 x 1.7 in (438 x 215 x 44 mm)	
	Weight	7.8 lbs (3.5kgs)	
	Line cord	Detachable 5-15P to C13	C14 inlet
	Receptacles	(5) 5-15R (4 battery back up + 1 surge only)	(5) IEC C13 (4 battery back up + 1 surge only)
ENVIRONMENT	Temperature	32-104°F (0-40°C)	
	Humidity	0-90%	
	Altitude	11,500 ft above sea level	
COMMUNICATIONS INTERFACE	Standard communications	USB Interface including cable and software	
	Web/SNMP card option	Optional Web/SNMP card providing UPS monitoring and receptacle On/Off control	
	Environmental monitoring device	Measures temperature and humidity (requires Web/SNMP card option)	
APPROVALS (pending)	UL-1778, cTUVus, FCC, RoHSCE, RoHS, TAA compliant (120V) CE, RoHS, TAA compliant (230V)		
WARRANTY	5 years electronics, 5 years battery warranty (USA & Canada)*		
AVAILABLE OPTIONS	Web/SNMP card, Environmental Monitoring Device		
INCLUDED IN BOX	ViewPower CD, user manual, 5-15P to C13 line cord (120VAC unit only)		

\*Warranty outside of USA & Canada is 3 years.

## BATTERY RUNTIMES

System Load (watts)	30	40	80	120	160	200	240	280	320	360
J60C/J60Ci-600	86	64	35	23	17	14	11	9	8	6

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)



J60C(i)-600 front view

LCD display provides local metering and UPS status

8.5" Depth – suitable for short depth racks

UPS Network Management Card



J60C-600 rear view

Lithium-ion batteries provide 3X longer life than VRLA



J60Ci-600 rear view

**X-TREME**  
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

www.xpcc.com

©2022 Xtreme Power Conversion Corporation. All Rights Reserved. J60C.02U (Rev 8/11/22)