

P80g Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Pure Sine Wave Line Interactive 3000VA-5000VA

208VAC or 208/120VAC

Up to 4.5kW of efficient reliable power in just 2U rack space

- › 0.9 output power factor
- › 99% efficient operation
- › Extended battery packs available
- › Auto restart
- › Programmable receptacle group
- › \$50,000 load protection policy
- › CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P80g Series 208/230V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions* (W x D x H)
P80g-3000	90000954	3000VA/2700W 208/230V UPS, 2U	\$1,670.00	IEC C19 to L6-20P, 8ft	(1) IEC C19 + (8) IEC C13	61.9 lbs	17.2" x 23.6" x 3.5"
P80g-5000	90000430	5000VA/4500W 208/230V UPS, 2U	\$2,750.00	L6-30P, 6ft	(1) L6-30R + (4) IEC C19	78.5 lbs	17.2" x 23.6" x 3.5"
P80g-5KB1	Bundle	5000VA/4500W 208/230V UPS Bundle	\$2,987.00	L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (1) IEC C19	90 lbs	17.2" x 23.6" x 3.5"
P80g-5KB2	Bundle	5000VA/4500W 208/230V UPS and XPD24C13V Bundle	\$3,090.00	L6-30P, 6ft	(4) IEC C19 + (24) IEC C13	97 lbs	N/A

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80g Series 208/120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions* (W x D x H)
P80g-3KTB	Bundle	3000VA/2700W UPS and XPD-IT15A Bundle 208/120V Output**	\$2,920.00	L6-20P, 6ft	(1) IEC C19 + (7) IEC C13 + (16) 5-15R	207 lbs	17.2" x 23.6" x 7"
P80g-5KTB	Bundle	5000VA/4500W UPS and XPD-IT60A Bundle 208/120V Output**	\$5,427.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (12) 5-15/20R	224 lbs	17.2" x 23.6" x 7"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. **Includes P90-RAIL in bundle.

P80g Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90-BP72	90000917	72V Battery Pack for P80g-3000 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 29.9" x 23.6" x 9.45
P80-BP72X	90000432	72V High Rate Battery Pack for P80g-5000 2U	\$1,720.00	110.4 lbs	17.2" x 23.6" x 3.5" 29.9" x 23.6" x 9.45

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80g Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-C14-615R	IEC C14 to 6-15R for use with P80g-3000	1ft	208/230V	\$45.00	3 lbs

P80g Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
P90L-RAIL	90000933	4-Post Rail Kit	\$149.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"

P80g Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A Capacity for use with P80g-3000 (Includes (2) IEC C20 C19 Cord Kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD24C13V	90000374	30A 208V Basic Power Distribution Unit	\$340.00	L6-30P, 6ft	(24) C13	12.0 lbs	66.0" x 1.75" x 1.75"
XPD31	90000251	30A 240V 2U 19" Basic Power Distribution Unit	\$580.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Power Distribution Unit	\$580.00	L6-30P, 6ft	(2) L6-30R + (4) L6-20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Power Distribution Unit	\$450.00	L6-30P, 6ft	(4) IEC C19 + (8) IEC C13	6.0 lbs	19.0" x 2.4" x 3.5"
XPDU-IEC	90000053	230V Basic Power Distribution Unit	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"

P80g Isolation Transformers

Model	Part Number	Description	List Price	Weight	Unit Dimensions (W x D x H)
XPD-IT60A	90000407	6kVA PDU with Isolation Transformer 208V to 120V (or 240V to 120V), 3ft L6-30P Input Cord, (1) L6-30R and (12) 5-15/20R Receptacles, Max. 120V load is 4kW.	\$2,150.00	137 lbs	19.0" x 18.0" x 3.5"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P80g-3000, 2ft IEC C14 Input Cord, 2ft 5-15 Output Cord	\$600.00	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	Isolation transformer with (16) 5-15 output receptacles, 3ft C-14 to 5-15P Output Cord	\$980.00	43 lbs	17.25" x 15" x 3.5"

P80g Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P905SP23	90000523	Extended 5 Year Factory Warranty for P80g-3000, P80-2000, P80-2200, P80-3000(V2), P90-2000, P90-3000, P90g-3000 UPS	\$610.00
P805SP5	90000431	Extended 5 Year Factory Warranty for P80g-5000 UPS	\$800.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P80g Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model		Internal batteries				(1) Battery pack				(2) Battery packs			
Percentage load:	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%	
P80g-3000	13	8	5	3	56	34	24	20	107	66	47	38	
P80g-5000	10	5	3	2	38	24	18	14	71	45	33	27	

Maximum of two battery packs per P80g-3000 or P80g-5000.