

P91g 1-3kVA UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 1000VA-3000VA
208/230VAC

Premium power protection for mission critical applications

- › High output power factor
- › Up to 98% efficient operation
- › Extended battery packs available for 2U models
- › Multiple communications capability
- › Hot swappable battery design
- › Programmable Outlet Group (2U)
- › \$50,000 load protection policy
- › CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P91g Series 230V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91gc-1000	90000746	1000VA/800W 208/230V UPS with 1A Charger, 1U	\$1,050.00	C14 inlet, 8ft L6-20P to C13 line cord	(3) C13	28 lbs	17.2" x 17.8" x 1.7" 22.5" x 24.5" x 6.5"
P91g-1500	90000747	1500VA/1450W 208/230V UPS with 2A Charger, 2U	\$1,399.00	C14 inlet, 8ft L6-20P to C13 line cord	(8) IEC C13	34.2 lbs	17.2" x 15.1" x 3.5" 23.6" x 19.7" x 9.45"
P91g-2000	90000748	2000VA/1930W 208/230V UPS with 2A Charger, 2U	\$1,829.00	C20 inlet, 8ft L6-20P to C19 line cord	(8) IEC C13	43 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91g-3000	90000749	3000VA/2880W 208/230V UPS with 2A Charger, 2U	\$2,449.00	C20 inlet, 8ft L6-20P to C19 line cord	(1) IEC C19 + (8) IEC C13	60.6 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. Capacity derates to 90% at 208 output.

P91g Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91-BP36	90000787	36V Battery Pack for P91g-1500, 2U	\$920.00	58.1 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P91-BP36E	90000788	36V 4 String Extended Battery Pack for P91g-1500, 2U	\$1,320.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P91-BP48	90000789	48V Battery Pack for P91g-2000, 2U	\$1,080.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P91-BP72	90000790	72V Battery Pack for P91g-3000, P91g-3000, 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91g Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-C14-615R	IEC C14 to 6-15R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	208/230V	\$45.00	3 lbs
XPC-C14-620R	IEC C14 to 6-15/20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$49.00	2 lbs
XPC-C14-L620R	IEC C14 to L6-20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-C14-L630R	IEC C14 to L6-30R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs

P91g Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket (2U units)	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91g-1000, 1500, 2000	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P91g Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A capacity for use with P91g-3000 (includes (2) IEC C20 C19 cord kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P91g-3000	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P91g-1500, P91g-3000	\$600.00	208V IEC C14, 2ft	120V 5–15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$980.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)

P91g Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P905SP15	90000522	Extended 5 Year Factory Warranty for P91g-1500, P91gc-1000, P91g-1000, P91g-1500	\$375.00
P905SP23	90000523	Extended 5 Year Factory Warranty for P91g-2000, P91g-3000	\$610.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P91g Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal batteries		1		2		3		4		5		6		7		8	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
P91gc-1000	20	8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-1500 (BP36)	10	3	42	17	84	33	120	51	157	72	199	93	244	112	289	128	339	146
P91g-1500 (BP36E)	10	3	84	33	157	72	244	112	339	146	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-2000 (BP48)	10	3	42	17	84	33	121	51	157	72	200	93	244	112	290	128	340	147
P91g-3000 (BP72)	10	3	42	17	84	33	121	52	158	73	201	94	246	112	292	129	343	148

Maximum of eight battery packs per P91g-1500, P91g-2000, or P91g-3000 (excluding BP36E). Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.