

R91 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Three-phase Online 20kVA

415/240VAC, 400/230VAC, 380/220VAC

Reduce power consumption with 94% online efficiency

- › High output power factor of 0.9
- › Parallel for capacity or redundancy up to 4 modules
- › 50Hz or 60Hz operation
- › Online double conversion or ECO mode operation
- › 99% efficiency in single module systems in ECO mode
- › UL 1778, FCC A, CE, RoHS
- › 2 years depot warranty (USA only)



R91 Series UPS

Model	Part Number	Description	List Price	Input/Output	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
R91-20K	90000129	20kVA/18kW Three-phase UPS 3U with Rack Shelf Kit	\$12,800.00	Terminal block	68.4 lbs	91.5 lbs	17.4" x 22.8" x 5.2" 22.2" x 28.5" x 14.2"
BP-XR4U480A	90000390	R91 Battery Module 4U with hot swappable battery modules	\$6,400.00	N/A	280 lbs	300 lbs	17.4 x 33.9 x 7" 24.5" x 39" x 10"

R91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-R90	90000266	External Web/SNMP card	\$425.00	1 lb	7.3" x 3.5" x 1.8"

R91 Accessories

Model	Part Number	Description	List Price	Utility Input Connection	Load Output Connection	Unit Weight	Unit Dimensions (W x D x H)
R90-MBP40A	90000369	400V 40A Maintenance Bypass with Rotary Switch, Cable Kit, and UPS Interlock	\$3,000.00	Terminal block	Terminal block	10.5 lbs	17.0" x 9.0" x 3.5"
R91-IEC309	90000535	32A input/output IEC 309 cable kit	\$650.00	IEC 309	IEC 309	TBA	TBA

R91 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
R91SU581	90000536	Startup 5x8 and 1 year on-site warranty	\$2,450.00
R91SU582	90000537	Startup 5x8 and 2 year on-site warranty	\$3,950.00

R91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Percentage load	20%	40%	60%	80%	100%
R91-20K + (1)BP-XR4U480A	52	23	14	9	7
R91-20K + (2)BP-XR4U480A	116	53	33	23	18
R91-20K + (3)BP-XR4U480A	170	87	53	38	29
R91-20K + (4)BP-XR4U480A	234	117	75	53	41
R91-20K + (5)BP-XR4U480A	300	140	99	70	53
R91-20K + (6)BP-XR4U480A	368	172	117	87	66
R91-20K + (7)BP-XR4U480A	437	204	131	104	80
R91-20K + (8)BP-XR4U480A	507	237	151	117	94

For longer runtimes please contact sales@xpcc.com