

XTREME POWER CONVERSION Isolation PDU

Isolation Rack Power Distribution // 1.5kW to 10kW

For more information, visit www.xpcc.com/ipdu



Rack isolation transformer solutions designed to meet the voltage and power quality requirements

Meet voltage requirements and improve power quality with the Xtreme Power isolation PDU family, a series of power distribution units that combine the key features needed to manage equipment racks.

Our isolation PDU combined with Xtreme Power UPS provides the cleanest power in the most demanding conditions. The galvanic isolation transformer eliminates common mode noise found in many IT, retail, industrial, and laboratories applications.

Xtreme isolation PDU provides output voltages and receptacles to meet a wide range of load requirements.

For PDUs without isolation transformer reference the XPDU at www.xpcc.com/xpdu

PRODUCT SNAPSHOT

- › Available models: 1.5kW to 10kW
- › 208/240V input and 120/208/240V output
- › Vertical and horizontal mounting
- › 3 year full warranty (USA and Canada)

FEATURES

Hardwire or Plug/Receptacle—multiple configurations to meet site requirements

NEMA plugs and IEC inlet—multiple input configurations available

208V or 240V input—input terminal block connections allow either 208V or 240V from UPS (IT6kW, IT10kW)

208V or 240V selector—input selector switch for 208V or 240V from UPS (IT60A)

Galvanic Isolation—eliminates common mode noise

Mounting options—wall, rack, and floor mounting options available

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/ipdu

MODEL NUMBER	Input Power Connection	Outlets	Voltage	Capacity	Dimensions (W x D x H)	Weight
Transformer PDU						
XPD-IT15A	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	208V in to 120V	1.5kW	17.3 x 10.5 x 3.5 in (2U)	43 lbs
XPD-IT60A	3 ft, L6-30P	(1) L6-30R* and (12) 5-15/20R	208V to 208/120V 240V to 240/120V	6kW	17.3 x 18.0 x 3.5 in (2U)	137 lbs
XPD-IT6kW	Input terminal block	Output terminal block (2) L14-30R (8) 5-15/20R	208V to 240/120V 240V to 240/120V	6kW	17.3" x 32.8" x 4.7 (3U)	199 lbs
XPD-IT10kW	Input terminal block	Output terminal block (2) L14-30R (8) 5-15/20R	208V to 240/120V 240V to 240/120V	10kW	17.3 x 32.8 x 4.7 in (3U)	209 lbs

*L6-30R output voltage is passed through (not isolated) and the same as input.



XPD-IT15A rear view

(16) 5-15R



XPD-IT60A rear view

L6-30R



XPD-IT6kW & XPD-IT10kW rear view

(8) 5-20R

Input & output terminal blocks

X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2020 Xtreme Power Conversion Corporation. All Rights Reserved. XPDU.01U (Rev 3/19/20)