


XTREME POWER CONVERSION

CRITICAL POWER SOLUTIONS

USA PRICEBOOK



Prices are subject to change without prior notice
This pricebook supersedes all previous pricing publications

Subject to Xtreme Power Terms and Conditions

USA Pricebook August 1, 2024

J60 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Ion UPS 350VA, 600VA 120VAC or 230VAC

Protect digital signage from spikes, surges and power outages with an ultra-slim J60 UPS

- › Slim and light weight (1.2" and 3.4 lbs, 350 models) the J60/J60i mounts easily behind flat panel displays
- › Lithium batteries provide protection for up to 10 years and 2000 discharges
- › Power outage protection – up to 7 minutes at full load
- › Primary applications: digital signage, kiosks, gaming machines, and Point of Sale (POS)
- › Easily mounts to wall or ceiling in any orientation
- › Optional detachable offset, right angle 5–15P power cord provides flexible installation (only J60)
- › UL, CE, RoHS, TAA compliant (UPS only)
- › 5 years electronics, 5 years battery warranty (USA & Canada)



J60 Series UPS 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60-350	90000465	350VA/200W 120V UPS	\$439.00	IEC C13 to 5-15P, 3 ft	(3) 5–15R	3.4 lbs	6.9" x 8.5" x 1.25"
J60-600	90000776	600VA/360W 120V UPS	\$749.00	IEC C13 to 5-15P, 3 ft	(3) 5–15R	4.7 lbs	7.3" x 10.8" x 1.6"

J60i Series UPS 230VAC 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60i-350	90000472	350VA/200W 230V UPS	\$439.00	IEC C14 inlet	(2) IEC C13	3.4 lbs	6.9" x 8.5" x 1.25"
J60i-600	90000777	600VA/360W 230V UPS	\$749.00	IEC C14 inlet	(2) IEC C13	4.7 lbs	7.3" x 10.8" x 1.6"

J60 Accessories

Model	Part Number	Description	List Price	Unit Weight
XPC-515P-3RA	N/A	3ft line cord with offset, right angle 5–15P for use with J60-350/600	\$22.00	1 lbs
XPC-515P-6RA	N/A	6ft line cord with offset, right angle 5–15P for use with J60-350/600	\$22.00	1 lbs
SNMP-J60	90000778	J60-600(i) external SNMP card	\$279.00	1 lb
EMD-J60	90000785	Environmental monitoring device for use with SNMP-J60*	\$195.00	1 lb
JX-200	90000742	200W Isolation transformer matching J60-350 dimensions	\$220.00	7 lbs
J60-DIN	90000765	DIN rail mount kit for J60	\$19.00	2 lbs

*EMD-J60 must be used with the SNMP-J60

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

BATTERY RUNTIMES

System Load (watts)	20	40	80	120	160	200	240	280	320	360
J60/J60i-350	72	35	17	11	9	7	N/A	N/A	N/A	N/A
J60/J60i-600	161	79	35	23	17	14	11	9	8	6

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)

J60C Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Ion UPS 600VA

120VAC or 230VAC

Protect critical servers and network devices from spikes, surges and power outages with short depth 1U J60C UPS

- › Lithium batteries provide protection for up to 10 years and 2000 discharges
- › LCD display provides input/ output voltage, load level and battery capacity
- › Power outage protection – up to 6 minutes at full load
- › 8.5" depth for tight spaces
- › 1U rack, tower or wall mounting
- › UL, CE, RoHs
- › 5 years electronics, 5 years battery warranty (USA & Canada)



J60C Series UPS 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60C-600	90001061	600VA/360W 120V UPS	\$835.00	IEC C13 to 5-15P, 3 ft	(5) 5-15R receptacles (4 battery backup + 1 surge only)	7.8 lbs	17.3 x 8.5 x 1.7 in

J60Ci Series UPS 230VAC 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J60Ci-600	90001062	600VA/360W 230V UPS	\$835.00	IEC C14 inlet	(5) C13 receptacles (4 battery backup + 1 surge only)	7.8 lbs	17.3 x 8.5 x 1.7 in

J60C Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with J60C-600	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"

BATTERY RUNTIMES

System Load (watts)	20	40	80	120	160	200	240	280	320	360
J60C/J60Ci-600	161	79	35	23	17	14	11	9	8	6

(Runtimes are shown in minutes and will vary based on battery age and site conditions.)

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/ battery. Telephone technical support. Depot exchange. Ground shipment one way.

Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

A60 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Standby 550VA, 850VA
120VAC

Affordable, reliable power protection for valuable home and small business electronics

- › Compact design allows for horizontal, verticle and wall mount placement
- › USB communcation port
- › Surge protection
- › Touch LCD display (850 only)
- › USB port allows mobile device charging (850 only)
- › \$25,000 Load Protection Policy
- › UL, cUL, Energy Star, TAA compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)



A60 Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
A60-550	90000875	550VA/330W 120V UPS	\$125.00	5-15P, 6ft	(10) NEMA 5-15R*	5.7 lbs	6.2 x 12 x 3.7 in 4.7 x 11.4 x 11.0 in
A60-850	90000876	850VA/500W 120V UPS	\$165.00	5-15P, 6ft	(10) NEMA 5-15R*	6.4 lbs	6.2 x 12 x 3.7 in 4.7 x 11.4 x 11.0 in

*5 battery backup + 5 surge only receptacles

A60 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-USB	90000281	External Web/SNMP Card	\$325.00	1 lb	7.25" x 6" x 2.5"

A60 Service Plan (USA and Canada)

Model	Part Number	Description	List Price
A605SP	90001033	Extended 5 Year Factory Warranty for A60-550/850	\$69.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

A60 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Load:	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
A60-550	60	27	15	10	8	6	4.5	3	2.2	<1
A60-850	45	20	12	7.3	6	4	2.5	2	1	<1

S71 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Line Interactive 700VA-1500VA 120VAC

Equip your office with reliable battery backup and protection from power outages

- › Touch LCD display
- › Auto restart
- › Automatic voltage regulation (AVR)
- › Primary applications: home or small office, desktop computers, routers, and switches
- › USB ensures plug and play communications between servers, desktops, and the UPS
- › 465 Joule surge suppression rating
- › \$25,000 Load Protection Policy
- › UL and cUL listed, RoHS, TAA compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)



S71 Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
S71-700	90001237	700VA/420W 120V Tower UPS	\$189.00	Detachable 6ft, C13 to 5-15P	(4) 5-15R	11.2 lbs	3.9" x 11.3" x 5.6" 5.5" x 13.1" x 8.7"
S71-1000	90001238	1000VA/600W 120V Tower UPS	\$275.00	6 ft, 5-15P	(6) 5-15R	18 lbs	5.1" x 12.6" x 7.1" 7.5" x 17.4" x 10.0"
S71-1500	90001240	1500VA/900W 120V Tower UPS	\$389.00	6 ft, 5-15P	(6) 5-15R	23 lbs	5.1" x 12.6" x 7.1" 7.5" x 17.4" x 10.0"

S71 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-USB	90000281	External Web/SNMP Card	\$325.00	1 lb	7.25" x 6" x 2.5"

S71 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
S715SP57	90000248	Extended 5 Year Factory Warranty for S71-700	\$95.00
S715SP152	90000249	Extended 5 Year Factory Warranty for S71-1000, S71-1500	\$140.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

S71 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Load	S71-700	S71-1000	S71-1500
250VA	15	22	30
350VA	6	12	21
500VA	2	6	11
700VA	<1	3	6
1000VA	-	1	3
1500VA	-	-	1.5

V80 Lead Acid Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Value Series Pure Sine Wave Line Interactive UPS 120V

Value series line interactive power protection for servers and network equipment

- › Pure Sinewave Output
- › Automatic voltage regulation (AVR)
- › Auto restart
- › Hot Swappable Battery
- › Tower feet and front mount rack brackets included
- › USB, RS232, EPO and Intelligent Slot for optional cards
- › 465 Joule surge suppression rating
- › \$25,000 Load Protection Policy
- › UL, cUL, RoHS
- › 3 years electronics, 3 years battery warranty (USA and Canada)



V80 Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
V80-700	90000853	700VA/420W 120V UPS, 2U	\$499.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	24 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1000	90000854	1000VA/600W 120V UPS, 2U	\$659.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	27.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1500	90000855	1500VA/900W 120V UPS, 2U	\$749.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	29.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-2000	90000856	2000VA/1200W 120V UPS, 2U	\$869.00	Detachable 5ft, 5-20P to C19	(8) 5-15R	31.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"

V80 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

V80 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with v80-700, V80-1000, V80-1500	\$379.00	5-15P, 12ft	(6) 5-15R front (4) 5-15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"

V80 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
V805SP71	90000409	Extended 5 Year Factory Warranty for V80-700, V80-1000	\$225.00
V805SP52	90000410	Extended 5 Year Factory Warranty for V80-1500, V80-2000	\$360.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

V80XR Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Value Series Pure Sine Wave Line Interactive UPS 120V

Value series line interactive power protection with extended runtimes

- › Pure Sinewave Output
- › Automatic voltage regulation (AVR)
- › Hot Swappable Battery
- › Tower feet and front mount rack brackets included
- › USB, RS232, EPO and Intelligent Slot for optional cards
- › 465 Joule surge suppression rating
- › \$25,000 Load Protection Policy
- › UL, cUL, RoHS, TAA Compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)



V80XR Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
V80-700XR1	90000890	700VA/420W 120V UPS, 2U, 1 string of 12V 9AH batteries	\$565.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	25.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700XR2	90000891	700VA/420W 120V UPS, 2U 2 strings of 12V 9AH batteries	\$625.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	31.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700XR3	90000892	700VA/420W 120V UPS, 2U 3 strings of 12V 9AH batteries	\$685.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	37.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700XR4	90000893	700VA/420W 120V UPS, 2U 4 strings of 12V 9AH batteries	\$745.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	43.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1000XR1	90000894	1000VA/600W 120V UPS, 2U 1 string of 12V 9AH batteries	\$755.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	31.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1000XR2	90000895	1000VA/600W 120V UPS, 2U 2 strings of 12V 9AH batteries	\$865.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	43.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1500XR1	90000896	1500VA/900W 120V UPS, 2U 1 string of 12V 9AH batteries	\$809.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	32.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1500XR2	90000897	1500VA/900W 120V UPS, 2U 2 strings of 12V 9AH batteries	\$949.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	44.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-2000XR1	90000898	2000VA/1200W 120V UPS, 2U 1 string of 12V 9AH batteries	\$899.00	Detachable 5ft, 5-20P to C19	(8) 5-15R	34.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-2000XR2	90000899	2000VA/1200W 120V UPS, 2U 2 strings of 12V 9AH batteries	\$1,039.00	Detachable 5ft, 5-20P to C19	(8) 5-15R	46.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"

V80 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

V80XR Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with V80XR-700, V80XR-1000, V80XR-1500	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5–15R	3.4 lbs	19" x 3.5" x 1.75"

V80XR Service Plans (USA and Canada)

Model	Part Number	Description	List Price
V805SP71	90000409	Extended 5 Year Factory Warranty for V80-700XR, V80-1000XR	\$225.00
V805SP52	90000410	Extended 5 Year Factory Warranty for V80-1500XR, V80-2000XR	\$360.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

V80XR Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Battery Strings:	1 string (XR1)				2 strings (XR2)				3 strings (XR3)				4 strings (XR4)			
Percentage Load:	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%
V80-700XR	31	13	6	4.3	70	29	17	13	114	49	28	21	153	73	41	22
V80-1000XR	47	20	12	6.0	105	45	26	16	-	-	-	-	-	-	-	-
V80-1500XR	28	12	6	3.8	63	27	15	11	-	-	-	-	-	-	-	-
V80-2000XR	19	7	3.5	1.7	43	18	10	4.4	-	-	-	-	-	-	-	-

V80 Lithium Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Pure Sine Wave Line Interactive UPS 120V

Value series line interactive power protection for servers and network equipment

- › Pure Sinewave Output
- › Automatic voltage regulation (AVR)
- › Auto restart
- › Hot Swappable Battery
- › 6A Charger for 60 minute recharge
- › Tower feet and front mount rack brackets included
- › USB, RS232, EPO and Intelligent Slot for optional cards
- › 465 Joule surge suppression rating
- › \$25,000 Load Protection Policy
- › UL, cUL, RoHS, TAA Compliant
- › 5 years electronics, 5 years battery warranty (USA and Canada)



V80 Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
V80-0.7kLi1	90000857	700VA/420W 120V UPS, 2U 1 string of LiFePO4 batteries	\$999.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	21.2 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-0.7kLi2	90000967	700VA/420W 120V UPS, 2U 2 strings of LiFePO4 batteries	\$1,399.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	23.4 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-0.7kLi3	90000968	700VA/420W 120V UPS, 2U 3 strings of LiFePO4 batteries	\$1,799.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	25.6 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-0.7kLi4	90000969	700VA/420W 120V UPS, 2U 4 strings of LiFePO4 batteries	\$2,199.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	27.8 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1kLi1	90000858	1000VA/600W 120V UPS, 2U 1 string of LiFePO4 batteries	\$1,549.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	24.2 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1kLi2	90000970	1000VA/600W 120V UPS, 2U 2 strings of LiFePO4 batteries	\$2,349.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	28.6 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1.5kLi1	90000859	1500VA/900W 120V UPS, 2U 1 string of LiFePO4 batteries	\$1,639.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	26 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1.5kLi2	90000971	1500VA/900W 120V UPS, 2U 2 strings of LiFePO4 batteries	\$2,439.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	30.4lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"

V80 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

V80 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with V80Li-700, V80Li-1000, V80Li-1500	\$379.00	5-15P, 12ft	(6) 5-15R front (4) 5-15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"

V80 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Percentage load:	1 string (Li1)		2 strings (Li2)		3 strings (Li3)		4 strings (Li4)	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%
V80-0.7kLi	16	<3	36	16	56	18	72	22
V80-1kLi	25	7	49	20	-	-	-	-
V80-1.5kLi	11	<3	32	11	-	-	-	-

V80HT Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Value Series Pure Sine Wave Line Interactive UPS 120V

Power protection for extreme temperature environments

- › Pure Sinewave Output
- › Batteries rated for up to 12 years at 77°F (25 °C) or 5 years at 113°F (45 °C)
- › High temperature operations from up to 113°F (45 °C)
- › Hot Swappable Battery
- › Tower feet and front mount rack brackets included
- › USB, RS232, EPO and Intelligent Slot for optional cards
- › 465 Joule surge suppression rating
- › \$25,000 Load Protection Policy
- › UL, cUL, RoHS, TAA Compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)



V80HT Series UPS 120V 60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions (W x D x H)
V80-700HT1	90000864	700VA/420W 120V UPS, 2U 1 string of 12V 8.5AH batteries	\$579.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	25.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700HT2	90000961	700VA/420W 120V UPS, 2U 2 strings of 12V 8.5AH batteries	\$689.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	31 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700HT3	90000862	700VA/420W 120V UPS, 2U 3 strings of 12V 8.5AH batteries	\$799.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	37 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-700HT4	90000863	700VA/420W 120V UPS, 2U 4 strings of 12V 8.5AH batteries	\$909.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	43 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1000HT1	90000865	1000VA/600W 120V UPS , 2U 1 string of 12V 8.5AH batteries	\$799.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	31.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1000HT2	90000964	1000VA/600W 120V UPS , 2U 2 strings of 12V 8.5AH batteries	\$1,019.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	43 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1500HT1	90000866	1500VA/900W 120V UPS, 2U 1 string of 12V 8.5AH batteries	\$879.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	32.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-1500HT2	90000965	1500VA/900W 120V UPS, 2U 2 strings of 12V 8.5AH batteries	\$1,099.00	Detachable 5ft, 5-15P to C13	(8) 5-15R	44.5 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-2000HT1	90000867	2000VA/1200W 120V UPS, 2U 1 string of 12V 8.5AH batteries	\$999.00	Detachable 5ft, 5-20P to C19	(8) 5-15R	34.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"
V80-2000HT2	90000966	2000VA/1200W 120V UPS, 2U 2 strings of 12V 8.5AH batteries	\$1,219.00	Detachable 5ft, 5-20P to C19	(8) 5-15R	46.3 lbs	17.2" x 16.1" x 3.5" 21.5" x 22" x 9"

V80 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

V80HT Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with V80HT-700, V80HT-1000, V80HT-1500	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5–15R	3.4 lbs	19" x 3.5" x 1.75"

V80HT Service Plans (USA and Canada)

Model	Part Number	Description	List Price
V80HT5SP71	90000409	Extended 5 Year Factory Warranty for V80HT-700, V80HT-1000	\$225.00
V80HT5SP52	90000410	Extended 5 Year Factory Warranty for V80HT-1500, V80HT-2000	\$360.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

V80HT Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

	1 string (HT1)				2 string (HT2)				3 string (HT3)				4 string (HT4)			
Percentage Load:	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%
V80-700HT	30	10	5	3.6	63	29	15	10	109	45	28	21	153	66	38	22
V80-1000HT	43	18	9	4.9	99	41	26	14	-	-	-	-	-	-	-	-
V80-1500HT	28	9	5	3.2	58	26	13	9	-	-	-	-	-	-	-	-
V80-2000HT	17	6	3.1	1.1	40	16	10	4.4	-	-	-	-	-	-	-	-

P80 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Pure Sine Wave Line Interactive 800VA-3000VA 120VAC

Advanced line interactive power protection for servers and network equipment

- › 0.9 output power factor
- › 99% efficient operation
- › Extended battery packs available for 1500VA-3000VA models
- › Auto restart
- › Programmable receptacle group
- › \$50,000 load protection policy
- › UL, cUL, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P80 Series 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions* (W x D x H)
P80-800	90000900	800VA/720W 120V UPS, 2U	\$789.00	5-15P, 6ft	(8) 5-15R	29.3 lbs	17.2 x 15.1 x 3.5 in
P80-1100	90000901	1100VA/990W 120V UPS, 2U	\$849.00	5-15P, 6ft	(8) 5-15R	30.5 lbs	17.2 x 15.1 x 3.5 in
P80-1500	90000902	1500VA/1350W 120V UPS, 2U	\$1,099.00	5-15P, 6ft	(8) 5-15R	44.7 lbs	17.2 x 18.9 x 3.5 in
P80-2000	90000955	2000VA/1800W 120V UPS, 2U	\$1,249.00	5-20P, 6ft	(8) 5-15/20R	47.4 lbs	17.2 x 18.9 x 3.5 in
P80-2200	90000903	2200VA/2000W 120V UPS, 2U	\$1,569.00	5-20P, 6ft	(8) 5-15/20R	61.7 lbs	17.2 x 23.6 x 3.5 in
P80-3000	90000904	3000VA/2700W 120V UPS, 2U	\$1,729.00	L5-30P, 6ft	(8) 5-15/20R	67.1 lbs	17.2 x 23.6 x 3.5 in
P80-3000V2	90000529	3000VA/2700W 120V UPS, 2U	\$1,729.00	L5-30P, 6ft	(6) 5-15/20R + (1) L5-30R	68 lbs	17.2 x 23.6 x 3.5 in

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80 Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90-BP48	90000916	48V Battery Pack for P80-1500, P80-2000, 2U	\$990.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P90-BP72	90000917	72V Battery Pack for P80-2200, P80-3000, 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 29.9" x 23.6" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P80-800, P80-1100, P80-1500, P80-2000	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P80 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with P80-800, P80-1100 or P80-1500	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5–15R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass 20A/120VAC for use with P80-2000 or P80-2200	\$419.00	5–20P, 12ft	(6) 5–20R front (4) 5–20R back	5–20R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass 30A/120VAC for use with P80-3000V2	\$659.00	L5–30P, 6ft	(6) 5–20R front (4) 5–20R back	L5-30R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XPD-1420HV	90000045	120V Basic Power Distribution Unit	\$190.00	L5–20P, 12ft or 5–20P with adapter	(14) 5–20R	4.8 lbs	19.0" x 3.5" x 1.75"

P80 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P905SP15	90000522	Extended 5 Year Factory Warranty for P80-800, P80-1100, P80-1500, P90c-1000, P90-1000, P90-1500, P90g-1500 UPS	\$375.00
P905SP23	90000523	Extended 5 Year Factory Warranty for P80-2000, P80-2200, P80-3000(V2), P80g-3000, P90-2000, P90-3000 UPS, P90g-3000	\$610.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P80 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal batteries				(1) Battery pack				(2) Battery packs			
Percentage load:	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%
P80-800	29	11	6	4	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P80-1100	26	11	5	3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P80-1500	31	12	6	4	124	53	31	22	216	102	61	42
P80-2000	30	12	6	4	119	50	30	20	211	97	58	40
P80-2200	32	12	6	4	125	54	32	22	219	104	62	43
P80-3000(V2)	30	12	6	4	119	50	30	20	211	97	58	40

Maximum of two battery packs per P80-1500, P80-2000, P80-2200, or P80-3000(V2).

P80g Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Pure Sine Wave Line Interactive 3000VA-5000VA

208VAC or 208/120VAC

Up to 4.5kW of efficient reliable power in just 2U rack space

- › 0.9 output power factor
- › 99% efficient operation
- › Extended battery packs available
- › Auto restart
- › Programmable receptacle group
- › \$50,000 load protection policy
- › CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P80g Series 208/230V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions* (W x D x H)
P80g-3000	90000954	3000VA/2700W 208/230V UPS, 2U	\$1,670.00	IEC C19 to L6-20P, 8ft	(1) IEC C19 + (8) IEC C13	61.9 lbs	17.2" x 23.6" x 3.5"
P80g-5000	90000430	5000VA/4500W 208/230V UPS, 2U	\$2,750.00	L6-30P, 6ft	(1) L6-30R + (4) IEC C19	78.5 lbs	17.2" x 23.6" x 3.5"
P80g-5KB1	Bundle	5000VA/4500W 208/230V UPS Bundle	\$3,066.00	L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (1) IEC C19	90 lbs	17.2" x 23.6" x 3.5"
P80g-5KB2	Bundle	5000VA/4500W 208/230V UPS and XPD24C13V Bundle	\$3,090.00	L6-30P, 6ft	(4) IEC C19 + (24) IEC C13	97 lbs	N/A

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80g Series 208/120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions* (W x D x H)
P80g-3KTB	Bundle	3000VA/2700W UPS and XPD-IT15A Bundle 208/120V Output**	\$2,920.00	L6-20P, 6ft	(1) IEC C19 + (7) IEC C13 + (16) 5-15R	207 lbs	17.2" x 23.6" x 7"
P80g-5KTB	Bundle	5000VA/4500W UPS and XPD-IT60A Bundle 208/120V Output**	\$5,427.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (12) 5-15/20R	224 lbs	17.2" x 23.6" x 7"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. **Includes P90-RAIL in bundle.

P80g Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90-BP72	90000917	72V Battery Pack for P80g-3000 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 29.9" x 23.6" x 9.45
P80-BP72X	90000432	72V High Rate Battery Pack for P80g-5000 2U	\$1,720.00	110.4 lbs	17.2" x 23.6" x 3.5" 29.9" x 23.6" x 9.45

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P80g Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P80g-3000, P80g-5000	1ft	208/230V	\$79.00	3 lbs
XPC-C14-615R	IEC C14 to 6-15R for use with P80g-3000	1ft	208/230V	\$45.00	3 lbs

P80g Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
P90L-RAIL	90000933	4-Post Rail Kit	\$149.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"

P80g Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A Capacity for use with P80g-3000 (Includes (2) IEC C20 C19 Cord Kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD24C13V	90000374	30A 208V Basic Power Distribution Unit	\$340.00	L6-30P, 6ft	(24) C13	12.0 lbs	66.0" x 1.75" x 1.75"
XPD31	90000251	30A 240V 2U 19" Basic Power Distribution Unit	\$580.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Power Distribution Unit	\$580.00	L6-30P, 6ft	(2) L6-30R + (4) L6-20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Power Distribution Unit	\$450.00	L6-30P, 6ft	(4) IEC C19 + (8) IEC C13	6.0 lbs	19.0" x 2.4" x 3.5"
XPDU-IEC	90000053	230V Basic Power Distribution Unit	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"

P80g Isolation Transformers

Model	Part Number	Description	List Price	Weight	Unit Dimensions (W x D x H)
XPD-IT60A	90000407	6kVA PDU with Isolation Transformer 208V to 120V (or 240V to 120V), 3ft L6-30P Input Cord, (1) L6-30R and (12) 5-15/20R Receptacles, Max. 120V load is 4kW.	\$2,150.00	137 lbs	19.0" x 18.0" x 3.5"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P80g-3000, 2ft IEC C14 Input Cord, 2ft 5-15 Output Cord	\$600.00	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	Isolation transformer with (16) 5-15 output receptacles, 3ft C-14 to 5-15P Output Cord	\$980.00	43 lbs	17.25" x 15" x 3.5"

P80g Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P905SP23	90000523	Extended 5 Year Factory Warranty for P80g-3000, P80-2000, P80-2200, P80-3000(V2), P90-2000, P90-3000, P90g-3000 UPS	\$610.00
P805SP5	90000431	Extended 5 Year Factory Warranty for P80g-5000 UPS	\$800.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P80g Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model		Internal batteries				(1) Battery pack				(2) Battery packs			
Percentage load:	25%	50%	75%	100%	25%	50%	75%	100%	25%	50%	75%	100%	
P80g-3000	13	8	5	3	56	34	24	20	107	66	47	38	
P80g-5000	10	5	3	2	38	24	18	14	71	45	33	27	

Maximum of two battery packs per P80g-3000 or P80g-5000.

P91 1-3kVA UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 1000VA-3000VA
120VAC

Premium power protection for mission critical applications

- › High output power factor
- › Up to 98% efficient operation
- › Extended battery packs available for 2U models
- › Multiple communications capability
- › Hot swappable battery design
- › Programmable outlet groups (2U)
- › \$50,000 load protection policy
- › UL, cUL, RoHS, FCC Class B (1000VA (2U), 1500VA),
FCC Class A (1000VA (1U), 2000VA, 3000VA, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P91 Series 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91c-1000	90000621	1000VA/800W 120V UPS with 1A Charger, 1U	\$1,130.00	C14 inlet, 5ft 5-15P to C13 line cord	(3) NEMA 5-15R	28 lbs	17.2" x 17.8" x 1.7" 22.5" x 24.5" x 6.5"
P91-1000	90000756	1000VA/1000W 120V UPS with 1-8A Charger, 2U	\$1,165.00	6 ft, 5-15P	(8) NEMA 5-15R	25.5 lbs	17.2" x 15.1" x 3.5" 23" x 20" x 7.5"
P91-1500	90000622	1500VA/1450W 120V UPS with 1-8A Charger, 2U	\$1,520.00	6 ft, 5-15P	(8) NEMA 5-15R	34.2 lbs	17.2" x 15.1" x 3.5" 23" x 20" x 7.5"
P91-2000	90000623	2000VA/1930W 120V UPS with 1-8A Charger, 2U	\$1,985.00	6 ft, 5-20P	(8) NEMA 5-15/20R	43 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91-3000	90000624	3000VA/2880W 120V UPS with 1-8A Charger, 2U	\$2,650.00	6 ft, L5-30P	L5-30R + (6) 5-15/20R	60.6 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91 Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91-BP36	90000787	36V Battery Pack for P91-1500, 2U	\$920.00	58.1 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P91-BP36E	90000788	36V 4 String Extended Battery Pack for P91-1500, 2U	\$1,320.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P91-BP48	90000789	48V Battery Pack for P91-2000, 2U	\$1,080.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P91-BP72	90000790	72V Battery Pack for P91-3000	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket (2U units)	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91-1000, 1500, 2000	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

**SNMP-EMPV2 to be used with SNMP-2PV3*

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with P91c-1000, P91-1000, P91-1500	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass 20A/120VAC for use with P91-2000	\$419.00	5–20P, 12ft	(6) 5–20R front (4) 5–20R back	5-20R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass 30A/120VAC for use with P91-3000	\$659.00	L5–30P, 6ft	(6) 5–20R front (4) 5–20R back	L5-30R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XPD-1420HV	90000045	120V Basic Power Distribution Unit	\$190.00	L5–20P, 12ft or 5–20P with adapter	(14) 5–20R	4.8 lbs	19.0" x 3.5" x 1.75"

P91 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P915SP15	90000877	Extended 5 Year Factory Warranty for P91c-1000, P91-1000, P91-1500	\$375.00
P915SP23	90000878	Extended 5 Year Factory Warranty for P91-2000, P91-3000	\$610.00
P91L5SPBP	90000879	Extended 5 Year Factory Warranty for P91-BP36, P91-BP36E, P91-BP48, P91-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal batteries		1		2		3		4		5		6		7	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
P91c-1000	20	8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91-1000	10	3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91-1500 (BP36)	10	3	42	17	84	33	120	51	157	72	199	93	244	112	289	128
P91-1500 (BP36E)	10	3	84	33	157	72	244	112	339	146	N/A	N/A	N/A	N/A	N/A	N/A
P91-2000 (BP48)	10	3	42	17	84	33	121	51	157	72	200	93	244	112	290	128
P91-3000 (BP72)	10	3	42	17	84	33	121	52	158	73	201	94	246	112	292	129

Maximum of seven battery packs per P91-1500, P91-2000, or P91-3000 (excluding BP36E). Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

P91 Li 1-3kVA UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Online 1500VA-3000VA 120VAC

High performance online UPS for critical network applications

- › Lithium-ion batteries
- › Up to 98% efficient operation
- › Multiple communications capability
- › Easy to replace battery design
- › Programmable Outlet Group
- › \$50,000 load protection policy
- › UL, cUL, RoHS, FCC A
- › 6 years electronics, 6 years battery warranty (USA and Canada)



P91 Li Series 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91-1.5kLi	90000750	1500VA/1350W 120V UPS with 8A Charger, 2U	\$2,520.00	6 ft, 5-15P	(8) NEMA 5-15R	25.6 lbs	17.2" x 15.1" x 3.5" 23.6" x 19.7" x 9.45"
P91-2kLi	90000751	2000VA/1800W 120V UPS with 8A Charger, 2U	\$3,730.00	6 ft, 5-20P	(8) NEMA 5-15/20R	33.5 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91-3kLi	90000752	3000VA/2700W 120V UPS with 8A Charger, 2U	\$4,570.00	6 ft, L5-30P	L5-30R + (6) 5-15/20R	45.2 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91-1.5kLi, 2kLi	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with P91-1.5kLi	\$379.00	5-15P, 12ft	(6) 5-15R front (4) 5-15R back	5-15R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass 20A/120VAC for use with P91-2kLi	\$419.00	5-20P, 12ft	(6) 5-20R front (4) 5-20R back	5-20R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass 30A/120VAC for use with P91-3kLi	\$659.00	L5-30P, 6ft	(6) 5-20R front (4) 5-20R back	L5-30R	3.4 lbs	19" x 3.5" x 1.75"

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XPD-1420HV	90000045	120V Basic Power Distribution Unit	\$190.00	L5–20P, 12ft or 5–20P with adapter	(14) 5–20R	4.8 lbs	19.0" x 3.5" x 1.75"

P91 Li Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Internal batteries											
Percentage load:	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	
P91-1.5kLi	111	54	34	25	19	16	13	11	9	8	
P91-2kLi	163	79	51	38	30	24	21	18	16	14	
P91-3kLi	127	62	40	29	23	19	16	14	12	11	

P91Li Advanced Exchange Warranty Upgrade

Model	Part Number	Description	List Price
P91ADVEX	90001036	Advanced Exchange Warranty Upgrade - Advanced Warranty Exchange and Shipping for P91(g)-1.5kLi, P91(g)-2kLi, and P91(g)-3kLi	\$250.00

Standard 6 Year Factory Warranty – 6 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way	Advanced Warranty Exchange – 6 years electronics/battery. Telephone technical support. Advanced warranty exchange. Ground shipment both ways. Pricing is limited to the continental USA
---	--

P91g 1-3kVA UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 1000VA-3000VA
208/230VAC

Premium power protection for mission critical applications

- › High output power factor
- › Up to 98% efficient operation
- › Extended battery packs available for 2U models
- › Multiple communications capability
- › Hot swappable battery design
- › Programmable Outlet Group (2U)
- › \$50,000 load protection policy
- › CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P91g Series 230V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91gc-1000	90000746	1000VA/800W 208/230V UPS with 1A Charger, 1U	\$1,050.00	C14 inlet, 8ft L6-20P to C13 line cord	(3) C13	28 lbs	17.2" x 17.8" x 1.7" 22.5" x 24.5" x 6.5"
P91g-1500	90000747	1500VA/1450W 208/230V UPS with 2A Charger, 2U	\$1,399.00	C14 inlet, 8ft L6-20P to C13 line cord	(8) IEC C13	34.2 lbs	17.2" x 15.1" x 3.5" 23.6" x 19.7" x 9.45"
P91g-2000	90000748	2000VA/1930W 208/230V UPS with 2A Charger, 2U	\$1,829.00	C20 inlet, 8ft L6-20P to C19 line cord	(8) IEC C13	43 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91g-3000	90000749	3000VA/2880W 208/230V UPS with 2A Charger, 2U	\$2,449.00	C20 inlet, 8ft L6-20P to C19 line cord	(1) IEC C19 + (8) IEC C13	60.6 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. Capacity derates to 90% at 208 output.

P91g Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91-BP36	90000787	36V Battery Pack for P91g-1500, 2U	\$920.00	58.1 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P91-BP36E	90000788	36V 4 String Extended Battery Pack for P91g-1500, 2U	\$1,320.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P91-BP48	90000789	48V Battery Pack for P91g-2000, 2U	\$1,080.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P91-BP72	90000790	72V Battery Pack for P91g-3000, P91g-3000, 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91g Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-C14-615R	IEC C14 to 6-15R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	208/230V	\$45.00	3 lbs
XPC-C14-620R	IEC C14 to 6-15/20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$49.00	2 lbs
XPC-C14-L620R	IEC C14 to L6-20R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-C14-L630R	IEC C14 to L6-30R for use with P91cg-1000, P91g-1500, P91g-2000, P91g-3000	1ft	200-240V	\$69.00	2 lbs
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P91g-3000	1ft	208/230V	\$79.00	3 lbs

P91g Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket (2U units)	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91g-1000, 1500, 2000	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P91g Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A capacity for use with P91g-3000 (includes (2) IEC C20 C19 cord kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P91g-3000	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P91g-1500, P91g-3000	\$600.00	208V IEC C14, 2ft	120V 5–15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$980.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)

P91g Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P905SP15	90000522	Extended 5 Year Factory Warranty for P91g-1500, P91gc-1000, P91g-1000, P91g-1500	\$375.00
P905SP23	90000523	Extended 5 Year Factory Warranty for P91g-2000, P91g-3000	\$610.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P91g Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal batteries		1		2		3		4		5		6		7		8	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
P91gc-1000	20	8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-1500 (BP36)	10	3	42	17	84	33	120	51	157	72	199	93	244	112	289	128	339	146
P91g-1500 (BP36E)	10	3	84	33	157	72	244	112	339	146	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P91g-2000 (BP48)	10	3	42	17	84	33	121	51	157	72	200	93	244	112	290	128	340	147
P91g-3000 (BP72)	10	3	42	17	84	33	121	52	158	73	201	94	246	112	292	129	343	148

Maximum of eight battery packs per P91g-1500, P91g-2000, or P91g-3000 (excluding BP36E). Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

P91g Li 1.5-3kVA UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Lithium Online 1500VA-3000VA

208/230VAC

High performance online UPS for critical network applications

- › Lithium-ion batteries
- › Up to 98% efficient operation
- › Multiple communications capability
- › Easy to replace battery design
- › Programmable Outlet Group
- › \$50,000 load protection policy
- › CE, RoHS
- › 6 years electronics, 6 years battery warranty (USA and Canada)



P91g Li Series 208/230V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P91g-1.5kLi	90000753	1500VA/1350W 208/230V UPS with 8A Charger, 2U	\$2,470.00	C14 inlet, 8 ft L6-20P to C13 line cord	(8) IEC C13	25.6 lbs	17.2" x 15.1" x 3.5" 23.6" x 19.7" x 9.45"
P91g-2kLi	90000754	2000VA/1800W 208/230V UPS with 8A Charger, 2U	\$3,680.00	C20 inlet, 8 ft L6-20P to C19 line cord	(8) IEC C13	33.5 lbs	17.2" x 19" x 3.5" 22.2" x 27.6" x 9.45"
P91g-3kLi	90000755	3000VA/2700W 208/230V UPS with 8A Charger, 2U	\$4,520.00	C20 inlet, 8 ft (2.4 m) L6-20P to C19 line cord	(1) IEC C19 + (8) IEC C13	45.2 lbs	17.2" x 23.8" x 3.5" 23.6" x 30.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P91g Li Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-C14-615R	IEC C14 to 6-15R for use with P91g-1kLi, P91g-1.5kLi, P91g-2kLi, P91g-3kLi	1ft	208/230V	\$45.00	3 lbs
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P91g-3kLi	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P91g-3kLi	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P91g-3kLi	1ft	208/230V	\$79.00	3 lbs

P91g Li Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$80.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P91g-1.5kLi, 2kLi	\$36.00	1 lb	0.9" x 2.0" x 3.4"

P91g Li Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A capacity for use with P91g-3000 (includes (2) IEC C20 C19 cord kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units and Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P91g-3000	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P91g-1500, P91g-3000	\$600.00	208V IEC C14, 2ft	120V 5–15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$980.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)

P91g Li Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Internal batteries											
Percentage load:	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	
P91g-1.5kLi	111	54	34	25	19	16	13	11	9	8	
P91g-2kLi	163	79	51	38	30	24	21	18	16	14	
P91g-3kLi	127	62	40	29	23	19	16	14	12	11	

P91Li Advanced Exchange Warranty Upgrade

Model	Part Number	Description	List Price
P91ADVEX	90001036	Advanced Exchange Warranty Upgrade - Advanced Warranty Exchange and Shipping for P91(g)-1.5kLi, P91(g)-2kLi, and P91(g)-3kLi	\$250.00

Standard 6 Year Factory Warranty – 6 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way

Advanced Warranty Exchange – 6 years electronics/battery. Telephone technical support. Advanced warranty exchange. Ground shipment both ways. Pricing is limited to the continental USA

P90L Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 1500VA-3000VA

120VAC or 208/230VAC

Online UPS with a powerful charger for extended battery runtimes

- › 98% efficient operation
- › Smart LCD display
- › Multiple communications capability
- › Programmable outlets
- › \$50,000 load protection policy
- › UL, cUL, CE, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P90L Series UPS 120V 50/60Hz

P90L Series have 6A chargers with no internal batteries.

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90L-1500	90000912	1250VA/1125W 120V UPS Module with 246W 36V Nominal Charger, 2U	\$1,450.00	5-15P, 6ft	(8) 5-15R	33 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P90L-2000	90000913	1700VA/1530W 120V UPS Module with 328W 48V Nominal Charger, 2U	\$1,675.00	5-20P, 6ft	(8) 5-15/20R	35 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P90L-3000	90000914	2500VA/2250W 120V UPS Module with 493W 72V Nominal Charger, 2U	\$2,525.00	L5-30P, 6ft	(1) L5-30R + (4) 5-15/20R	47 lbs	17.2" x 25.8" x 3.5" 23.6" x 31.5" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P90Lg Series UPS 208/230V 50/60Hz

P90Lg-3000 has a 6A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90Lg-3000	90000921	3000VA/2400W 208/230V UPS Module with 6A Charger, 2U	\$2,490.00	IEC C19 to L6-20P, 8ft	(1) IEC C19 + (6) IEC C13	47 lbs	17.2" x 25.8" x 3.5" 23.6" x 29.9" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P90L Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90-BP36	90000915	36V Battery Pack for P90L-1500, 2U	\$920.00	58.1 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"
P90-BP36E	90000923	36V 4 String Extended Battery Pack for P90L-1500, 2U	\$1,320.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P90-BP48	90000916	48V Battery Pack for P90L-2000, 2U	\$990.00	74.6 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P90-BP72	90000917	72V Battery Pack for P90L-3000, P90Lg-3000, 2U	\$1,290.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel.

P90Lg Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R for use with P90Lg-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R for use with P90Lg-3000	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P90Lg-3000	1ft	208/230V	\$79.00	3 lbs
XPC-C14-615R	IEC C14 to 6-15R for use with P90Lg-3000	1ft	208/230V	\$59.00	3 lbs

P90L Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$135.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$102.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"

P90L Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass 15A/120VAC for use with P90L-1500	\$379.00	5–15P, 12ft	(10) 5–15R	5–15R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass 20A/120VAC for use with P90L-2000	\$419.00	5–20P, 12ft	(10) 5–20R	5–20R	3.4 lbs	19" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass 30A/120VAC for use with P90L-3000, P90Lg-3000	\$659.00	L5–30P, 6ft	(10) 5–20R	L5–30R	3.4 lbs	19" x 3.5" x 1.75"
XBDM1020HV2	90000094	Bypass 16A Capacity for use with P90Lg-3000 (Includes (2) IEC C20 C19 Cord Kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (8) IEC C13	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD-1415HV	90000041	120V Basic Power Distribution Unit	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XPD-1420HV	90000045	120V Basic Power Distribution Unit	\$190.00	L5–20P, 12ft or 5–20P with adapter	(14) 5–20R	4.8 lbs	19.0" x 3.5" x 1.75"
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P90Lg-3000	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P90Lg-3000	\$600.00	208V IEC C14, 2ft	120V 5–15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"

P90L Service Plans (USA and Canada)

Model	Part Number	Description	List Price
P90L5SP15	90000527	Extended 5 Year Factory Warranty for P90L-1500 UPS	\$370.00
P90L5SP23	90000528	Extended 5 Year Factory Warranty for P90L-2000, P90L-3000, P90Lg-3000 UPS	\$610.00
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P90L Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	P90L-1500 (BP36)		P90L-1500 (BP36E)		P90L-2000 (BP48)		P90L(g)-3000 (BP72)	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%
(1) Battery pack	26	15	63	36	25	14	23	13
(2) Battery packs	63	36	140	90	61	35	58	33
(3) Battery packs	105	61	228	136	102	60	97	56
(4) Battery packs	140	90	322	193	137	88	130	84
(5) Battery packs	183	115	N/A	N/A	179	113	169	107
(6) Battery packs	228	136	N/A	N/A	223	133	211	128
(7) Battery packs	274	164	N/A	N/A	268	160	254	152
(8) Battery packs	322	193	N/A	N/A	314	188	298	178

T91 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 700VA-3000VA

120VAC or 230VAC

Unity power factor tower UPS provides high density online power protection for unstable power conditions

- › Online double conversion technology
- › Unity output power factor
- › Multiple communications capability
- › Controlled load segment
- › Adjustable charging current from 2A to 8A
- › Extended battery packs available
- › UL, cUL, CE, RoHS, FCC B, FCC A (varies by model), TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



T91 Series 120V 50/60Hz

UL, cUL, FCC A or B, RoHS, TAA Compliant

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
T91-700	90000480	700VA/700W 120V Tower UPS	\$769.00	5-15P, 6 ft	(6) 5-15R	25.7 lbs	5.6" x 15.6" x 8.6"
T91-1000	90000481	1000VA/1000W 120V Tower UPS	\$949.00	5-15P, 6 ft	(6) 5-15R	30 lbs	5.6" x 15.6" x 8.6"
T91-1500	90000482	1500VA/1450W 120V Tower UPS	\$1,149.00	5-15P, 6 ft	(6) 5-15R	34.3 lbs	5.6" x 15.6" x 8.6"
T91-2000	90000483	2000VA/1930W 120V Tower UPS	\$1,539.00	L5-20P, 6ft	(1) L5-20R + (8) 5-20R	63 lbs	7.4" x 16.5" x 12.5"
T91-2000V2	90001242	2000VA/1930W 120V Tower UPS	\$1,539.00	5-20P, 6 ft	(1) L5-20R + (8) 5-20R	63 lbs	7.4" x 16.5" x 12.5"
T91-3000	90000484	3000VA/2880W 120V Tower UPS	\$1,979.00	L5-30P, 6 ft	(1) L5-30R + (8) 5-20R	66 lbs	7.4" x 16.5" x 12.5"

T91i Series 208/230V 50/60Hz

CE, RoHS, TAA Compliant

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
T91i-2000	90000485	2000VA/2000W 230V Tower UPS	\$1,629.00	C19 to L6-20P, 8 ft	(1) C19 + (8) C13	62 lbs	7.4" x 16.5" x 12.5"
T91i-3000	90001214	3000VA/3000W 230V Tower UPS	\$2,149.00	C19 to L6-20P, 8 ft	(1) C19 + (8) C13	66 lbs	7.4" x 16.5" x 12.5"

T91 Extended Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
T91-BP36A	90000486	Extended Battery Pack for T91-1000, T91-1500	\$699.00	44 lbs	5.6" x 15.6" x 8.6"
T91-BP72A	90000487	Extended Battery Pack for T91-2000/(V2), T91i-2000, T91-3000, T91i-3000	\$1,259.00	82 lbs	7.4" x 16.5" x 12.5"

T91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

T91 Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
T90-WMB	90000389	Wall Mount Bracket for use with T91-700, T91-1000, T91-1500 Rated for 40 lbs	\$219.00	5 lbs	4.0"-8.0" x 7.0" x 8.0"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with T91i-2000, T91i-3000	\$600.00	208V IEC C14, 2ft	120V 5-15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"

T91 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
T915SP715	90000488	Extended 5 Year Factory Warranty for T91-700, T91-1000, T91-1500, UPS	\$350.00
T915SP23	90000489	Extended 5 Year Factory Warranty for T91-2000/(V2), T91i-2000, T91-3000, T91i-3000 UPS	\$575.00
T915SPBP	90000490	Extended 5 Year Factory Warranty for T91 extended battery packs	\$320.00

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

T91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	T91-700		T91-1000		T91-1500		T91-2000/(V2)		T91i-2000		T91-3000		T91i-3000	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
Internal batteries	16	5.6	17	6	10	3	18	6.4	17	6	10	3	9	2
(1) Battery pack	N/A	N/A	74	29	44	18	77	30	74	29	45	18	40	16
(2) Battery packs	N/A	N/A	129	57	88	35	133	59	129	57	89	35	80	32
(3) Battery packs	N/A	N/A	192	89	125	54	200	93	192	89	126	54	116	49
(4) Battery packs	N/A	N/A	259	117	165	77	270	121	259	117	167	78	150	68
(5) Battery packs	N/A	N/A	330	143	211	97	350	149	330	143	212	97	191	90
(6) Battery packs	N/A	N/A	419	175	258	117	437	183	419	175	260	118	234	107
(7) Battery packs	N/A	N/A	485	208	306	133	500	217	485	208	309	134	278	124

P91 5kVA–10kVA Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online Unity Power Factor 5kVA–10kVA

208/230VAC or 240/120VAC

More Power in Less Space with Lead Acid Batteries

- › Multiple communications capability
- › Up to 94% online or 99% ECO mode efficiency
- › P91 optional battery packs are easy to replace without interrupting the load
- › \$50,000 load protection policy
- › UL 1778, cUL, FCC, RoHS, CE, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



P91 208/230VAC Bundle Pricing

Bundles include 4-post rail kits. 6kVA system capacity will be reduced by 30A input circuit.

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Total Weight	Rack Space
P91-5KB	Bundle	5kVA/5kW UPS Bundle with 2U Battery Pack	\$4,658.00	Terminal block	Terminal block	163 lbs	4U
P91-5KB1	Bundle	5kVA/5kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91A	\$5,546.00	L6–30P, 6ft	(2) L6–20R + (2) L6–30R	173 lbs	4U
P91-5KB2	Bundle	5kVA/5kW UPS Bundle with 3U Battery Pack	\$5,078.00	Terminal block	Terminal block	203 lbs	5U
P91-5KB3	Bundle	5kVA/5kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91A	\$5,966.00	L6–30P, 6ft	(2) L6–20R + (2) L6–30R	113 lbs	5U
P91-6KB	Bundle	6kVA/6kW UPS Bundle with 2U Battery Pack	\$5,048.00	Terminal block	Terminal block	164 lbs	4U
P91-6KB1	Bundle	6kVA/6kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91A	\$5,936.00	L6–30P, 6ft	(2) L6–20R + (2) L6–30R	174 lbs	4U
P91-6KB2	Bundle	6kVA/6kW UPS Bundle with 3U Battery Pack	\$5,468.00	Terminal block	Terminal block	204 lbs	5U
P91-6KB3	Bundle	6kVA/6kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91A	\$6,356.00	L6–30P, 6ft	(2) L6–20R + (2) L6–30R	214 lbs	5U
P91-10KB	Bundle	10kVA/10kW UPS Bundle with 3U Battery Pack	\$6,548.00	Terminal block	Terminal block	210 lbs	5U
P91-10KB1	Bundle	10kVA/10kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91B	\$7,436.00	Terminal block	Terminal block + (1) L6–30R + (2) L6–20R	218 lbs	5U
P91-10KB2	Bundle	10kVA/10kW UPS Bundle with 2U Battery Pack	\$6,128.00	Terminal block	Terminal block	170 lbs	4U
P91-10KB3	Bundle	10kVA/10kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91B	\$7,016.00	Terminal block	Terminal block + (1) L6–30R + (2) L6–20R	178 lbs	4U

P91 240/120V Bundle Pricing

Bundles include isolation transformer and 4-post rail kits. 6kVA system capacity will be reduced by 30A input circuit.

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Total Weight	Rack Space
P91-5KTB	Bundle	5kVA/5kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91A and XPD-IT60A transformer	\$7,865.00	Terminal block + L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (12) 5-15/20R	315.1 lbs	6U
P91-5KTB2	Bundle	5kVA/5kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91C and XPD-IT6kW transformer	\$7,847.00	Terminal block + L6-30P, 6ft	Terminal Block, (1) L6-30R, (2) L14-30, (8) 5-15/20R	315.1 lbs	7U
P91-5KTB3	Bundle	5kVA/5kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91A and XPD-IT60A transformer	\$8,283.00	Terminal block + L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (12) 5-15/20R	355.1 lbs	7U
P91-5KTB4	Bundle	5kVA/5kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91C and XPD-IT6kW transformer	\$8,267.00	Terminal block + L6-30P, 6ft	Terminal Block, (1) L6-30R, (2) L14-30, (8) 5-15/20R	355.1 lbs	8U
P91-6KTB	Bundle	6kVA/6kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91A and XPD-IT60A transformer	\$8,255.00	Terminal block + L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (12) 5-15/20R	316 lbs	6U
P91-6KTB2	Bundle	6kVA/6kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91C and XPD-IT6kW transformer	\$8,237.00	Terminal block + L6-30P, 6ft	Terminal Block, (1) L6-30R, (2) L14-30, (8) 5-15/20R	316 lbs	7U
P91-6KTB3	Bundle	6kVA/6kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91A and XPD-IT60A transformer	\$8,675.00	Terminal block + L6-30P, 6ft	(2) L6-20R + (2) L6-30R + (12) 5-15/20R	356 lbs	7U
P91-6KTB4	Bundle	6kVA/6kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91C and XPD-IT6kW transformer	\$8,657.00	Terminal block + L6-30P, 6ft	Terminal Block, (1) L6-30R, (2) L14-30, (8) 5-15/20R	356 lbs	8U
P91-10KTB	Bundle	10kVA/10kW UPS Bundle with 3U Battery Pack and Plug/Receptacle XBDM-P91B and XPD-IT60A transformer	\$9,755.00	Terminal block	(2) L6-20R + (1) L6-30R + (12) 5-15/20R	359.7 lbs	7U
P91-10KTB1	Bundle	10kVA/10kW UPS Bundle with 2U Battery Pack and Plug/Receptacle XBDM-P91B and XPD-IT60A transformer	\$8,920.00	Terminal block	(2) L6-20R + (1) L6-30R + (12) 5-15/20R	319.7 lbs	6U

P91 Series UPS 208/230V50/60Hz

P91 Series UPS come with no internal batteries. 6kVA system capacity will be reduced by 30A input circuit.

Model	Part Number	Description	List Price	Input Connections	Output Connections	Weight	Unit Dimensions (W x D x H)
P91-5K	90000640	5kVA/5kW 208/230V UPS Module, 2U	\$2,310.00	Terminal block	Terminal block	33.1 lbs	17.2" x 23.6" x 3.5"
P91-6K	90000641	6kVA/6kW 208/230V UPS Module, 2U	\$2,700.00	Terminal block	Terminal block	34 lbs	17.2" x 23.6" x 3.5"
P91-10K	90000642	10kVA/10kW 208/230V UPS Module, 2U	\$3,780.00	Terminal block	Terminal block	39.7 lbs	17.2" x 23.6" x 3.5"

P91 Battery Packs

Battery packs include DC Breaker, and cable with connector

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
BPXR2U240A	90000643	(20) 12V 5AH Lead Acid Battery Pack, 2U	\$2,050.00	120 lbs	17.2" x 30" x 3.5"
BPXR3U240A	90000644	(20) 12V 580W Lead Acid Battery Pack, 3U	\$2,470.00	160 lbs	17.2" x 30" x 5.2"

Bypass Distribution Modules

Mating Anderson cable kit included for connection to the UPS input and output

Model	Part Number	Description	List Price	Input Connections	Output Connections	Weight	Unit Dimensions (W x D x H)
XBDM-P91A	90000645	Plug and Receptacle Distribution Module	\$730.00	L6-30P (5kVA, 6kVA)	(2) L6-30R short cords, each protected by a breaker + (2) C19 flush mounted, each protected by a 20A breaker	8 lbs	14.6" x 5" x 3.5"
XBDM-P91B	90000646	Receptacle Bypass Distribution Module	\$730.00	Terminal block	Terminal block + (1) L6-30R short cord, protected by a breaker + (2) C19 flush mounted, each protected by a breaker	6 lbs	14.6" x 5" x 3.5"
XBDM-P91C	90000737	Receptacle Bypass Distribution Module	\$730.00	Terminal block	Terminal block + (1) L6-30R short cord, protected by a breaker	5 lbs	14.6" x 5" x 3.5"
XBDM-P91D	90000738	Receptacle Bypass Distribution Module	\$730.00	Terminal block	(2) L6-30R short cords, each protected by a breaker	6 lbs	14.6" x 5" x 3.5"

P91 Cords Options

For use with Xtreme Bypass Distribution Modules (XBDM) with C19 output. 6kVA system capacity will be reduced by 30A input circuit.

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6–30R	1ft	208/230V	\$79.00	3 lbs
XPC-C20-L615R	Non-locking IEC C20 to L6–15R	1ft	208/230V	\$59.00	3 lbs
XPC-L630R	L6–30R Factory Terminated to Output TB	6ft	208/230V	\$125.00	5 lbs
XPC-L630P	L6–30P Factory Terminated to Input TB	6ft	208/230V	\$125.00	5 lbs

P91 Isolation Transformers

Model	Part Number	Description	List Price	Weight	Unit Dimensions (W x D x H)
XPD-IT60A	90000407	6kVA PDU with Isolation Transformer 208V to 120V (or 240V to 120V), 3ft L6–30P Input Cord, (1) L6–30R and (12) 5–15/20R receptacles	\$2,150.00	137 lbs	19.0" x 18.0" x 3.5"
XPD-IT6KW	90000781	6kVA 3U PDU with Isolation Transformer 208V to 240/120V (or 240V to 240/120V), Input terminal block, Output terminal block + (2) L14-30R and (8) 5–15/20R receptacles	\$2,310.00	199 lbs	17.3" x 32.8" x 4.7"
XPD-IT10KW	90000740	10kVA 3U PDU with Isolation Transformer 208V to 240/120V (or 240V to 240/120V), Input terminal block, Output terminal block + (2) L14-30R and (8) 5–15/20R receptacles	\$2,760.00	209 lbs	17.3" x 32.8" x 4.7"

P91 Mounting Kits

Model	Part Number	Description	List Price	Weight	Unit Dimensions (W x D x H)
P90L-RAIL	90000933	4-Post Rail Kit	\$149.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$160.00	9 lbs	21.5" x 23.3" x 3.5"
XPC-2POST	90003042	Heavy Duty 2-Post Shelf Kit; Rated for 300 lbs	\$270.00	14 lbs	19.0" x 29.0" x 5.2"

P91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2	90000674	Environmental Monitoring Sensor*	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 to be used with SNMP-2PV3

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Weight	Unit Dimensions (W x D x H)
XPD24C13V	90000374	30A 208V Basic PDU	\$340.00	L6–30P, 6ft	(24) IEC C13	12.0 lbs	66.0" x 1.75" x 1.75"
XPD31	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (2) L6–20R + (4) 6–15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (4) L6–20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6–30P, 6ft	(4) IEC C19 + (8) IEC C14	6.0 lbs	19.0" x 2.4" x 3.5"
XPD35	90000255	50A 240V 2U 19" Basic Rack PDU	\$580.00	Pigtail 2W+G	(2) L6–30R + (4) L6–20R	7.0 lbs	19.0" x 2.4" x 3.5"
XPD36	90000256	50A 240V 2U 19" Basic Rack PDU	\$460.00	Pigtail 2W+G	(4) IEC C19 + (8) IEC C13	6.8 lbs	19.0" x 2.4" x 3.5"

P91 Startup/Service Plans (USA and Canada)

On-site service within 100 miles of an Xtreme Power Service Technician. Contact inside sales for locations exceeding 100 miles.

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	M90S preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

On-site 3 Year Service Plan – 3 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

On-site 5 Year Service Plan – 5 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

P91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

		Qty	1kW	2kW	3kW	4kW	5kW	6kW	7kW	8kW	9kW	10kW
Model Number	BPXR2U240A	1 BP	53	27	15	11	7	5	4	4	3	2
Dimensions	17.2 x 27.4 x 3.5 in (2U)	2 BP	117	61	38	27	20	15	13	11	9	7
Battery Quantity/Type	(20) 12V 5AH Lead Acid	3 BP	171	100	62	43	33	27	22	18	15	13
Model Number	BPXR3U240A	1 BP	92	46	29	20	15	12	10	8	7	6
Dimensions	17.2 x 27.4 x 5.2 in (3U)	2 BP	182	106	66	47	36	29	24	20	18	15
Battery Quantity/Type	(20) 12V 580W Lead Acid	3 BP	287	151	107	76	58	47	39	33	29	25
		4 BP	395	208	134	107	83	66	55	47	41	36
		5 BP	507	267	172	128	107	87	72	61	53	47
		6 BP	621	327	211	153	124	107	90	76	66	58
		7 BP	738	388	250	182	142	122	107	92	80	70
		8 BP	857	451	291	211	164	134	120	107	94	83

M90S-2S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online UPS

Capacity: 6kVA/6kW

208/120VAC Single-phase

Mission Critical Availability while reducing costs with Scalable, Modular M90S for 6kVA applications

- › Unity power factor
- › Hardwired or plug & receptacle configurations
- › Up to 98% ECO mode or 93% online efficiency
- › UL-1778 (TUV), cUL, FCC A, RoHS
- › 3 years electronic, 3 years battery warranty (USA and Canada)



M90S-2S Series 208/120VAC Single-phase 2 Slot

M90S-2S bundles include UPS power module, battery module, and 2-slot enclosure with integral maintenance bypass.

Line cord and receptacle panel are optional.

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90S-2S6K	Bundle	6kVA/6kW rack system with rail kit and 1 battery pack	\$8,240	Hardwired	185 lbs	17.5"W x 33.5"D x 10.5"H
M90S-2S6KT	Bundle	6kVA/6kW tower system with caster base and 1 battery pack	\$8,695	Hardwired	198 lbs	17.4"W x 33.7"D x 14.5"H

For panel configurations, see below.

M90S Receptacle Panels

Add panel needed to part number above. Example: M90S-2S6KB33 (M90S-2S6K with panel B and (2) L6-30R). 1 receptacle panel per 2 slot enclosure.

Model	Part No	Panel	Description	Additional Receptacle Options	Unit Weight	Price	Unit Dimensions (W x D x H)
M90S-RPA	90000699	A	(8) 5-20R	N/A	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPB	90000700	B	(4) 5-20R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPC	90000701	C	L6-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPD	90000702	D	L14-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPE	Bundle	E	(2) L6-20R + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPF	Bundle	F	L6-20R + L6-30R* + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPG	Bundle	G	L6-30R + (2) L6-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPH	Bundle	H	(3) L6-30R*	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H

*Dongle options: 208V/240V 1 - L6-15R, 2 - L6-20R, 3 - L6-30R, 4 - 6-15/20R. Add the dongle option number after the panel letter. Each configurable output is protected by a 20A breaker.

M90S Series Battery Cabinet Bundles

M90S-BC7 tower bundles include battery enclosure and battery modules.

Model	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90S-BC7-1	M90S 7 slot battery cabinet with one battery module	\$7,408	269 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-2	M90S 7 slot battery cabinet with two battery modules	\$9,440	376 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-3	M90S 7 slot battery cabinet with three battery modules	\$11,472	483 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-4	M90S 7 slot battery cabinet with four battery modules	\$13,504	590 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-5	M90S 7 slot battery cabinet with five battery modules	\$15,536	697 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-6	M90S 7 slot battery cabinet with six battery modules	\$17,568	804 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-7	M90S 7 slot battery cabinet with seven battery modules	\$19,600	911 lbs	17.4" x 33.7" x 45.5"

M90S BC7 battery cabinets are tower configuration only. All BC7 bundles include blank panels for slots that do not have battery modules.

M90S-2S Series Component pricing

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
M90S-PWM6	90000693	6kVA power module	\$4,190	38 lbs	23"W x 35"D x 10"H
M90S-BMXRV2	90001262	Battery module with breaker	\$2,095	107 lbs	23"W x 35"D x 10"H
M90S-ENC2	90000690	M90S 2 slot enclosure	\$1,800	34 lbs	23"W x 31.5"D x 15"H
M90S-RAIL2S	90000695	2 slot enclosure rail kit	\$155	5 lbs	20"W x 4"D x 2.5" H
M90S-BC7	90000696	M90S 7 slot tower battery cabinet	\$4,935	162 lbs	40"W x 25"D x 54"H
XPC-L14-30P*	90000717	8 ft L14-30P input cord	\$135	10 lbs	4"W x 4"D x 6"H
M90S-CB	90000719	Caster base for M90S-2S enclosure	\$610	18 lbs	17"W x 24"D x 5"H
M90S-BP	90000703	Matching front blank panel	\$63	5 lbs	16.5"W x 2"D x 5.2"H

*30A line cord limits UPS capacity to 24A continuous UPS input

M90S-2S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-M90S	90000698	Internal SNMP card	\$339	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Environmental monitoring device*	\$180	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	Relay card	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-EMD to be used with SNMP-M90S

M90S Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6–30R protected by a 20A breaker	1ft	208/230V	\$79	3 lbs
XPC-C20-L615R	C20 to L6–15R	1ft	208/230V	\$59	3 lbs

M90S Service Plans (USA and Canada)

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	M90S preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

*Service adder (SVCADD) must be added for all on-site service plans for locations further than 100 miles from a metropolitan area.

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Depot Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

BATTERY RUNTIMES

Battery Modules	1		2		3		4		5		6		7		8	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
M90S-2S6K	21	9	49	22	80	35	111	50	131	66	160	82	189	99	220	113

Runtimes are shown in minutes and will vary based on battery age and site conditions. Maximum 8 battery modules per UPS power module.

M90S-4S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Two capacities: 6kVA/6kW, 12kVA/12kW

208/120VAC Single-phase

Mission Critical Availability while reducing costs with Scalable, Modular M90S for 6kVA to 12kVA applications

- › Modular for capacity or redundancy
- › Hot swappable power and battery modules
- › Hardwired or plug & receptacle configurations
- › Up to 98% ECO mode or 93% online efficiency
- › Large LCD display
- › UL-1778 (TUV), cUL, FCC A, RoHS
- › 3 years electronic, 3 years battery warranty (USA and Canada)



M90S-4S Series 208/120VAC single-phase 4 Slot

M90S-4S Bundles include UPS power module(s), battery module(s), large LCD display, blank panels for open slots, and 4-slot enclosure with front facing integral maintenance bypass. 4-slot enclosure can have up to 2 optional receptacle panels.

Model	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90S-4S6K1	6kVA/6kW system with 1 battery module	\$11,211	Terminal block and/or up to 2 optional receptacle panels	275 lbs	17.4" x 33.7" x 33"
M90S-4S6K2	6kVA/6kW system with 2 battery modules	\$13,243	Terminal block and/or up to 2 optional receptacle panels	382 lbs	17.4" x 33.7" x 33"
M90S-4S6K3	6kVA/6kW system with 3 battery modules	\$15,275	Terminal block and/or up to 2 optional receptacle panels	489 lbs	17.4" x 33.7" x 33"
M90S-4S12K2	12kVA/12kW system with 2 battery modules	\$17,370	Terminal block and/or up to 2 optional receptacle panels	420 lbs	17.4" x 33.7" x 33"

For panel configurations, see below.

M90S Receptacle Panels

Add panel needed to part number above. Example: M90S-4S12K1AC23 (M90S-4S12K1 with panel A, C with (1) L6-20R and (1) L6-30R). Maximum of 2 receptacle panels per 4 slot enclosure.

Model	Part No	Panel	Description	Additional Receptacle Options	Unit Weight	Price	Unit Dimensions (W x D x H)
M90S-RPA	90000699	A	(8) 5-20R	N/A	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPB	90000700	B	(4) 5-20R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPC	90000701	C	L6-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPD	90000702	D	L14-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPE	Bundle	E	(2) L6-20R + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPF	Bundle	F	L6-20R + L6-30R* + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPG	Bundle	G	L6-30R + (2) L6-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPH	Bundle	H	(3) L6-30R*	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H

*Dongle options: 208V/240V: 1 - L6-15R, 2 - L6-20R, 3 - L6-30R, 4 - 6-15/20R. Add the dongle option number after the panel letter. Each configurable output is protected by a 20A breaker.

M90S Series Battery Cabinet Bundles

M90S-BC7 tower bundles include battery enclosure and battery modules

Model	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90S-BC7-1	M90S 7 slot battery cabinet with one battery module	\$7,408	269 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-2	M90S 7 slot battery cabinet with two battery modules	\$9,440	376 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-3	M90S 7 slot battery cabinet with three battery modules	\$11,472	483 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-4	M90S 7 slot battery cabinet with four battery modules	\$13,504	590 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-5	M90S 7 slot battery cabinet with five battery modules	\$15,536	697 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-6	M90S 7 slot battery cabinet with six battery modules	\$17,568	804 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-7	M90S 7 slot battery cabinet with seven battery modules	\$19,600	911 lbs	17.4" x 33.7" x 45.5"

M90S BC7 battery cabinets are tower configuration only. All BC7 bundles include blank panels for slots that do not have battery modules.

M90S-4S Series Component pricing

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
M90S-PWM6	90000693	6kVA power module	\$4,190	38 lbs	35"W x 23"D x 10"H
M90S-BMXRV2	90001262	Battery module with breaker	\$2,095	107 lbs	23"W x 35"D x 10"H
M90S-ENC4	90000691	M90S 4 slot enclosure	\$4,800	130 lbs	40"W x 25"D x 40"H
M90S-BC7	90000696	M90S 7 slot tower battery cabinet	\$4,935	162 lbs	40"W x 25"D x 54"H
XPC-L14-30P*	90000717	8 ft L14-30P input cord (6kVA only)	\$135	10 lbs	4"W x 4"D x 6"H
M90S-BP	90000703	Matching front blank panel	\$63	5 lbs	16.5"W x 2"D x 5.2"H
M90-SEIS	90000678	Seismic hold down anchorage	\$1,900	TBA	TBA

*30A line cord limits UPS capacity to 24A continuous UPS input

M90S-4S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-M90S	90000698	Internal SNMP card	\$339	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Environmental monitoring device*	\$180	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	Relay card	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-EMD to be used with SNMP-M90S

M90S Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R protected by a 20A breaker	1ft	208/230V	\$79	3 lbs
XPC-C20-L615R	C20 to L6-15R	1ft	208/230V	\$59	3 lbs

M90S Service Plans (USA and Canada)

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	M90S preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

*Service adder (SVCADD) must be added for all on-site service plans for locations further than 100 miles from a metropolitan area.

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Depot Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

BATTERY RUNTIMES

Battery Modules	4S UPS			4S UPS + 1 BC7							4S UPS + 2 BC7					
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
6kW	9	22	35	50	66	82	99	113	124*	133*	148*	163*	179*	194*	209*	220*
12kW	-	9	15	22	28	35	43	50	58	66	74	82	90	99	106	113

Runtimes are shown in minutes and will vary based on battery age and site conditions. Maximum of 8 battery modules per UPS power module.

*Additional power module required for battery recharge.

M90S-6S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Four capacities: 6kVA/6kW, 12kVA/12kW, 18kVA/18kW, 24kVA/24kW

208/120VAC Single-phase

Mission Critical Availability while reducing costs with Scalable, Modular M90 for 6kVA to 24kVA applications

- › Modular for capacity or redundancy
- › Hot swappable power and battery modules
- › Hardwired or plug & receptacle configurations
- › Up to 98% ECO mode or 93% online efficiency
- › Large LCD display
- › UL-1778 (TUV), cUL, FCC A, RoHS
- › 3 years electronic, 3 years battery warranty (USA and Canada)



M90S Series 208/120VAC Single-phase 6 Slot

M90S-6S Bundles include UPS power module(s), battery module(s), large LCD display, blank panels for open slots, and 6-slot enclosure with front facing integral maintenance bypass. 6-slot enclosure can have up to 4 optional receptacle panels.

Model	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90S-6S6k1	6kVA/6kW system with one battery module	\$13,787	Terminal block and/or up to 4 optional receptacle panels	314 lbs	17.4" x 33.7" x 45.5"
M90S-6S6k2	6kVA/6kW system with two battery modules	\$15,819	Terminal block and/or up to 4 optional receptacle panels	421 lbs	17.4" x 33.7" x 45.5"
M90S-6S6k3	6kVA/6kW system with three battery modules	\$17,851	Terminal block and/or up to 4 optional receptacle panels	528 lbs	17.4" x 33.7" x 45.5"
M90S-6S6k4	6kVA/6kW system with four battery modules	\$19,883	Terminal block and/or up to 4 optional receptacle panels	635 lbs	17.4" x 33.7" x 45.5"
M90S-6S6k5	6kVA/6kW system with five battery modules	\$21,915	Terminal block and/or up to 4 optional receptacle panels	742 lbs	17.4" x 33.7" x 45.5"
M90S-6S12k2	12kVA/12kW system with two battery modules	\$19,946	Terminal block and/or up to 4 optional receptacle panels	459 lbs	17.4" x 33.7" x 45.5"
M90S-6S12k3	12kVA/12kW system with three battery modules	\$21,978	Terminal block and/or up to 4 optional receptacle panels	566 lbs	17.4" x 33.7" x 45.5"
M90S-6S12k4	12kVA/12kW system with four battery modules	\$24,010	Terminal block and/or up to 4 optional receptacle panels	673 lbs	17.4" x 33.7" x 45.5"
M90S-6S18k3	18kVA/18kW system with three battery modules	\$26,105	Terminal block and/or up to 4 optional receptacle panels	604 lbs	17.4" x 33.7" x 45.5"
M90S-6S24k4	24kVA/24kW system with four battery modules in a BC7 enclosure	\$39,798	Terminal block and/or up to 4 optional receptacle panels	535 lbs (UPS) 376 lbs (BC7)	17.4" x 33.7" x 45.5" (UPS) 17.4" x 33.7" x 45.5" (BC7)

For panel configurations, see below.

M90S Receptacle Panels

Add panel needed to part number above. Example: M90S-6S18K2AB33EG (M90S-6S18K2 with panel A, B with (2) L6-30R, E, and G). Maximum of 4 receptacle panels per 6 slot enclosure.

Model	Part No	Panel	Description	Additional Receptacle Options	Unit Weight	Price	Unit Dimensions (W x D x H)
M90S-RPA	90000699	A	(8) 5-20R	N/A	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPB	90000700	B	(4) 5-20R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPC	90000701	C	L6-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPD	90000702	D	L14-30R + (2) C19*	*choose up to 2 dongles	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPE	Bundle	E	(2) L6-20R + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPF	Bundle	F	L6-20R + L6-30R* + (4) 5-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPG	Bundle	G	L6-30R + (2) L6-20R	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPH	Bundle	H	(3) L6-30R*	N/A	8 lbs	\$453	16.5"W x 2"D x 5.2"H

*Dongle options: 208V/240V: 1 - L6-15R, 2 - L6-20R, 3 - L6-30R, 4 - 6-15/20R. Add the dongle option number after the panel letter. Each configurable output is protected by a 20A breaker.

M90S Series Battery Cabinet Bundles

M90S-BC7 tower bundles include battery enclosure and battery modules

Model	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90S-BC7-1	M90S 7 slot battery cabinet with one battery module	\$7,408	269 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-2	M90S 7 slot battery cabinet with two battery modules	\$9,440	376 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-3	M90S 7 slot battery cabinet with three battery modules	\$11,472	483 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-4	M90S 7 slot battery cabinet with four battery modules	\$13,504	590 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-5	M90S 7 slot battery cabinet with five battery modules	\$15,536	697 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-6	M90S 7 slot battery cabinet with six battery modules	\$17,568	804 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-7	M90S 7 slot battery cabinet with seven battery modules	\$19,600	911 lbs	17.4" x 33.7" x 45.5"

M90S BC7 battery cabinets are tower configuration only. All BC7 bundles include blank panels for slots that do not have battery modules.

BATTERY RUNTIMES

Battery Modules	6S UPS					6S UPS + 1 BC7							6S UPS + 2 BC7			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
6kW	9	22	35	50	66	82	99	113	-	-	-	-	-	-	-	-
12kW	-	9	15	22	28	35	43	50	58	66	74	82	90	99	106	113
18kW	-	-	9	13	17	22	26	31	35	40	45	50	55	61	66	71
24kW	-	-	-	9	12	15	19	22	25	28	32	35	39	43	46	50

Battery Modules	6S UPS + 2 BC7					6S UPS + 4 BC7							6S UPS + 5 BC7			
	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
6kW	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
12kW	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
18kW	77	82	88	93	99	104	109	113	-	-	-	-	-	-	-	-
24kW	54	58	62	66	70	74	78	82	86	90	95	99	103	106	110	113

Runtimes are shown in minutes and will vary based on battery age and site conditions. Maximum 8 battery modules per UPS power module.

*Additional power module required for battery recharge. For additional runtime options, visit the UPS selector at www.xpcc.com/selector or contact sales@xpcc.com

M90S-6S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-M90S	90000698	Internal SNMP card	\$339	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Environmental monitoring device*	\$180	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	Relay card	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-EMD to be used with SNMP-M90S

M90S-6S Series Component pricing

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
M90S-PWM6	90000693	6kVA power module	\$4,190	38 lbs	35"W x 23"D x 10"H
M90S-BMXRV2	90001262	Battery module with breaker	\$2,095	107 lbs	23"W x 35"D x 10"H
M90S-ENC6	90000692	M90S 6 slot enclosure	\$7,250	169 lbs	40"W x 25"D x 50"H
M90S-BC7	90000696	M90S 7 slot tower battery cabinet	\$4,935	162 lbs	40"W x 25"D x 54"H
XPC-L14-30P*	90000717	8 ft L14-30P input cord (6kVA only)	\$135	10 lbs	4"W x 4"D x 6"H
M90S-BP	90000703	Matching front blank panel	\$63	5 lbs	16.5"W x 2"D x 5.2"H
M90-SEIS	90000678	Seismic hold down anchorage	\$1,900	TBA	TBA

*30A line cord limits UPS capacity to 24A continuous UPS input

M90S Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6–30R protected by a 20A breaker	1ft	208/230V	\$79	3 lbs
XPC-C20-L615R	C20 to L6–15R	1ft	208/230V	\$59	3 lbs

M90S Service Plans (USA and Canada)

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	M90S preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

**Service adder (SVCADD) must be added for all on-site service plans for locations further than 100 miles from a metropolitan area.*

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Depot Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

TX91 3.8kVA-10kVA Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolated Online 3.8kVA-10kVA

208VAC Input // 240/120VAC or 230/115VAC Output

Isolated online UPS provides protection from all 10 common power problems

- › Available models: 3.8kVA/3.8kW, 5kVA/5kW, 6kVA/6kW, 10kVA/10kW
- › Optional battery runtimes up to 8 hours
- › Maintenance bypass
- › Galvanic isolation transformer
- › Configurable outputs
- › Auto restart
- › Unity power factor
- › UL1778, cUL, FCC Class A, RoHS, TAA compliant (UPS only)
- › 3 years electronics, 3 years battery warranty (USA and Canada)



TX91 3.8kVA 208VAC Input - 240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Battery	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91-3.8K	90000579	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$6,350.00	(20) 9AH	Terminal block	Terminal block	272 lbs	9.8" x 23.2" x 32.4"
TX91-3.8KXR	90000572	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$8,050.00	(20) 580W	Terminal block	Terminal block	275 lbs	9.8" x 23.2" x 32.4"
TX91-3.8KB1####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$7,540.00	(20) 9AH	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	277 lbs	9.8" x 27.1" x 32.4"
TX91-3.8KXRB1####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$9,240.00	(20) 580W	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	280 lbs	9.8" x 27.1" x 32.4"
TX91-3.8KB2####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$7,540.00	(20) 9AH	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	277 lbs	9.8" x 27.1" x 32.4"
TX91-3.8KXRB2####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$9,240.00	(20) 580W	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	280 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91 5kVA 208VAC Input - 240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Battery	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91-5K	90000573	5kVA/5kW Tower UPS with Isolation Transformer	\$7,200.00	(20) 9AH	Terminal block	Terminal block	275 lbs	9.8" x 23.2" x 32.4"
TX91-5KXR	90000574	5kVA/5kW Tower UPS with Isolation Transformer	\$8,900.00	(20) 580W	Terminal block	Terminal block	278 lbs	9.8" x 23.2" x 32.4"
TX91-5KB1####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$8,390.00	(20) 9AH	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	280 lbs	9.8" x 27.1" x 32.4"
TX91-5KXRB1####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$10,090.00	(20) 580W	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	283 lbs	9.8" x 27.1" x 32.4"
TX91-5KB2####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$8,390.00	(20) 9AH	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	280 lbs	9.8" x 27.1" x 32.4"
TX91-5KXRB2####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$10,090.00	(20) 580W	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	283 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91 6kVA 208VAC Input - 240/120VAC or 230/115VAC Output Pricing

6kVA system capacity will be reduced by 30A input circuit

Model	Part Number	Description	List Price	Battery	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91-6K	90000575	6kVA/6kW Tower UPS with Isolation Transformer	\$8,050.00	(20) 9AH	Terminal block	Terminal block	278 lbs	9.8" x 23.2" x 32.4"
TX91-6KXR	90000576	6kVA/6kW Tower UPS with Isolation Transformer	\$9,750.00	(20) 580W	Terminal block	Terminal block	281 lbs	9.8" x 23.2" x 32.4"
TX91-6KB1####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$9,240.00	(20) 9AH	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	283 lbs	9.8" x 27.1" x 32.4"
TX91-6KXRB1####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$10,940.00	(20) 580W	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	286 lbs	9.8" x 27.1" x 32.4"
TX91-6KB2####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$9,240.00	(20) 9AH	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	283 lbs	9.8" x 27.1" x 32.4"
TX91-6KXRB2####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$10,940.00	(20) 580W	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	286 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91 10kVA 208VAC Input - 240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Battery	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91-10K	90000577	10kVA/10kW Tower UPS with Isolation Transformer	\$11,340.00	(20) 9AH	Terminal block	Terminal block	307 lbs	9.8" x 23.2" x 32.4"
TX91-10KXR	90000578	10kVA/10kW Tower UPS with Isolation Transformer	\$12,900.00	(20) 580W	Terminal block	Terminal block	310 lbs	9.8" x 23.2" x 32.4"
TX91-10KB1####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$12,530.00	(20) 9AH	Terminal block	(6) Configurable 240V outputs* + (4) 5-15/20R	312 lbs	9.8" x 27.1" x 32.4"
TX91-10KXRB1####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$14,090.00	(20) 580W	Terminal block	(6) Configurable 240V outputs* + (4) 5-15/20R	315 lbs	9.8" x 27.1" x 32.4"
TX91-10KB2####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$12,530.00	(20) 9AH	Terminal block	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	312 lbs	9.8" x 27.1" x 32.4"
TX91-10KXRB2####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$14,090.00	(20) 580W	Terminal block	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	315 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

Custom Voltage Configurations

Model	Part Number	Description	List Price
T9VCNFG	90000375	Preconfigure TX91 Transformer and Electronics for Custom Voltage Configuration, Input:Output Voltages Available: 240V:240/120V, 230V:230/115V, 220V:220/110V	\$300.00

TX91 Battery Options

Battery packs not for use with "XR" models.

Model	Part Number	Description	List Price	Shipping Weight	Unit Dimensions (W x D x H)
TX91-BP960-1	90000584	Extended Battery Pack for TX91 with (20) 12V 9AH Batteries	\$3,400.00	190 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-2	90000585	Extended Battery Pack for TX91 with (40) 12V 9AH Batteries	\$4,900.00	320 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-3	90000586	Extended Battery Pack for TX91 with (60) 12V 9AH Batteries	\$6,450.00	450 lbs	9.8" x 22.3" x 32.4"
TX91-CHG	90000762	208V 8A External Battery Charger	\$780.00	11 lbs	17.25" x 9" x 3.5"

TX91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMP2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 must be used with SNMP-2PV3

TX91 Cord Options

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6–30R	1ft	208/230V	\$79.00	3 lbs
XPC-C20-L615R	Non-locking IEC C20 to L6–15R	1ft	208/230V	\$59.00	3 lbs
XPC-L630R	L6–30R Factory Terminated to Output TB	6ft	208/230V	\$125.00	5 lbs
XPC-L630P	L6–30P Factory Terminated to Input TB	6ft	208/230V	\$125.00	5 lbs
XPC-L14-30R	L14-30R Factory Terminated to Output TB	6ft	208/230V	\$125.00	5 lbs

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD31	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (2) L6–20R + (4) 6–15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (4) L6–20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6–30P, 6ft	(4) IEC C19 + (8) IEC C14	6 lbs	19.0" x 2.4" x 3.5"
XPD34	90000254	30A 240/120V 2U 19" Basic Rack PDU	\$690.00	L14–30P, 6ft	(2) L6–30R + (4) L6–20R + (12) 5–15/20R	9.5 lbs	19.0" x 4.7" x 3.5"
XPD38	90001037	30A 120V 2U 19" Basic Rack PDU	\$690.00	L14–30P, 6ft	(4) L5–30R + (4) L5–20R	9.5 lbs	19.0" x 4.7" x 3.5"

TX91 Startup/Service Plans (USA and Canada)

On-site service within 100 miles of an Xtreme Power Service Technician. Contact inside sales for locations exceeding 100 miles.

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	Preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	Preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

On-site 3 Year Service Plan – 3 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

On-site 5 Year Service Plan – 5 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

TX91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	Internal battery		XR Internal		+ BP960-1		+ BP960-2		+ BP960-3		+ (2) BP960-2		+ (2) BP960-3		+ (3) BP960-3	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
TX91-3.8K	37	15	48	21	92	38	140	64	198	94	258	120	403	172	572	265
TX91-5K	26	10	35	15	64	26	106	45	142	65	186	89	279	126	443	190
TX91-6K	20	8	28	12	40	21	87	35	119	51	149	70	224	105	349	153
TX91-10K	9	3	14	6	23	10	39	18	58	26	79	35	116	55	170	89

For extended runtimes and detailed requirements, see www.xpcc.com/selector

TX91L 3.8kVA-10kVA Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolated Online 3.8kVA-10kVA

208VAC Input // 240/120VAC or 230/115VAC Output

Isolated online UPS provides protection from all 10 common power problems

- › Available models: 3.8kVA/3.8kW, 5kVA/5kW, 6kVA/6kW, 10kVA/10kW
- › Powerful 4A charger for use with large external battery systems
- › Maintenance bypass
- › Galvanic isolation transformer
- › Configurable outputs
- › Auto restart
- › UL1778, cUL, FCC Class A, RoHS, TAA compliant (UPS only)
- › 3 years electronics (USA and Canada)



TX91L 3.8kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-3.8K	90000587	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$5,100.00	Terminal block	Terminal block	152 lbs	9.8" x 23.2" x 32.4"
TX91L-3.8KB1####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$6,290.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	157 lbs	9.8" x 27.1" x 32.4"
TX91L-3.8KB2####	Bundle	3.8kVA/3.8kW Tower UPS with Isolation Transformer	\$6,290.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	157 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 5kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-5K	90000588	5kVA/5kW Tower UPS with Isolation Transformer	\$6,050.00	Terminal block	Terminal block	155 lbs	9.8" x 23.3" x 32.4"
TX91L-5KB1####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$7,240.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	160 lbs	9.8" x 27.1" x 32.4"
TX91L-5KB2####	Bundle	5kVA/5kW Tower UPS with Isolation Transformer	\$7,240.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	160 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 6kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries. 6kVA system capacity will be reduced by 30A input circuit

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-6K	90000589	6kVA/6kW Tower UPS with Isolation Transformer	\$6,800.00	Terminal block	Terminal block	158 lbs	9.8" x 23.3" x 32.4"
TX91L-6KB1####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$7,990.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	163 lbs	9.8" x 27.1" x 32.4"
TX91L-6KB2####	Bundle	6kVA/6kW Tower UPS with Isolation Transformer	\$7,990.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	163 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TX91L 10kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

TX91L series have a 4A charger with no internal batteries.

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TX91L-10K	90000590	10kVA/10kW Tower UPS with Isolation Transformer	\$9,240.00	Terminal block	Terminal block	187 lbs	9.8" x 23.3" x 32.4"
TX91L-10KB1####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$10,430.00	Terminal block	(6) Configurable 240V outputs* + (4) 5-15/20R	192 lbs	9.8" x 27.1" x 32.4"
TX91L-10KB2####	Bundle	10kVA/10kW Tower UPS with Isolation Transformer	\$10,430.00	Terminal block	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	192 lbs	9.8" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

Custom Voltage Configurations

Model	Part Number	Description	List Price
T9VCNFG	90000375	Preconfigure TX91L Transformer and Electronics for Custom Voltage Configuration, Input:Output Voltages Available: 240V:240/120V, 230V:230/115V, 220V:220/110V	\$300.00

TX91 Battery Options

Battery packs not for use with "XR" models.

Model	Part Number	Description	List Price	Shipping Weight	Unit Dimensions (W x D x H)
TX91-BP960-1	90000584	Extended Battery Pack for TX91 with (20) 12V 9AH Batteries	\$3,400.00	190 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-2	90000585	Extended Battery Pack for TX91 with (40) 12V 9AH Batteries	\$4,900.00	320 lbs	9.8" x 22.3" x 32.4"
TX91-BP960-3	90000586	Extended Battery Pack for TX91 with (60) 12V 9AH Batteries	\$6,450.00	450 lbs	9.8" x 22.3" x 32.4"

TX91L Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 must be used with SNMP-2PV3

TXVR Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R	1ft	208/230V	\$79.00	3 lbs
XPC-C20-L615R	Non-locking IEC C20 to L6-15R	1ft	208/230V	\$59.00	3 lbs

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPD31	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XPD32	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (4) L6-20R	7.5 lbs	19.0" x 2.4" x 3.5"
XPD33	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6-30P, 6ft	(4) IEC C19 + (8) IEC C14	6 lbs	19.0" x 2.4" x 3.5"
XPD34	90000254	30A 240/120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(2) L6-30R + (4) L6-20R + (12) 5-15/20R	9.5 lbs	19.0" x 4.7" x 3.5"
XPD38	90001037	30A 120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(4) L5-30R + (4) L5-20R	9.5 lbs	19.0" x 4.7" x 3.5"

TX91L Startup/Service Plans (USA and Canada)

On-site service within 100 miles of an Xtreme Power Service Technician. Contact inside sales for locations exceeding 100 miles.

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	Preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	Preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

On-site 3 Year Service Plan – 3 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

On-site 5 Year Service Plan – 5 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

TX91L Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	BP960-1		BP960-2		BP960-3		BP960-1 + BP960-3		BP960-2 + BP960-3		(2) BP960-3		BP960-1 + (2) BP960-3		BP960-2 + (2) BP960-3	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%	50%	100%
TX91L-3.8K	37	16	92	38	140	65	198	94	259	120	322	144	404	173	468	203
TX91L-5K	26	11	64	27	106	45	142	66	186	90	232	109	279	127	328	146
TX91L-6K	20	8	50	21	87	36	119	52	150	70	186	90	224	106	263	122
TX91L-10K	9	3	24	11	40	18	58	27	80	36	97	45	116	55	131	66

For extended runtimes and detailed requirements, see www.xpcc.com/selector

TXVR 3.8kVA-10kVA Series Isolated Electronic Voltage Regulator Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolated Electronic Voltage Regulator 3.8kVA-10kVA

208VAC Input // 240/120VAC or 230/115VAC Output

Power Conditioning for Voltage Critical Processes in the Most Demanding Conditions

- › Available models: 3.8kVA/3.8kW, 5kVA/5kW, 6kVA/6kW, 10kVA/10kW
- › Maintenance bypass
- › Regulates utility voltage variations to within $\pm 1\%$
- › Configurable outputs
- › Eliminates surges, spikes and noise without batteries
- › UL, cUL, RoHS, TAA compliant (TXVR only)
- › 3 years electronics (USA and Canada)



TXVR 3.8kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TXVR-3.8K	90000494	3.8kVA/3.8kW Tower Isolated Voltage Regulator	\$4,620.00	Terminal block	Terminal block	142 lbs	9.9" x 23.3" x 32.4"
TXVR-3.8KB1####	Bundle	3.8kVA/3.8kW Tower Isolated Voltage Regulator	\$5,810.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	147 lbs	9.9" x 27.1" x 32.4"
TXVR-3.8KB2####	Bundle	3.8kVA/3.8kW Tower Isolated Voltage Regulator	\$5,810.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	147 lbs	9.9" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TXVR 5kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TXVR-5K	90000495	5kVA/5kW Tower Isolated Voltage Regulator	\$5,900.00	Terminal block	Terminal block	145 lbs	9.9" x 23.3" x 32.4"
TXVR-5KB1####	Bundle	5kVA/5kW Tower Isolated Voltage Regulator	\$7,090.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	150 lbs	9.9" x 27.1" x 32.4"
TXVR-5KB2####	Bundle	5kVA/5kW Tower Isolated Voltage Regulator	\$7,090.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	150 lbs	9.9" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TXVR 6kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TXVR-6K	90000496	6kVA/6kW Tower Isolated Voltage Regulator	\$6,250.00	Terminal block	Terminal block	148 lbs	9.9" x 23.3" x 32.4"
TXVR-6KB1####	Bundle	6kVA/6kW Tower Isolated Voltage Regulator	\$7,440.00	L6-30P, 6ft	(6) Configurable 240V outputs* + (4) 5-15/20R	153 lbs	9.9" x 27.1" x 32.4"
TXVR-6KB2####	Bundle	6kVA/6kW Tower Isolated Voltage Regulator	\$7,440.00	L6-30P, 6ft	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	153 lbs	9.9" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

TXVR 10kVA 208VAC Input - **240/120VAC or 230/115VAC Output Pricing

Model	Part Number	Description	List Price	Input Connection	Output Connection	Shipping Weight	Unit Dimensions (W x D x H)
TXVR-10K	90000497	10kVA/10kW Tower Isolated Voltage Regulator	\$8,710.00	Terminal block	Terminal block	187 lbs	9.9" x 23.3" x 32.4"
TXVR-10KB1####	Bundle	10kVA/10kW Tower Isolated Voltage Regulator	\$9,905.00	Terminal block	(6) Configurable 240V outputs* + (4) 5-15/20R	192 lbs	9.9" x 27.1" x 32.4"
TXVR-10KB2####	Bundle	10kVA/10kW Tower Isolated Voltage Regulator	\$9,905.00	Terminal block	(4) Configurable 240V outputs* + (4) 5-15/20R + (1) L6-30R	192 lbs	9.9" x 27.1" x 32.4"

*Replace the "####" in the model number with four of the letters shown below. Each configurable output is protected by a 20A breaker.

240V/230V: A. L6-20R; B. L6-30R; C. 6-15/20R; D. L6-15R (non-locking C20) **For optional voltage configurations add \$300 list (PN:T9VCNFG, see below)

Custom Voltage Configurations

Model	Part Number	Description	List Price
T9VCNFG	90000375	Preconfigure TXVR Transformer and Electronics for Custom Voltage Configuration, Input:Output Voltages Available: 240V:240/120V, 230V:230/115V, 220V:220/110V	\$300.00

TXVR Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PV3	90000741	Two Port Internal SNMP Card	\$359.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMPV2*	90000674	Environmental Monitoring Sensor	\$230.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Modbus Card	\$319.00	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$120.00	1 lb	7.25" x 6" x 2.5"

*SNMP-EMPV2 must be used with SNMP-2PV3

TXVR Cord Options

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6-15/20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6-20R	1ft	208/230V	\$79.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R	1ft	208/230V	\$79.00	3 lbs
XPC-C20-L615R	Non-locking IEC C20 to L6-15R	1ft	208/230V	\$59.00	3 lbs
XPC-L630R	L6-30R Factory Terminated to Output TB	6ft	208/230V	\$125.00	5 lbs
XPC-L630P	L6-30P Factory Terminated to Input TB	6ft	208/230V	\$125.00	5 lbs
XPC-L14-30R	L14-30R Factory Terminated to Output TB	6ft	208/230V	\$125.00	5 lbs

Power Distribution Units

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XP31	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (2) L6-20R + (4) 6-15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XP32	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6-30P, 6ft	(2) L6-30R + (4) L6-20R	7.5 lbs	19.0" x 2.4" x 3.5"
XP33	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6-30P, 6ft	(4) IEC C19 + (8) IEC C14	6 lbs	19.0" x 2.4" x 3.5"
XP34	90000254	30A 240/120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(2) L6-30R + (4) L6-20R + (12) 5-15/20R	9.5 lbs	19.0" x 4.7" x 3.5"
XP38	90001037	30A 120V 2U 19" Basic Rack PDU	\$690.00	L14-30P, 6ft	(4) L5-30R + (4) L5-20R	9.5 lbs	19.0" x 4.7" x 3.5"

TXVR Startup/Service Plans (USA and Canada)

On-site service within 100 miles of an Xtreme Power Service Technician. Contact inside sales for locations exceeding 100 miles.

Model	Part Number	Description	List Price
9SUS8051	90001282	Startup 5x8 and 1 year on-site warranty	\$3,900.00
9SUS8052	90001283	Startup 5x8 and 2 year on-site warranty	\$4,500.00
9SUS8053	90001284	Startup 5x8 and 3 year on-site warranty	\$5,100.00
9SU724051	90001285	Startup 7x24 and 1 year on-site warranty	\$5,070.00
9SU724052	90001286	Startup 7x24 and 2 year on-site warranty	\$5,850.00
9SU724053	90001287	Startup 7x24 and 3 year on-site warranty	\$6,630.00
9PM58	90001288	Preventative maintenance service, 5x8	\$3,500.00
9PM724	90001289	Preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

Standard 3 Year Factory Warranty – 3 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On-site 3 Year Service Plan – 3 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

On-site 5 Year Service Plan – 5 year on-site service. On-site startup. On-site corrective maintenance. Services performed 5 x 8.

E91 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Three-phase Online

10kVA/10kW, 15kVA/15kW, 20kVA/20kW, 30kVA/30kW, 40kVA/40kW

208/120VAC or 220/127VAC

Unity power factor three-phase UPS for Edge facilities and IT applications

- › Unity Power Factor
- › Large Touch LCD
- › Rear clearance is not required (30 and 40kVA)
- › Internal maintenance bypass
- › Dual or single utility inputs
- › UL, cUL, FCC. 10, 15, & 20kW are Energy Star 2.0
- › 2 years warranty (USA & Canada)



E91 Series UPS

208/120VAC Three phase 10-40kVA including internal batteries and maintenance bypass

Model	Part Number	Description	List Price	Battery	Input/Output	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
E91-10K	90000975	10kVA/10kW 11 minute battery	\$10,800.00	(40) 12V/9AH	Terminal blocks	273 lbs	303 lbs	9.9" x 26.3" x 32.3" 14.5" x 30.5" x 35.4"
E91-15K	90000976	15kVA/15kW 11 minute battery	\$12,700.00	(60) 12V/9AH	Terminal blocks	306 lbs	336 lbs	11.9" x 34" x 40.2" 16.5" x 35.4" x 44.9"
E91-20K	90000977	20kVA/20kW 7 minute battery	\$13,600.00	(60) 12V/9AH	Terminal blocks	306 lbs	336 lbs	11.9" x 34" x 40.2" 16.5" x 35.4" x 44.9"
E91-30K	90000979	30kVA/30kW 6 minute battery	\$21,800.00	(60) 12V/580W	Terminal blocks	496 lbs	526 lbs	23.6" x 36.3" x 65.6" 39.4" x 47.2" x 76.8"
E91-30K4	90001234	30kVA/30kW 9 minute battery	\$23,700.00	(80) 12V/580W	Terminal blocks	549 lbs	579 lbs	23.6" x 36.3" x 65.6" 39.4" x 47.2" x 76.8"
E91-40K	90000980	40kVA/40kW 6 minute battery	\$25,300.00	(80) 12V/580W	Terminal blocks	551 lbs	581 lbs	23.6" x 36.3" x 65.6" 39.4" x 47.2" x 76.8"

E91 Series Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
EBP09-2	90000984	(40) 12V 9AH batteries for 10/15/20kVA models	\$6,100.00	310 lbs	345 lbs	11.9" x 34" x 40.2" 14.5" x 35.4" x 44.9"
EBP09-5	90000985	(100) 12V 9AH batteries for 10/15/20kVA models	\$9,950.00	670 lbs	705 lbs	11.9" x 34" x 40.2" 14.5" x 35.4" x 44.9"
EBP10-5	90000986	(100) 12V 580W batteries for 30/40kVA models	\$11,700.00	770 lbs	805 lbs	11.9" x 34" x 40.2" 14.5" x 35.4" x 44.9"

E91 Power Distribution Units

For 10, 15 & 20k models only

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions (W x D x H)
E91-PDU1	90001023	(4) L21-20R each protected by a 20A breaker	\$1,350.00	15 lb	9.5" x 4.3" x 11.6" 14.9" x 8.5" x 12"
E91-PDU2	90001024	(4) L21-30R each protected by a 30A breaker	\$1,500.00	15 lb	9.5" x 4.3" x 11.6" 14.9" x 8.5" x 12"

E91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PG1	90001245	Two port internal SNMP card	\$649	1 lb	7.25" x 6" x 2.5"
SNMP-TMPH	90001246	Temperature and humidity probe*	\$299	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	MODBUS (RTU protocol) card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	RELAY card with 10 port relay connector	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-TMPH to be used with SNMP-2PG1

E91 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
E91SU581	90001011	Startup 5x8 and 1 year on-site warranty	\$3,900.00
E91SU582	90001005	Startup 5x8 and 2 year on-site warranty	\$4,500.00
E91SU583	90001006	Startup 5x8 and 3 year on-site warranty	\$7,400.00
E91SU7241	90001012	Startup 7x24 and 1 year on-site warranty	\$5,070.00
E91SU7242	90001007	Startup 7x24 and 2 year on-site warranty	\$5,850.00
E91SU7243	90001235	Startup 7x24 and 3 year on-site warranty	\$9,620.00
E91PM58	90001236	E91 preventative maintenance service, 5x8	\$3,500.00
E91PM724	90001010	E91 preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

E91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Models	Internal Batteries		Qty (1) EBP09-2		Qty (1) EBP09-5		Qty (2) EBP09-5	
Percentage load:	50%	100%	50%	100%	50%	100%	50%	100%
E91-10K	28	11	69	28	130	58	247	113
E91-15K	28	11	54	22	98	41	167	78
E91-20K	19	7	37	15	69	28	122	52

Models	Internal Batteries		Qty (1) EBP10-5		Qty (2) EBP10-5	
Percentage load:	50%	100%	50%	100%	50%	100%
E91-30K	16	6	52	23	94	41
E91-30K4	23	9	60	26	102	44
E91-40K	16	6	42	18	73	31

For longer runtimes please contact sales@xpcc.com

E91L Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing


Three-phase Online

20kVA/20kW, 30kVA/30kW, 40kVA/40kW

208/120VAC or 220/127VAC

Unity power factor three-phase UPS for Edge facilities and IT applications

- › Unity Power Factor
- › Internal maintenance bypass
- › Dual or single utility inputs
- › Battery charging up to 24A
- › UL, cUL, FCC
- › 2 years warranty (USA & Canada)



E91L Series UPS

208/120VAC Three phase 20/30/40kVA including maintenance bypass

Model	Part Number	Description	List Price	Input/Output	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
E91-20KL	90000980	20kVA/20kW no internal batteries	\$11,800.00	Terminal blocks	296 lbs	315 lbs	11.9" x 34" x 40.2" 16.5" x 35.4" x 44.9"
E91-30KL	90000981	30kVA/30kW no internal batteries	\$17,000.00	Terminal blocks	419 lbs	504 lbs	23.6" x 31.1" x 65.6" 39.4" x 47.2" x 76.8"
E91-40KL	90000982	40kVA/40kW no internal batteries	\$18,500.00	Terminal blocks	539 lbs	510 lbs	23.6" x 31.1" x 65.6" 39.4" x 47.2" x 76.8"

E91 Series Battery Packs

Model	Part Number	Description	List Price	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
EBP09-2	90000984	Battery cabinet including (40) 12V 9AH batteries & breaker	\$6,100.00	310 lbs	345 lbs	11.9" x 34" x 40.2" 14.5" x 35.4" x 44.9"
EBP09-5	90000985	Battery cabinet including (100) 12V 9AH batteries & breaker	\$9,950.00	670 lbs	705 lbs	11.9" x 34" x 40.2" 14.5" x 35.4" x 44.9"

E91L Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PG1	90001245	Two port internal SNMP card	\$649	1 lb	7.25" x 6" x 2.5"
SNMP-TMPH	90001246	Temperature and humidity probe*	\$299	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	MODBUS (RTU protocol) card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	RELAY card with 10 port relay connector	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-TMPH to be used with SNMP-2PG1

E91L Service Plans (USA and Canada)

Model	Part Number	Description	List Price
E91SU581	90001011	Startup 5x8 and 1 year on-site warranty	\$3,900.00
E91SU582	90001005	Startup 5x8 and 2 year on-site warranty	\$4,500.00
E91SU583	90001006	Startup 5x8 and 3 year on-site warranty	\$7,400.00
E91SU7241	90001012	Startup 7x24 and 1 year on-site warranty	\$5,070.00
E91SU7242	90001007	Startup 7x24 and 2 year on-site warranty	\$5,850.00
E91SU7243	90001235	Startup 7x24 and 3 year on-site warranty	\$9,620.00
E91PM58	90001236	E91L preventative maintenance service, 5x8	\$3,500.00
E91PM724	90001010	E91L preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service adder for locations further than 100 miles	\$1,050

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

E91L Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Models	EBP09-5 (qty)				
System Load	(1)	(2)	(3)	(4)	(5)
20KW	15	37	63	93	118
30KW	9	22	37	54	74
40KW	5	15	26	37	50

M90C-2S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online UPS

Capacity: 5kW or 8kW

208/120VAC Three-phase

Modular 3-phase UPS for Continuous Power Availability

- › Unity power factor
- › Hardwired or plug & receptacle configurations
- › Up to 98% ECO mode or 93% online efficiency
- › UL-1778 (TUV), cUL, FCC A, RoHS, TAA compliant (pending)
- › 2 years electronic, 2 years battery warranty (USA and Canada)



M90C-2S Series 5W 208/120VAC Three-phase 2 Slot

M90C-2S bundles include 5kW UPS power module, battery module, and 2-slot enclosure with integral maintenance bypass. Line cord and receptacle panel are optional.

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90C-2S5K	Bundle	5kVA/5kW rack system with rail kit and 1 battery pack	\$9,450.00	Hardwired	185 lbs	17.5"W x 33.5"D x 10.5"H
M90C-2S5KT	Bundle	5kVA/5kW tower system with caster base and 1 battery pack	\$9,905.00	Hardwired	198 lbs	17.4"W x 33.7"D x 14.5"H

For panel configurations, see below.

M90C-2S Series 8W 208/120VAC Three-phase 2 Slot

M90C-2S bundles include 8kW UPS power module, battery module, and 2-slot enclosure with integral maintenance bypass. Line cord and receptacle panel are optional.

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90C-2S8K	Bundle	8kVA/8kW rack system with rail kit and 1 battery pack	\$10,250.00	Hardwired	185 lbs	17.5"W x 33.5"D x 10.5"H
M90C-2S8KT	Bundle	8kVA/8kW tower system with caster base and 1 battery pack	\$10,705.00	Hardwired	198 lbs	17.4"W x 33.7"D x 14.5"H

For panel configurations, see below.

M90C Receptacle Panels

1 receptacle panel per 2 slot enclosure. Add list price for the receptacle panel added to configuration.

Model	Part No	Description	Unit Weight	Price	Unit Dimensions (W x D x H)
M90C-RPI	90001058	(1) L21-20R & (1) breaker	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPJ	90001059	(1) L21-30R & (1) breaker	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPK	90001260	(2) L21-20R	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPL	90001261	(2) L21-30R	6 lbs	\$395	16.5"W x 2"D x 5.2"H

M90C-2S Series Component pricing

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
M90C-PWM5	90001211	5kVA/5kW power module	\$4,900	40 lbs	23"W x 35"D x 10"H
M90C-PWM8	90001029	8kVA/8kW power module	\$5,700	41 lbs	23"W x 35"D x 10"H
M90S-BMXRV2	90001262	Battery module with breaker	\$2,095	107 lbs	23"W x 35"D x 10"H
M90C-ENC2	90001032	M90C-2S enclosure with maintenance bypass	\$2,300	34 lbs	23"W x 31.5"D x 15"H
M90S-RAIL2S	90000695	2 slot enclosure rail kit	\$155	5 lbs	20"W x 4"D x 2.5" H
XPC-L21-20P	90001219	8ft, L21-20P input cord (for 5kW)	\$420	10 lbs	4"W x 4"D x 6"H
XPC-L21-30P	90001220	8ft, L21-30P input cord (for 8kW)	\$420	10 lbs	4"W x 4"D x 6"H
M90S-CB	90000719	Caster base for M90C-2S enclosure	\$610	18 lbs	17"W x 24"D x 5"H
M90S-BP	90000703	Matching front blank panel	\$63	5 lbs	16.5"W x 2"D x 5.2"H

M90C-2S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PG1	90001245	Two port internal SNMP card	\$649	1 lb	7.25" x 6" x 2.5"
SNMP-TMPH	90001246	Temperature and humidity probe*	\$299	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	MODBUS (RTU protocol) card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	RELAY card with 10 port relay connector	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-TMPH to be used with SNMP-2PG1

M90C Service Plans (USA and Canada)

Model	Part Number	Description	List Price
MCSU58OS1	90001290	Startup 5x8 and 1 year on-site warranty	\$3,900.00
MCSU58OS2	90001291	Startup 5x8 and 2 year on-site warranty	\$4,500.00
MCSU58OS3	90001292	Startup 5x8 and 3 year on-site warranty	\$5,100.00
MCSU724OS1	90001293	Startup 7x24 and 1 year on-site warranty	\$5,070.00
MCSU724OS2	90001294	Startup 7x24 and 2 year on-site warranty	\$5,850.00
MCSU724OS3	90001295	Startup 7x24 and 3 year on-site warranty	\$6,630.00
MCPM58	90001296	M90S preventative maintenance service, 5x8	\$3,500.00
MCPM724	90001297	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

*Service adder (SVCADD) must be added for all on-site service plans for locations further than 100 miles from a metropolitan area.

Standard 2 Year Factory Warranty – 2 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Extended 5 Year Depot Warranty – 5 year electronics/battery. Telephone technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

BATTERY RUNTIMES

Load (kw)	1	2	3	4	5	6	7	8
M90C-2S5K	85	38	22	15	12	-	-	-
M90C-2S8K	85	38	22	15	12	9	7	6

Runtimes are shown in minutes and will vary based on battery age and site conditions.

M90C-6S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Capacities: 5kW to 24kW

208/120VAC Three-phase

Compact Three-Phase Modular UPS for Continuous Power

- › Modular for capacity or redundancy
- › Hot swappable power and battery modules
- › Hardwired or plug & receptacle configurations
- › Up to 98% ECO mode or 93% online efficiency
- › Large LCD display
- › UL-1778 (TUV), cUL, FCC A, RoHS, TAA compliant
- › 2 years electronic, 2 years battery warranty (USA and Canada)



M90C Series 208/120VAC Three-phase 6 Slot

M90C-6S Bundles include UPS power module(s), battery module(s), large LCD display, blank panels for open slots, and 6-slot enclosure with front facing integral maintenance bypass . 6-slot enclosure can have up to 4 optional receptacle panels.

Model	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90C-6S5k1	5kW system with one battery module	\$15,247	Terminal block and/or up to 4 optional receptacle panels	314 lbs	17.4" x 33.7" x 45.5"
M90C-6S5k2	5kW system with two battery modules	\$17,279	Terminal block and/or up to 4 optional receptacle panels	421 lbs	17.4" x 33.7" x 45.5"
M90C-6S5k3	5kW system with three battery modules	\$19,311	Terminal block and/or up to 4 optional receptacle panels	528 lbs	17.4" x 33.7" x 45.5"
M90C-6S5k4	5kW system with four battery modules	\$21,343	Terminal block and/or up to 4 optional receptacle panels	635 lbs	17.4" x 33.7" x 45.5"
M90C-6S5k5	5kW system with five battery modules	\$23,375	Terminal block and/or up to 4 optional receptacle panels	742 lbs	17.4" x 33.7" x 45.5"
M90C-6S10k2	10kW system with two battery modules	\$22,116	Terminal block and/or up to 4 optional receptacle panels	459 lbs	17.4" x 33.7" x 45.5"
M90C-6S10k3	10kW system with three battery modules	\$24,148	Terminal block and/or up to 4 optional receptacle panels	566 lbs	17.4" x 33.7" x 45.5"
M90C-6S10k4	10kW system with four battery modules	\$26,180	Terminal block and/or up to 4 optional receptacle panels	673 lbs	17.4" x 33.7" x 45.5"
M90C-6S15k2	15kW system with two battery modules	\$26,953	Terminal block and/or up to 4 optional receptacle panels	604 lbs	17.4" x 33.7" x 45.5"
M90C-6S15k3	15kW system with three battery modules	\$28,985	Terminal block and/or up to 4 optional receptacle panels	711 lbs	17.4" x 33.7" x 45.5"

For panel configurations, see below.

M90C Series 208/120VAC Three-phase 6 Slot

M90C-6S Bundles include UPS power module(s), battery module(s), large LCD display, blank panels for open slots, and 6-slot enclosure with front facing integral maintenance bypass . 6-slot enclosure can have up to 4 optional receptacle panels.

Model	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90C-6S8k1	8kW system with one battery module	\$16,047	Terminal block and/or up to 4 optional receptacle panels	314 lbs	17.4" x 33.7" x 45.5"
M90C-6S8k2	8kW system with two battery modules	\$18,079	Terminal block and/or up to 4 optional receptacle panels	421 lbs	17.4" x 33.7" x 45.5"
M90C-6S8k3	8kW system with three battery modules	\$20,111	Terminal block and/or up to 4 optional receptacle panels	528 lbs	17.4" x 33.7" x 45.5"
M90C-6S8k4	8kW system with four battery modules	\$22,143	Terminal block and/or up to 4 optional receptacle panels	635 lbs	17.4" x 33.7" x 45.5"
M90C-6S8k5	8kW system with five battery modules	\$24,175	Terminal block and/or up to 4 optional receptacle panels	742 lbs	17.4" x 33.7" x 45.5"
M90C-6S16k2	16kW system with two battery modules	\$23,716	Terminal block and/or up to 4 optional receptacle panels	459 lbs	17.4" x 33.7" x 45.5"
M90C-6S16k3	16kW system with three battery modules	\$25,748	Terminal block and/or up to 4 optional receptacle panels	566 lbs	17.4" x 33.7" x 45.5"
M90C-6S16k4	16kW system with four battery modules	\$27,780	Terminal block and/or up to 4 optional receptacle panels	673 lbs	17.4" x 33.7" x 45.5"
M90C-6S24k3	24kW system with three battery modules	\$31,385	Terminal block and/or up to 4 optional receptacle panels	711 lbs	17.4" x 33.7" x 45.5"

For panel configurations, see below.

M90C Receptacle Panels

Add panel needed to part number above. Example: M90C-6S16K2AB33IJ (M90C-6S16K2 with panel A, B with (2) L6-30R, I, and J). Maximum of 4 receptacle panels per 6 slot enclosure. Add list price for each receptacle panel or dongle added to configuration.

Model	Part No	Panel	Description	Additional Receptacle Options	Wiring	Unit Weight	Price	Unit Dimensions (W x D x H)
M90S-RPA	90000699	A	(8) 5-20R	N/A	1Ø, N, G	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPB	90000700	B	(4) 5-20R + (2) C19*	*up to 2 dongles	2Ø, N, G	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPC	90000701	C	L6-30R + (2) C19*	*up to 2 dongles	2Ø, N, G	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPD	90000702	D	L14-30R + (2) C19*	*up to 2 dongles	2Ø, N, G	5 lbs	\$295	16.5"W x 2"D x 5.2"H
M90S-RPE	Bundle	E	(2) L6-20R + (4) 5-20R	N/A	2Ø, N, G	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPF	Bundle	F	L6-20R + L6-30R* + (4) 5-20R	N/A	2Ø, N, G	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPG	Bundle	G	L6-30R + (2) L6-20R	N/A	2Ø, N, G	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90S-RPH	Bundle	H	(3) L6-30R*	N/A	2Ø, N, G	8 lbs	\$453	16.5"W x 2"D x 5.2"H
M90C-RPI	90001058	I	(1)L21-20R & (1) Breaker	N/A	3Ø, N, G	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPJ	90001059	J	(1) L21-30R & (1) breaker	N/A	3Ø, N, G	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPK	90001260	K	(2) L21-20R	N/A	3Ø, N, G	6 lbs	\$395	16.5"W x 2"D x 5.2"H
M90C-RPL	90001261	L	(2) L21-30R	N/A	3Ø, N, G	6 lbs	\$395	16.5"W x 2"D x 5.2"H

*Dongle options: 208V/240V: 1 - L6-15R, 2 - L6-20R, 3 - L6-30R, 4 - 6-15/20R. Add the dongle option number after the panel letter. Each configurable output is protected by a breaker. Receptacle panels should be selected for balanced load on 3 output phases.

M90C Series Battery Cabinet Bundles

M90S-BC7 tower bundles include battery enclosure and battery modules

Model	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90S-BC7-1	M90C 7 slot battery cabinet with one battery module	\$7,408	269 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-2	M90C 7 slot battery cabinet with two battery modules	\$9,440	376 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-3	M90C 7 slot battery cabinet with three battery modules	\$11,472	483 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-4	M90C 7 slot battery cabinet with four battery modules	\$13,504	590 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-5	M90C 7 slot battery cabinet with five battery modules	\$15,536	697 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-6	M90C 7 slot battery cabinet with six battery modules	\$17,568	804 lbs	17.4" x 33.7" x 45.5"
M90S-BC7-7	M90C 7 slot battery cabinet with seven battery modules	\$19,600	911 lbs	17.4" x 33.7" x 45.5"

M90S BC7 battery cabinets are tower configuration only. All BC7 bundles include blank panels for slots that do not have battery modules.

BATTERY RUNTIMES

Battery Modules	6S UPS					6S UPS + 1 BC7							6S UPS + 2 BC7				
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
5kW	12	28	46	66	86	106	121	133	151*	170*	190*	209*	228*	248*	268*	288*	308*
10kW	N/A	12	20	28	37	46	56	66	76	86	96	106	114	121	127	133	142*
15kW	N/A	7	12	17	23	28	34	40	46	53	59	66	72	79	86	93	100
Battery Modules	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
8kW	6	16	26	37	49	61	73	86	99*	110*	119*	127*	135*	147*	159*	170*	182*
16kW	N/A	6	11	16	21	26	32	37	43	49	55	61	67	73	79	86	92*
24kW	N/A	N/A	6	9	13	16	19	23	26	30	33	37	41	45	49	53	57

Runtimes are shown in minutes and will vary based on battery age and site conditions. Maximum 8 battery modules per UPS power module.

*Additional power module(s) required for battery recharge. Contact sales@xpcc.com for longer runtimes.

M90C-6S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PG1	90001245	Two port internal SNMP card	\$649	1 lb	7.25" x 6" x 2.5"
SNMP-TMPH	90001246	Temperature and humidity probe*	\$299	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	MODBUS (RTU protocol) card	\$319	1 lb	7.25" x 6" x 2.5"
RELAY-MINI	90000265	RELAY card with 10 port relay connector	\$120	1 lb	7.25" x 6" x 2.5"

*SNMP-TMPH to be used with SNMP-2PG1

M90C-6S Series Component pricing

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
M90C-PWM5	90001211	5kVA/5kW power module	\$4,900	40 lbs	23"W x35"D x 10"H
M90C-PWM8	90001029	8kVA/8kW power module	\$5,700	40 lbs	23"W x35"D x 10"H
M90S-BMXRV2	90001262	Battery module with breaker	\$2,095	107 lbs	23"W x 35"D x 10"H
M90C-ENC6	90001218	M90C-6S enclosure	\$8,000	169 lbs	40"W x 25"D x 50"H
XPC-L21-20P	90001219	8ft, L21-20P input cord for (for 5kW)	\$420	10 lbs	4"W x 4"D x 6"H
XPC-L21-30P	90001220	8ft, L21-30P input cord (for 8kW)	\$420	10 lbs	4"W x 4"D x 6"H
M90S-BP	90000703	Matching front blank panel	\$63	5 lbs	16.5"W x 2"D x 5.2"H

M90C Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R	1ft	208/230V	\$79	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6–30R protected by a 20A breaker	1ft	208/230V	\$79	3 lbs
XPC-C20-L615R	C20 to L6–15R	1ft	208/230V	\$45	3 lbs

M90C Service Plans (USA and Canada)

Model	Part Number	Description	List Price
MCSU58OS1	90001290	Startup 5x8 and 1 year on-site warranty	\$3,900.00
MCSU58OS2	90001291	Startup 5x8 and 2 year on-site warranty	\$4,500.00
MCSU58OS3	90001292	Startup 5x8 and 3 year on-site warranty	\$5,100.00
MCSU724OS1	90001293	Startup 7x24 and 1 year on-site warranty	\$5,070.00
MCSU724OS2	90001294	Startup 7x24 and 2 year on-site warranty	\$5,850.00
MCSU724OS3	90001295	Startup 7x24 and 3 year on-site warranty	\$6,630.00
MCPM58	90001296	M90S preventative maintenance service, 5x8	\$3,500.00
MCPM724	90001297	M90S preventative maintenance service, 7x24	\$4,550.00
SVCADD	90000538	Service addder for locations further than 100 miles	\$1,050

**Service adder (SVCADD) must be added for all on-site service plans for locations further than 100 miles from a metropolitan area.*

M90LU Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Six capacities: 15kVA/15kW, 20kVA/20kW, 30kVA/30kW, 40kVA/40kW,
45kVA/45kW, 60kVA/60kW
208/120VAC Three phase

Mission Critical Availability while reducing costs with Scalable, Modular M90L for 15kVA to 60kVA applications

- › Unity power factor
- › Modular and upgradeable for capacity or redundancy
- › Hot swappable power modules
- › Large LCD display
- › Remote control and monitoring options
- › UL-1778, cUL, FCC A, RoHS, TAA (select models)
- › 2 year warranty (UPS)



M90LU Series 208/120VAC Three phase 20/40/60kVA bundles

Input neutral is required. For use with M90-BC, M90-BOS or 3rd party external battery cabinet.

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90LU-20k*	Bundle	20kVA/20kW no internal batteries	\$18,800	Hardwired	301 lbs	20.3" x 41.3" x 30"
M90LU-40k	Bundle	40kVA/40kW no internal batteries	\$27,300	Hardwired	375 lbs	20.3" x 41.3" x 30"
M90LU-60k	Bundle	60kVA/60kW no internal batteries	\$35,800	Hardwired	449 lbs	20.3" x 41.3" x 30"

*non-TAA compliant models

M90LU Series 208/120VAC Three phase 15/30/45kVA bundles

Input neutral is required. For use with M90-BC, M90-BOS or 3rd party external battery cabinet.

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90LU-15k*	Bundle	15kVA/15kW no internal batteries	\$17,000	Hardwired	300 lbs	20.3" x 41.3" x 30"
M90LU-30k	Bundle	30kVA/30kW no internal batteries	\$23,700	Hardwired	373 lbs	20.3" x 41.3" x 30"
M90LU-45k	Bundle	45kVA/45kW no internal batteries	\$30,400	Hardwired	446 lbs	20.3" x 41.3" x 30"

*non-TAA compliant models

M90-BC Modular Battery Cabinet with Battery Modules Bundles

M90-BC includes up to 8 battery strings, each with individual front facing breakers

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90-BC-04B	Bundle	M90-BC with 4 battery modules	\$16,300.00	Hardwired	1200 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-08B	Bundle	M90-BC with 8 battery modules	\$20,400.00	Hardwired	1540 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-12B	Bundle	M90-BC with 12 battery modules	\$24,500.00	Hardwired	1880 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-16B	Bundle	M90-BC with 16 battery modules	\$28,600.00	Hardwired	2220 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-20B	Bundle	M90-BC with 20 battery modules	\$32,700.00	Hardwired	2560 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-24B	Bundle	M90-BC with 24 battery modules	\$36,800.00	Hardwired	2900 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-28B	Bundle	M90-BC with 28 battery modules	\$40,900.00	Hardwired	3240 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-32B	Bundle	M90-BC with 32 battery modules	\$45,000.00	Hardwired	3580 lbs	23.6"W x 43.3"D x 79.1"H

M90-BC is an external battery cabinet for use with M90U-80 without internal batteries (00B), M90U-140, or M90LU.

M90-BOS Modular Battery Cabinet with Battery Modules Bundles

M90-BOS includes up to 6 battery strings of CSB UPS 12580 (+/-120Vdc) and rear facing breaker

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90-BOS-04B	Bundle	M90-BOS with 4 battery modules	\$9,060.00	Hardwired	499 lbs	20.3" x 39.4" x 30"
M90-BOS-06B	Bundle	M90-BOS with 6 battery modules	\$10,840.00	Hardwired	635 lbs	20.3" x 39.4" x 30"
M90-BOS-08B	Bundle	M90-BOS with 8 battery modules	\$12,620.00	Hardwired	771 lbs	20.3" x 39.4" x 30"
M90-BOS-10B	Bundle	M90-BOS with 10 battery modules	\$14,440.00	Hardwired	907 lbs	20.3" x 39.4" x 30"
M90-BOS-12B	Bundle	M90-BOS with 12 battery modules	\$16,180.00	Hardwired	1043 lbs	20.3" x 39.4" x 30"

M90-BOS is an external battery cabinet for use with M90L.

M90LU Series Pricing

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90L-ENC (Unity)	99000873	M90L complete enclosure (60kVA max) includes large LCD display, static switch, and maintenance bypass. Holds up to 3 UPS modules. Does not hold battery modules	\$10,300.00	227 lbs	20.3" x 39.4" x 30"
M90-PWRM (Unity)	99000870	M90 unity 20kVA/20kW power module	\$8,500.00	74 lbs	19.5" x 29.5" x 5.5"
M90-PWRM15 (Unity)	99000871	M90 unity 15kVA/15kW power module	\$6,700.00	73 lbs	19.5" x 29.5" x 5.5"
M90-SKIRT	90000565	Skirt kit for M90	\$380.00	20 lbs	7" x 43.5" x 6.5"
M90-SEIS	90000678	Seismic hold down anchorage**	\$1,900.00	TBA	TBA

M90-BC pricing

M90-BC	90000716	External modular battery cabinet. Holds up to 32 M90-BCBAT battery modules. BC to UPS cable is not included	\$12,200.00	860 lbs	23.6" x 43.8" x 79.1"
M90-BCBAT	90000764	M90-BC Battery Module with (5) HR1290 batteries. Fits M90-BC external battery cabinet	\$1,025.00	85 lbs	7.3" x 38.5" x 3.2"
M90-BCBT	90000851	Empty battery tray for M90-BC	\$500.00	14 lbs	7.3" x 38.5" x 3.2"

M90-BOS pricing

M90-BOS	90000852	M90L matching external battery cabinet	\$5,500.00	227 lbs	29.5" x 39.4" x 30"
M90-BATT	90000563	M90 battery tray (10) UPS 12580	\$890.00	68 lbs	4.3" x 28.5" x 6.5"

*Input neutral is required **Must order one seismic kit for each enclosure and battery cabinet.

M90LU Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2P3	90000566	Two port internal SNMP card	\$349.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Environmental monitoring device*	\$180.00	1 lb	7.25" x 6" x 2.5"
M90-COMM	90000498	Extra communication card for M90L	\$370.00	1 lb	5.7" x 5.2" x 1.7"
M90-BTS	90000796	Battery temperature sensor with 10' cable**	\$66.00	1 lb	5.7" x 5.2" x 1.7"

*SNMP-EMD to be used with SNMP-2P3 **One M90-BTS may be used directly with CN1 on M90L front panel. Up to 4 M90-BTS may be used with M90-COMM.

M90LU Service Plans (USA and Canada)

Model	Part Number	Description	List Price
M90SU582	90000571	Startup 5x8 and 2 year on-site warranty	\$5,500
M90SU583	90000593	Startup 5x8 and 3 year on-site warranty	\$8,400
M90SU7242	90000592	Startup 7x24 and 2 year on-site warranty	\$7,150
M90SU7245	90000647	Startup 7x24 and 5 year on-site warranty	\$17,900
M90EXW1YR	90000594	1 year factory warranty extension	\$3,200
M90PM724	90000648	M90LU preventative maintenance service, 7x24	\$4,600
SVCADD	90000538	Service adder for locations further than 100 miles	\$1,050

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

M90LU Service Plans for M90-BC (USA and Canada)

Example: On-site 3 year warranty and startup for M90-BC-12B (12 battery modules) system would need Qty (1) M90SU583 + (12) MS0S3BM

Model	Module Service Plans	On-site 2 Year Warranty	On-site 3 Year Warranty
M90-BCBAT	M90-BCBAT battery module. Order one service plan for each battery purchased.	Model - TBD	Model - MS0S3BM
		TBD	PN: 90000729
		List: \$250	List:\$350

** Startup must be purchased for all on-site service plans. * Same level plan must be purchased for all battery modules.*

M90-BOS Series Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (KVA)	5	10	15	20	25	30	35	40	45	50	55	60
2 battery modules	16	6	-	-	-	-	-	-	-	-	-	-
4 battery modules	37	16	9	6	-	-	-	-	-	-	-	-
6 battery modules	60	26	16	11	8	6	-	-	-	-	-	-
8 battery modules	85	37	23	16	12	9	8	6	-	-	-	-
10 battery modules	110	48	30	21	16	13	10	9	7	6	5	-
12 battery modules	127	60	37	26	20	16	13	11	9	8	7	6

M90-BC Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (KVA)	5	10	15	20	25	30	35	40	45	50	55	60
4 battery modules	40	16	10	5	-	-	-	-	-	-	-	-
8 battery modules	97	40	24	16	13	10	7	5	-	-	-	-
12 battery modules	154	67	40	28	21	16	14	12	10	8	7	5
16 battery modules	216	97	58	40	30	24	20	16	15	13	11	10
20 battery modules	283	126	77	53	40	32	26	22	19	16	15	13
24 battery modules	346	154	97	67	50	40	33	28	24	21	18	16
28 battery modules	410	185	118	82	61	49	40	34	29	25	22	20
32 battery modules	475	216	134	97	73	58	47	40	34	30	27	24
36 battery modules	541	248	154	113	84	67	55	46	40	35	31	28
40 battery modules	608	283	174	126	97	77	63	53	46	40	35	32
44 battery modules	675	316	195	139	110	86	71	60	52	45	40	36
48 battery modules	743	346	216	154	121	97	79	67	58	50	45	40
52 battery modules	812	378	237	169	131	108	88	74	64	56	49	44
56 battery modules	881	410	259	185	142	118	97	82	70	61	54	49
60 battery modules	951	442	283	200	154	126	106	89	77	67	59	53
64 battery modules	1022	475	305	216	166	134	115	97	83	73	64	58

For runtimes with more than 32 battery modules, a second M90-BC must be used. A parallel bus bar kit is required for all bundles that include (2) M90-BC.

M90U Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Six capacities: 15kVA/15kW, 20kVA/20kW, 30kVA/30kW, 40kVA/40kW,
45kVA/45kW, 60kVA/60kW
208/120VAC Three phase

Mission Critical Availability while reducing costs with Scalable, Modular M90U for 15kVA to 60kVA applications

- › Unity power factor
- › Modular and upgradeable for capacity or redundancy
- › Hot swappable power modules
- › Large LCD display
- › Up to 98% ECO mode or 94% online efficiency
- › UL-1778, cUL, FCC A, RoHS, TAA compliant (select models)
- › 2 year warranty (USA and Canada)



M90U Series 208/120VAC Three phase 15/30/45kVA bundles including internal maintenance bypass

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U-15k04BM*	Bundle	15kVA/15kW 9 minute battery	\$24,460.00	Hardwired	819 lbs	20.3" x 41.3" x 54"
M90U-15k06BM*	Bundle	15kVA/15kW 16 minute battery	\$26,240.00	Hardwired	955 lbs	20.3" x 41.3" x 54"
M90U-15k08BM*	Bundle	15kVA/15kW 22 minute battery	\$28,020.00	Hardwired	1090 lbs	20.3" x 41.3" x 54"
M90U-15k10BM	Bundle	15kVA/15kW 29 minute battery	\$29,800.00	Hardwired	1225 lbs	20.3" x 41.3" x 54"
M90U-15k12BM	Bundle	15kVA/15kW 37 minute battery	\$31,580.00	Hardwired	1361 lbs	20.3" x 41.3" x 54"
M90U-30k06BM	Bundle	30kVA/30kW 6 minute battery	\$32,940.00	Hardwired	1029 lbs	20.3" x 41.3" x 54"
M90U-30k08BM	Bundle	30kVA/30kW 9 minute battery	\$34,720.00	Hardwired	1165 lbs	20.3" x 41.3" x 54"
M90U-30k10BM	Bundle	30kVA/30kW 12 minute battery	\$36,500.00	Hardwired	1300 lbs	20.3" x 41.3" x 54"
M90U-30k12BM	Bundle	30kVA/30kW 16 minute battery	\$38,280.00	Hardwired	1436 lbs	20.3" x 41.3" x 54"
M90U-45k08BM	Bundle	45kVA/45kW 5 minute battery	\$41,420.00	Hardwired	1239 lbs	20.3" x 41.3" x 54"
M90U-45k10BM	Bundle	45kVA/45kW 7 minute battery	\$43,200.00	Hardwired	1375 lbs	20.3" x 41.3" x 54"
M90U-45k12BM	Bundle	45kVA/45kW 9 minute battery	\$44,980.00	Hardwired	1511 lbs	20.3" x 41.3" x 54"

*non-TAA compliant models

M90U Series 208/120VAC Three phase 20/40/60kVA bundles including internal maintenance bypass

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U-20k04BM*	Bundle	20kVA/20kW 6 minute battery	\$26,260.00	Hardwired	820 lbs	20.3" x 41.3" x 54"
M90U-20k06BM*	Bundle	20kVA/20kW 11 minute battery	\$28,040.00	Hardwired	956 lbs	20.3" x 41.3" x 54"
M90U-20k08BM	Bundle	20kVA/20kW 16 minute battery	\$29,820.00	Hardwired	1092 lbs	20.3" x 41.3" x 54"
M90U-20k10BM	Bundle	20kVA/20kW 21 minute battery	\$31,600.00	Hardwired	1228 lbs	20.3" x 41.3" x 54"
M90U-20k12BM	Bundle	20kVA/20kW 26 minute battery	\$33,380.00	Hardwired	1364 lbs	20.3" x 41.3" x 54"
M90U-40k08BM	Bundle	40kVA/40kW 6 minute battery	\$38,320.00	Hardwired	1166 lbs	20.3" x 41.3" x 54"
M90U-40k10BM	Bundle	40kVA/40kW 8 minute battery	\$40,100.00	Hardwired	1302 lbs	20.3" x 41.3" x 54"
M90U-40k12BM	Bundle	40kVA/40kW 11 minute battery	\$41,880.00	Hardwired	1438 lbs	20.3" x 41.3" x 54"
M90U-60k10BM	Bundle	60kVA/60kW 4 minute battery	\$48,600.00	Hardwired	1376 lbs	20.3" x 41.3" x 54"
M90U-60k12BM	Bundle	60kVA/60kW 6 minute battery	\$50,380.00	Hardwired	1512 lbs	20.3" x 41.3" x 54"

*non-TAA compliant models

M90U Series Pricing

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90-ENC (Unity)	99000872	M90 unity complete enclosure (60kVA max) includes large LCD display, static switch, and maintenance bypass. Holds up to 3 UPS modules, and 12 battery modules	\$14,200.00	484 lbs	20.3" x 41.3" x 54"
M90-PWRM (Unity)	99000870	M90 unity 20kVA/20kW power module	\$8,500.00	74 lbs	19.5" x 29.5" x 5.5"
M90-PWRM15 (Unity)	99000871	M90 unity 15kVA/15kW power module	\$6,700.00	73 lbs	19.5" x 29.5" x 5.5"
M90-BOS	90000852	M90L matching external battery cabinet	\$5,500.00	227 lbs	29.5" x 39.4" x 30"
M90-BATT	90000563	M90 battery tray (10) UPS 12580	\$890.00	68 lbs	4.3" x 28.5" x 6.5"
M90-BATT-EMPTY	90000885	Empty M90 battery tray	\$460.00	10 lbs	4.3" x 28.5" x 6.5"
M90 SKIRT	90000565	Skirt kit for M90	\$380.00	20 lbs	7" x 43.5" x 6.5"
M90-SEIS	90000678	Seismic hold down anchorage**	\$1,900.00	TBA	TBA
M90-AT60KW	90000679	Auto transformer for 60kW 208/480VAC or 480/208VAC*	\$3,900.00	309 lbs	18" x 9" x 47.75"

*Input neutral is required **Must order one seismic kit for each enclosure and battery cabinet.

M90U Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2P3	90000566	Two port internal SNMP card	\$349.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Environmental monitoring device*	\$180.00	1 lb	7.25" x 6" x 2.5"
M90-COMM	90000498	Extra communication card for M90	\$370.00	1 lb	5.7" x 5.2" x 1.7"
M90-BTS	90000796	Battery temperature sensor with 10' cable**	\$66.00	1 lb	5.7" x 5.2" x 1.7"

*SNMP-EMD to be used with SNMP-2P3 **One M90-BTS may be used directly with CN1 on M90 front panel. Up to 4 M90-BTS may be used with M90-COMM.

M90U Service Plans (USA and Canada)

Model	Part Number	Description	List Price
M90SU581	90000570	Startup 5x8 and 1 year on-site warranty	\$4,900
M90SU582	90000571	Startup 5x8 and 2 year on-site warranty	\$5,500
M90SU583	90000593	Startup 5x8 and 3 year on-site warranty	\$8,400
M90SU7242	90000592	Startup 7x24 and 2 year on-site warranty	\$7,150
M90SU7245	90000647	Startup 7x24 and 5 year on-site warranty	\$17,900
M90EXW1YR	90000594	1 year factory warranty extension	\$3,200
M90PM724	90000648	M90 preventative maintenance service, 7x24	\$4,600
SVCADD	90000538	Service adder for locations further than 100 miles	\$1,050

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

M90U Series Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (KVA)	5	10	15	20	25	30	35	40	45	50	55	60
2 battery modules	16	6	-	-	-	-	-	-	-	-	-	-
4 battery modules	37	16	9	6	-	-	-	-	-	-	-	-
6 battery modules	60	26	16	11	8	6	-	-	-	-	-	-
8 battery modules	85	37	23	16	12	9	8	6	5	-	-	-
10 battery modules	110	48	30	21	16	13	10	9	7	6	5	4
12 battery modules	127	60	37	26	20	16	13	11	9	8	7	6

Runtimes are shown in minutes and will vary based on battery age and site conditions. Runtimes are based on fully formed batteries.

M90U-80 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Capacities: 15kVA/15kW, 20kVA/20kW, 30kVA/30kW, 40kVA/40kW, 45kVA/45kW,
60kVA/60kW, 80kVA/80kW
208/120VAC Three-phase

Mission critical availability with scalable, modular, high density
M90U-80 for 15-80kVA applications

- › Modular and upgradeable for capacity or redundancy
- › Hot swappable power and battery modules
- › Large 10" LCD touchscreen display
- › Unity power factor
- › UL-1778, cUL, FCC A, RoHS, TAA (select models)
- › 2 year warranty (USA and Canada)



M90U-80 Series 208/120VAC Three phase 20/40/60/80kVA bundles including internal maintenance bypass

Input neutral is required

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U80-20K00B	Bundle	20kVA/20kW no internal batteries*	\$28,500.00	Hardwired	731 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K04B	Bundle	20kVA/20kW 6 minute battery	\$32,460.00	Hardwired	1011 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K06B	Bundle	20kVA/20kW 11 minute battery	\$34,440.00	Hardwired	1151 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K08B	Bundle	20kVA/20kW 16 minute battery	\$36,420.00	Hardwired	1291 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K10B	Bundle	20kVA/20kW 21 minute battery	\$38,400.00	Hardwired	1431 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K12B	Bundle	20kVA/20kW 26 minute battery	\$40,380.00	Hardwired	1571 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K14B	Bundle	20kVA/20kW 31 minute battery	\$42,360.00	Hardwired	1711 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-20K16B	Bundle	20kVA/20kW 37 minute battery	\$44,340.00	Hardwired	1851 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K00B	Bundle	40kVA/40kW no internal batteries*	\$37,000.00	Hardwired	805 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K08B	Bundle	40kVA/40kW 6 minute battery	\$44,920.00	Hardwired	1365 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K10B	Bundle	40kVA/40kW 8 minute battery	\$46,900.00	Hardwired	1505 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K12B	Bundle	40kVA/40kW 11 minute battery	\$48,880.00	Hardwired	1645 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K14B	Bundle	40kVA/40kW 13 minute battery	\$50,860.00	Hardwired	1785 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-40K16B	Bundle	40kVA/40kW 16 minute battery	\$52,840.00	Hardwired	1925 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60K00B	Bundle	60kVA/60kW no internal batteries*	\$45,500.00	Hardwired	879 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60K10B	Bundle	60kVA/60kW 4 minute battery	\$55,400.00	Hardwired	1579 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60K12B	Bundle	60kVA/60kW 6 minute battery	\$57,380.00	Hardwired	1719 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60K14B	Bundle	60kVA/60kW 8 minute battery	\$59,360.00	Hardwired	1859 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60K16B	Bundle	60kVA/60kW 9 minute battery	\$61,340.00	Hardwired	1999 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-80K00B	Bundle	80kVA/80kW no internal batteries*	\$54,000.00	Hardwired	953 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-80K14B	Bundle	80kVA/80kW 4 minute battery	\$67,860.00	Hardwired	1933 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-80K16B	Bundle	80kVA/80kW 6 minute battery	\$69,840.00	Hardwired	2073 lbs	23.6"W x 43.3"D x 79.1"H

*For use with external battery cabinet.

M90U-80 Series 208/120VAC Three phase 15/30/45/60kVA bundles including internal maintenance bypass

Input neutral is required

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U80-15K00B	Bundle	15kVA/15kW no internal batteries*	\$26,700.00	Hardwired	730 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K04B	Bundle	15kVA/15kW 9 minute battery	\$30,660.00	Hardwired	1010 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K06B	Bundle	15kVA/15kW 16 minute battery	\$32,640.00	Hardwired	1150 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K08B	Bundle	15kVA/15kW 22 minute battery	\$34,620.00	Hardwired	1290 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K10B	Bundle	15kVA/15kW 29 minute battery	\$36,600.00	Hardwired	1430 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K12B	Bundle	15kVA/15kW 37 minute battery	\$38,580.00	Hardwired	1570 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K14B	Bundle	15kVA/15kW 44 minute battery	\$40,560.00	Hardwired	1710 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-15K16B	Bundle	15kVA/15kW 52 minute battery	\$42,540.00	Hardwired	1850 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K00B	Bundle	30kVA/30kW no internal batteries*	\$33,400.00	Hardwired	803 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K06B	Bundle	30kVA/30kW 6 minute battery	\$39,340.00	Hardwired	1223 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K08B	Bundle	30kVA/30kW 9 minute battery	\$41,320.00	Hardwired	1363 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K10B	Bundle	30kVA/30kW 12 minute battery	\$43,300.00	Hardwired	1503 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K012B	Bundle	30kVA/30kW 16 minute battery	\$45,280.00	Hardwired	1643 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K014B	Bundle	30kVA/30kW 19 minute battery	\$47,260.00	Hardwired	1783 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-30K16B	Bundle	30kVA/30kW 22 minute battery	\$49,240.00	Hardwired	1923 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K00B	Bundle	45kVA/45kW no internal batteries*	\$40,100.00	Hardwired	876 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K08B	Bundle	45kVA/45kW 5 minute battery	\$48,020.00	Hardwired	1436 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K10B	Bundle	45kVA/45kW 7 minute battery	\$50,000.00	Hardwired	1576 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K12B	Bundle	45kVA/45kW 9 minute battery	\$51,980.00	Hardwired	1716 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K14B	Bundle	45kVA/45kW 11 minute battery	\$53,960.00	Hardwired	1856 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-45K16B	Bundle	45kVA/45kW 14 minute battery	\$55,940.00	Hardwired	1996 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60Ka00B	Bundle	60kVA/60kW no internal batteries*	\$46,800.00	Hardwired	949 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60Ka10B	Bundle	60kVA/60kW 4 minute battery	\$56,700.00	Hardwired	1889 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60Ka12B	Bundle	60kVA/60kW 6 minute battery	\$58,680.00	Hardwired	2029 lbs	23.6"W x 43.3"D x 79.1"H
M90U80-60Ka14B	Bundle	60kVA/60kW 8 minute battery	\$60,660.00	Hardwired	2169 lbs	23.6"W x 43.3"D x 79.1"H

*For use with external battery cabinet

M90-BC Modular Battery Cabinet with Battery Modules Bundles

M90-BC includes up to 8 battery strings, each with individual front facing breakers

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90-BC-04B	Bundle	M90-BC with 4 battery modules	\$16,300.00	Hardwired	1200 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-08B	Bundle	M90-BC with 8 battery modules	\$20,400.00	Hardwired	1540 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-12B	Bundle	M90-BC with 12 battery modules	\$24,500.00	Hardwired	1880 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-16B	Bundle	M90-BC with 16 battery modules	\$28,600.00	Hardwired	2220 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-20B	Bundle	M90-BC with 20 battery modules	\$32,700.00	Hardwired	2560 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-24B	Bundle	M90-BC with 24 battery modules	\$36,800.00	Hardwired	2900 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-28B	Bundle	M90-BC with 28 battery modules	\$40,900.00	Hardwired	3240 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-32B	Bundle	M90-BC with 32 battery modules	\$45,000.00	Hardwired	3580 lbs	23.6"W x 43.3"D x 79.1"H

M90-BC is an external battery cabinet for use with M90U-80 without internal batteries (00B), M90U-140, or M90LU.

M90U-80 Series Pricing

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90-ENC80 (Unity)	99000874	M90U-80 complete enclosure (80kVA max) includes large LCD display, static switch, and maintenance bypass. Holds up to 4 UPS modules, and 16 M90-80BAT battery modules	\$20,000.00	657 lbs	23.6" x 43.3" x 79.1"
M90-PWRM (Unity)	99000870	M90 unity 20kVA/20kW power module	\$8,500.00	74 lbs	19.5" x 29.5" x 5.5"
M90-PWRM15 (Unity)	99000871	M90 unity 15kVA/15kW power module	\$6,700.00	73 lbs	19.5" x 29.5" x 5.5"
M90-BC	90000716	External modular battery cabinet. Holds up to 32 M90-BCBAT battery modules. See below (M90-CBL) for optional Battery to UPS cable	\$12,200.00	860 lbs	23.6" x 43.8" x 79.1"
M90-BCBAT	90000764	M90-BC Battery Module with (5) HR1290 batteries. Fits M90-BC External Battery Cabinet	\$1,025.00	85 lbs	7.3" x 38.5" x 3.2"
M90-80BAT	90000763	M90U-80 battery tray (10) UPS 12580	\$990.00	70 lbs	4.3" x 28.5" x 6.5"
M90-80BT	90000851	Empty battery tray for M90-80	\$500.00	15 lbs	4.3" x 28.5" x 6.5"
M90-BCBT	90000851	Empty battery tray for M90-BC	\$525.00	14 lbs	7.3" x 38.5" x 3.2"
M90-BUS	90000767	M90BC paralalled busbar kit	\$500.00	9 lbs	20"W x 4"D x 2.5" H
M90-SEIS	90000678	Seismic hold down anchorage*	\$1,900.00	TBA	TBA
M90-CBL	90001213	8' Cable kit for M90-BC to M90(U)-80/140	\$1,050.00	69 lbs	24" x 20" x 8"

*Must order one seismic kit for each enclosure and battery cabinet.

M90U-80 Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2P3	90000566	Two port internal SNMP card	\$349.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Enviromental monitoring device*	\$180.00	1lb	7.25" x 6" x 2.5"
M90-COMM	90000498	Extra communication card for M90-80	\$370.00	1.b	5.7" x 5.2" x 1.7"
M90-BTS	90000796	Battery temperature sensor with 10' cable	\$66.00	1 lb	5.7" x 5.2" x 1.7"

*SNMP-EMD to be used with SNMP-2P3 **One M90-BTS may be used directly with CN6 on the STS module. Up to 4 M90-BTS may be used with M90-COMM.

M90U-80 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
M90814SU581	90000768	Startup 5x8 and 1 year on-site warranty	\$5,900
M90814SU582	90000769	Startup 5x8 and 2 year on-site warranty	\$6,500.00
M90814SU583	90000770	Startup 5x8 and 3 year on-site warranty	\$9,600.00
M90814SU72	90000772	Startup 7x24 and 2 year on-site warranty	\$8,450.00
M90814SU73	90000773	Startup 7x24 and 3 year on-Site warranty	\$11,700.00
M90814EX1	90000774	1 year factory warranty extension	\$4,200.00
M90814PM7	90000775	M90U-80 preventative maintenance service, 7x24	\$4,900.00
SVCADD	9000077	Service adder for locations further than 100 miles	\$1,050.00

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

M90U-80 Service Plans for M90-BC (USA and Canada)

Example: On-site 3 year warranty and startup for M90-BC-12B (12 battery modules) system would need Qty (1) M90814SU583 + (12) MS0S3BM

Model	Module Service Plans	On-site 2 Year Warranty	On-site 3 Year Warranty
M90-BCBAT	M90-BCBAT battery module. Order one service plan for each battery purchased.	Model - TBD	Model - MS0S3BM
		TBD	PN: 90000729
		List: \$250	List:\$350

* Startup must be purchased for all on-site service plans. * Same level plan must be purchased for all battery modules.

Internal Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (kVA)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80
4 battery modules	37	16	9	6	-	-	-	-	-	-	-	-	-	-	-	-
6 battery modules	60	26	16	11	8	6	5	-	-	-	-	-	-	-	-	-
8 battery modules	85	37	23	16	12	9	8	6	5	-	-	-	-	-	-	-
10 battery modules	110	48	30	21	16	13	10	9	7	6	5	-	-	-	-	-
12 battery modules	127	60	37	26	20	16	13	11	9	8	7	6	-	-	-	-
14 battery modules	146	73	44	31	24	19	16	13	11	10	9	8	7	6	5	-
16 battery modules	169	85	52	37	28	23	19	16	13	12	10	9	8	7.5	7	6

Runtimes are shown in minutes and will vary based on battery age and site conditions. Runtimes are based on fully formed batteries.

M90-BC Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (KVA)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80
4 battery modules	40	16	10	5	-	-	-	-	-	-	-	-	-	-	-	-
8 battery modules	97	40	24	16	13	10	7	5	-	-	-	-	-	-	-	-
12 battery modules	154	67	40	28	21	16	14	12	10	8	7	5	-	-	-	-
16 battery modules	216	97	58	40	30	24	20	16	15	13	11	10	8	7	6	5
20 battery modules	283	126	77	53	40	32	26	22	19	16	15	13	12	11	10	9
24 battery modules	346	154	97	67	50	40	33	28	24	21	18	16	15	14	13	12
28 battery modules	410	185	118	82	61	49	40	34	29	25	22	20	18	16.5	15	14
32 battery modules	475	216	134	97	73	58	47	40	34	30	27	24	21	20	18	16
36 battery modules	541	248	154	113	84	67	55	46	40	35	31	28	25	23	21	19
40 battery modules	608	283	174	126	97	77	63	53	46	40	35	32	29	26	24	22
44 battery modules	675	316	195	139	110	86	71	60	52	45	40	36	32	29	27	25
48 battery modules	743	346	216	154	121	97	79	67	58	50	45	40	36	33	30	28
52 battery modules	812	378	237	169	131	108	88	74	64	56	49	44	40	36	33	31
56 battery modules	881	410	259	185	142	118	97	82	70	61	54	49	44	40	37	34
60 battery modules	951	442	283	200	154	126	106	89	77	67	59	53	48	44	40	37
64 battery modules	1022	475	305	216	166	134	115	97	83	73	64	58	52	47	43	40

For runtimes with more than 32 battery modules, a second M90-BC must be used. A parallel bus bar kit is required for all bundles that include (2) M90-BC.

M90U-140 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Modular Online UPS

Capacities: 15kVA/15kW to 140kVA/140kW in 15kVA or 20kVA increments.

208/120VAC Three-phase

Mission critical availability with scalable, modular, high density

M90-140 for 15-140kVA (N+1) applications.

- › Modular and upgradeable for capacity or redundancy
- › Hot swappable power and battery modules
- › Front access design
- › Large 10" LCD touchscreen display
- › Unity power factor
- › Remote control and monitoring options
- › UL-1778, cUL, FCC A, RoHS, TAA (select models)
- › 2 year warranty (USA and Canada)



M90U-140 Series 208/120VAC Three phase 20KVA - 140KVA bundles including internal maintenance bypass (no batteries)

Input neutral is required

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U140-20K	Bundle	20kVA/20kW	\$34,500.00	Hardwired	731 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-40K	Bundle	40kVA/40kW	\$43,000.00	Hardwired	805 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-60K	Bundle	60kVA/60kW	\$51,500.00	Hardwired	879 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-80K	Bundle	80kVA/80kW	\$60,000.00	Hardwired	953 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-100K	Bundle	100kVA/100kW	\$68,500.00	Hardwired	1027 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-120K	Bundle	120kVA/120kW	\$77,000.00	Hardwired	1101 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-140K	Bundle	140kVA/140kW	\$85,500.00	Hardwired	1175 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-140KN1	Bundle	140kVA/140kW (N+1)	\$94,000.00	Hardwired	1249 lbs	23.6"W x 43.3"D x 79.1"H

M90U-140 Series 208/120VAC Three phase 15KVA - 105kVA bundles including internal maintenance bypass (no batteries)

Input neutral is required

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90U140-15K	Bundle	15kVA/15kW	\$32,700.00	Hardwired	730 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-30K	Bundle	30kVA/30kW	\$39,400.00	Hardwired	803 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-45K	Bundle	45kVA/45kW	\$46,100.00	Hardwired	876 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-60Ka	Bundle	60kVA/60kW	\$52,800.00	Hardwired	949 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-75K	Bundle	75kVA/75kW	\$59,500.00	Hardwired	1022 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-90K	Bundle	90kVA/90kW	\$66,200.00	Hardwired	1095 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-105K	Bundle	105kVA/105kW	\$72,900.00	Hardwired	1169 lbs	23.6"W x 43.3"D x 79.1"H
M90U140-105KN1	Bundle	105kVA/105kW (N+1)	\$79,600.00	Hardwired	1242 lbs	23.6"W x 43.3"D x 79.1"H

M90-BC Modular Battery Cabinet with Battery Modules Bundles*M90-BC includes up to 8 battery strings, each with individual front facing breakers*

Model	Part Number	Description	List Price	Input & Output Connection	Unit Weight	Unit Dimensions (W x D x H)
M90-BC-04B	Bundle	M90-BC with 4 battery modules	\$16,300.00	Hardwired	1200 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-08B	Bundle	M90-BC with 8 battery modules	\$20,400.00	Hardwired	1540 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-12B	Bundle	M90-BC with 12 battery modules	\$24,500.00	Hardwired	1880 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-16B	Bundle	M90-BC with 16 battery modules	\$28,600.00	Hardwired	2220 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-20B	Bundle	M90-BC with 20 battery modules	\$32,700.00	Hardwired	2560 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-24B	Bundle	M90-BC with 24 battery modules	\$36,800.00	Hardwired	2900 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-28B	Bundle	M90-BC with 28 battery modules	\$40,900.00	Hardwired	3240 lbs	23.6"W x 43.3"D x 79.1"H
M90-BC-32B	Bundle	M90-BC with 32 battery modules	\$45,000.00	Hardwired	3580 lbs	23.6"W x 43.3"D x 79.1"H

*M90-BC is an external battery cabinet for use with M90U-80 without internal batteries (00B), M90U-140, or M90LU.***M90U-140 Series Pricing**

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
M90-ENC140 (Unity)	99000875	M90U-140 power module enclosure (kVA max) includes large LCD display, static switch, and maintenance bypass. Holds up to 8 UPS modules	\$26,000.00	657 lbs	23.6" x 43.3" x 79.1"
M90-PWRM (Unity)	99000870	M90 unity 20kVA/20kW power module	\$8,500.00	74 lbs	19.5" x 29.5" x 5.5"
M90-PWRM15 (Unity)	99000871	M90 unity 15kVA/15kW power module	\$6,700.00	73 lbs	19.5" x 29.5" x 5.5"
M90-BC	90000716	External modular battery cabinet. Holds up to 32 M90-BCBAT battery modules. See below (M90-CBL) for optional Battery to UPS cable	\$12,200.00	860 lbs	23.6" x 43.8" x 79.1"
M90-BCBAT	90000764	M90-BC Battery Module with (5) HR1290 batteries. Fits M90-BC External Battery Cabinet	\$1,025.00	85 lbs	7.3" x 38.5" x 3.2"
M90-BCBT	90000851	Empty battery tray for M90-BC	\$525.00	14 lbs	7.3" x 38.5" x 3.2"
M90-BUS	90000767	M90-BC paralld busbar kit	\$500.00	9 lbs	20"W x 4"D x 2.5" H
M90-SEIS	90000678	Seismic hold down anchorage*	\$1,900.00	TBA	TBA
M90-CBL	90001213	8' Cable kit for M90-BC to M90(U)-80/140	\$1,050.00	69 lbs	24" x 20" x 8"

Must order one seismic kit for each enclosure and battery cabinet.*M90U-140 Series Connectivity**

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2P3	90000566	Two port internal SNMP card	\$349.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319.00	1 lb	7.25" x 6" x 2.5"
SNMP-EMD	90000398	Enviromental monitoring device*	\$180.00	1lb	7.25" x 6" x 2.5"
M90-COMM	90000498	Extra communication card	\$370.00	1.b	5.7" x 5.2" x 1.7"
M90-BTS	90000796	Battery temperature sensor with 10' cable**	\$66.00	1 lb	5.7" x 5.2" x 1.7"

SNMP-EMD to be used with SNMP-2P3 **One M90-BTS may be used directly with CN6 on the STS module. Up to 4 M90-BTS may be used with M90-COMM.*M90U-140 Service Plans (USA and Canada)**

Model	Part Number	Description	List Price
M90814SU581	90000768	Startup 5x8 and 1 year on-site warranty	\$5,900
M90814SU582	90000769	Startup 5x8 and 2 year on-site warranty	\$6,500.00
M90814SU583	90000770	Startup 5x8 and 3 year on-site warranty	\$9,600.00
M90814SU72	90000772	Startup 7x24 and 2 year on-site warranty	\$8,450.00
M90814SU73	90000773	Startup 7x24 and 3 year on-Site warranty	\$11,700.00
M90814EX1	90000774	1 year factory warranty extension	\$4,200.00
M90814PM7	90000775	M90U-80 preventative maintenance service, 7x24	\$4,900.00
SVCADD	9000077	Service adder for locations further than 100 miles	\$1,050.00

Standard 2 Year Factory UPS Warranty – 2 years electronics. Telephone technical support. Depot exchange. Ground shipment one way.**On Site Warranty** – Startup is included, telephone technical support. Ground shipment both ways.

M90U Service Plans for M90-BC (USA and Canada)

Example: On-site 3 year warranty and startup for M90-BC-12B (12 battery modules) system would need Qty (1) M90814SU583 + (12) MS0S3BM

Model	Module Service Plans	On-site 2 Year Warranty	On-site 3 Year Warranty
M90-BCBAT	M90-BCBAT battery module. Order one service plan for each battery purchased.	Model - TBD	Model - MS0S3BM
		TBD	PN: 90000729
		List: \$250	List:\$350

* Startup must be purchased for all on-site service plans. * Same level plan must be purchased for all battery modules.

M90U-140 UPS and Battery Cabinet Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (kVA)	5	10	15	20	25	30	35	40	45	50	55	60	65	70
4 battery modules	40	16	10	5	-	-	-	-	-	-	-	-	-	-
8 battery modules	97	40	24	16	13	10	7	5	-	-	-	-	-	-
12 battery modules	154	67	40	28	21	16	14	12	10	8	7	5	-	-
16 battery modules	216	97	58	40	30	24	20	16	15	13	11	10	8	7
20 battery modules	283	126	77	53	40	32	26	22	19	16	15	13	12	11
24 battery modules	346	154	97	67	50	40	33	28	24	21	18	16	15	14
28 battery modules	410	185	118	82	61	49	40	34	29	25	22	20	18	16
32 battery modules	475	216	134	97	73	58	47	40	34	30	27	24	21	20
36 battery modules	541	248	154	113	84	67	55	46	40	35	31	28	25	23
40 battery modules	608	283	174	126	97	77	63	53	46	40	35	32	29	26
44 battery modules	675	316	195	139	110	86	71	60	52	45	40	36	32	29
48 battery modules	743	346	216	154	121	97	79	67	58	50	45	40	36	33
52 battery modules	812	378	237	169	131	108	88	74	64	56	49	44	40	36
56 battery modules	881	410	259	185	142	118	97	82	70	61	54	49	44	40
60 battery modules	951	442	283	200	154	126	106	89	77	67	59	53	48	44
64 battery modules	1022	475	305	216	166	134	115	97	83	73	64	58	52	47

For runtimes with more than 32 battery modules, a second M90-BC must be used.

M90U-140 UPS and Battery Cabinet Runtimes (cont.)

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

System load (kVA)	75	80	85	90	95	100	105	110	115	120	125	130	135	140
16 battery modules	6	5	-	-	-	-	-	-	-	-	-	-	-	-
20 battery modules	10	9	8	7	6	5	-	-	-	-	-	-	-	-
24 battery modules	13	12	10	10	9	8	7	7	6	5	-	-	-	-
28 battery modules	15	14	13	12	11	10	10	9	9	8	7	7	6	5
32 battery modules	18	16	16	15	14	13	12	11	10	10	9	8	8	7
36 battery modules	21	19	18	16	16	15	14	13	12	12	11	10	10	9
40 battery modules	24	22	20	19	18	16	16	15	14	15	13	12	11	11
44 battery modules	27	25	23	21	20	19	17	17	16	15	14	14	13	12
48 battery modules	30	28	26	24	22	21	20	18	17	17	16	15	15	14
52 battery modules	33	31	28	26	25	23	22	20	19	18	17	17	16	15
56 battery modules	37	34	31	29	27	25	24	22	21	20	19	18	17	17
60 battery modules	40	37	34	32	30	28	26	24	23	22	21	20	19	18
64 battery modules	43	40	37	34	32	30	28	27	25	24	23	21	20	20

For runtimes with more than 32 battery modules, a second M90-BC must be used.

X90-2S Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

2 Slot Modular Online UPS

Capacities: 50kW, 70kW, 100kW, 140kW

480VAC 3W Three-phase

**Mission critical availability with scalable, modular, high density
X90-2S for 50-140kW applications.**

- › Modular and upgradeable for capacity or redundancy
- › Hot swappable power and battery modules
- › 65kAIC internal maintenance bypass
- › Front access design
- › Large 10" LCD touchscreen display
- › Up to 96.5% online mode, or 99% ECO mode
- › Unity power factor
- › UL-1778, cUL, FCC A, TAA, RoHS
- › 5x8 Startup and 2 Year on-site warranty (USA and Canada)



X90-2S Series 480VAC 3W Three phase 50kW - 140kW bundles including internal maintenance bypass

X90-2S holds up to 2 power modules and 20 battery modules. 5x8 Startup and 2 Year on-site warranty (USA and Canada)

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
X902S-50K00B	Bundle	50kVA/50kW no internal batteries	\$45,300.00	761 lbs	23.6" x 42" x 79"
X902S-50K12B	Bundle	50kVA/50kW 8 minute battery	\$57,180.00	1601 lbs	23.6" x 42" x 79"
X902S-50K16B	Bundle	50kVA/50kW 12 minute battery	\$61,140.00	1881 lbs	23.6" x 42" x 79"
X902S-50K20B	Bundle	50kVA/50kW 16 minute battery	\$65,100.00	2161 lbs	23.6" x 42" x 79"
X902S-70K00B	Bundle	70kVA/70kW no internal batteries	\$46,200.00	762 lbs	23.6" x 42" x 79"
X902S-70K16B	Bundle	70kVA/70kW 8 minute battery	\$62,040.00	1882 lbs	23.6" x 42" x 79"
X902S-70K20B	Bundle	70kVA/70kW 10 minute battery	\$66,000.00	2162 lbs	23.6" x 42" x 79"
X902S-100K00B	Bundle	100kVA/100kW no internal batteries	\$54,900.00	865 lbs	23.6" x 42" x 79"
X902S-100K20B	Bundle	100kVA/100kW 6 minute battery	\$74,700.00	2265 lbs	23.6" x 42" x 79"
X902S-140K00B	Bundle	140kVA/140kW no internal batteries	\$56,700.00	867 lbs	23.6" x 42" x 79"
X902S-140K28B	Bundle	140kVA/140kW 6 minute battery (with X90-BC)	\$90,920.00	867 lbs (UPS) 2376 lbs (BC)	23.6" x 42" x 79" (UPS) 23.6" x 42" x 79" (BC)

X90-BC Modular Battery Cabinet with Battery Modules Bundles

X90-BC holds up to 36 battery modules (4 modules per string)

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
X90BC-04B	Bundle	X90-BC with 4 battery modules	\$10,460.00	696 lbs	23.6"x 42"x 79.1"
X90BC-08B	Bundle	X90-BC with 8 battery modules	\$14,420.00	976 lbs	23.6"x 42"x 79.1"
X90BC-12B	Bundle	X90-BC with 12 battery modules	\$18,380.00	1256 lbs	23.6"x 42"x 79.1"
X90BC-16B	Bundle	X90-BC with 16 battery modules	\$22,340.00	1536 lbs	23.6"x 42"x 79.1"
X90BC-20B	Bundle	X90-BC with 20 battery modules	\$26,300.00	1816 lbs	23.6"x 42"x 79.1"
X90BC-24B	Bundle	X90-BC with 24 battery modules	\$30,260.00	2096 lbs	23.6"x 42"x 79.1"
X90BC-28B	Bundle	X90-BC with 28 battery modules	\$34,220.00	2376 lbs	23.6"x 42"x 79.1"
X90BC-32B	Bundle	X90-BC with 32 battery modules	\$38,180.00	2656 lbs	23.6"x 42"x 79.1"
X90BC-36B	Bundle	X90-BC with 36 battery modules	\$42,140.00	2936 lbs	23.6"x 42"x 79.1"

X90 Series Pricing

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
X90-ENC2S	90001013	X90-2S power module enclosure (140kW max) includes large LCD display, static switch, and maintenance bypass. Holds up to 2 UPS modules and 20 battery modules. 5x8 Startup and 2 Year on-site warranty (USA and Canada)	\$35,700.00	657 lbs	23.6" x 42" x 79.1"
X90-2SPM50	90001016	50kW 480V 3W Power Module for X90-2S	\$9,600.00	104 lbs	19.5" x 29.5" x 5.5"
X90-2SPM70	90001017	70kW 480V 3W Power Module for X90-2S	\$10,500.00	105 lbs	19.5" x 29.5" x 5.5"
X90-BC	90001066	External modular battery cabinet. Holds up to (36) X90-BCBAT battery modules	\$6,500.00	416 lbs	23.6" x 42" x 79.1"
X90-BCBAT	90001067	X90-BC Battery Module with (10) UPS12580 batteries for X90-2S or X90-BC	\$990.00	70 lbs	4.3" x 28.5" x 6.5"
X90-BCBT	90001076	Empty battery tray for X90-2S or X90-BC	\$500.00	15 lbs	4.3" x 28.5" x 6.5"
X90-SC2S	90001071	Side car for bottom entry	\$900.00	350 lbs	14" x 42" x 79.1"
X90-SEIS	90001075	Seismic hold down anchorage*	\$1,900.00	50 lbs	37" x 2" x 2"

*Must order one seismic kit for each enclosure and battery cabinet.

X90-2S Series Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-2PG1	90001245	Two port internal SNMP card	\$649.00	1 lb	7.25" x 6" x 2.5"
MODBUS-IN	90000267	Internal modbus card	\$319.00	1 lb	7.25" x 6" x 2.5"
SNMP-TMPH	90001246	Temperature and humidity probe*	\$299.00	1 lb	7.25" x 6" x 2.5"
M90-BTS	90000796	Battery temperature sensor with 10' cable	\$66.00	1 lb	5.7" x 5.2" x 1.7"

*SNMP-TMPH to be used with SNMP-2PG1

X90-2S Service Plans (USA and Canada)

Model	Part Number	Description	List Price
X902SSU583	90001248	Upgrade standard warranty to 3 years. Includes (1) PM (5x8) to be performed at beginning of year three.*	\$6,500.00
X902SSU72	90001249	Upgrade standard warranty to include 7x24 coverage.*	\$2,800.00
X902SSU73	90001250	Upgrade standard warranty to 3 years and 7x24 coverage. Includes (1) PM (7x24) to be performed at beginning of year three.*	\$9,300.00
X902S1YREE	90001251	X90 One-year extension of factory on-site warranty, electronics only. This warranty covers parts and labor, extending standard factory warranty by 1yr. Includes (1) PM (7x24) to be performed at beginning of the extension year. Maximum of 5 years.	\$8,800.00
X902SPM7	90001252	X90-2S Preventative Maintenance Service, 7x24. For Zone 1 (within 100 miles of XPC Service Center).	\$5,800.00
SVCADD	N/A	Service adder for locations further than 100 miles	\$1,200.00

*Must be purchased concurrently with equipment. Zone 1 - within 100 miles of XPC Service Center.

On Site Warranty – Startup is included, telephone technical support. Ground shipment both ways.

BATTERY RUNTIMES

Battery Modules	X90-2S UPS				X90-2S UPS + X90-BC								
	8	12	16	20	24	28	32	36	40	44	48	52	56
30kW	9	15	21	27	34	41	48	56	63	71	79	87	95
50kW	-	7	11	15	18	22	26	30	34	38	43	47	52
70kW	-	-	7	10	12	15	17	20	23	26	28	31	35
80kW	-	-	6	8	10	13	15	17	19	22	24	27	29
100kW	-	-	-	6	7	9	11	13	15	17	18	20	22
140kW	-	-	-	-	-	6	7	8	10	11	12	14	15

Runtimes are shown in minutes and will vary based on battery age and site conditions.

R91 Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Three-phase Online 20kVA

415/240VAC, 400/230VAC, 380/220VAC

Reduce power consumption with 94% online efficiency

- › High output power factor of 0.9
- › Parallel for capacity or redundancy up to 4 modules
- › 50Hz or 60Hz operation
- › Online double conversion or ECO mode operation
- › 99% efficiency in single module systems in ECO mode
- › UL 1778, FCC A, CE, RoHS
- › 2 years depot warranty (USA only)



R91 Series UPS

Model	Part Number	Description	List Price	Input/Output	Unit Weight	Shipping Weight	Unit & Shipping Dimensions (W x D x H)
R91-20K	90000129	20kVA/18kW Three-phase UPS 3U with Rack Shelf Kit	\$12,800.00	Terminal block	68.4 lbs	91.5 lbs	17.4" x 22.8" x 5.2" 22.2" x 28.5" x 14.2"
BP-XR4U480A	90000390	R91 Battery Module 4U with hot swappable battery modules	\$6,400.00	N/A	280 lbs	300 lbs	17.4 x 33.9 x 7" 24.5" x 39" x 10"

R91 Connectivity

Model	Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
SNMP-R90	90000266	External Web/SNMP card	\$425.00	1 lb	7.3" x 3.5" x 1.8"

R91 Accessories

Model	Part Number	Description	List Price	Utility Input Connection	Load Output Connection	Unit Weight	Unit Dimensions (W x D x H)
R90-MBP40A	90000369	400V 40A Maintenance Bypass with Rotary Switch, Cable Kit, and UPS Interlock	\$3,000.00	Terminal block	Terminal block	10.5 lbs	17.0" x 9.0" x 3.5"
R91-IEC309	90000535	32A input/output IEC 309 cable kit	\$650.00	IEC 309	IEC 309	TBA	TBA

R91 Service Plans (USA and Canada)

Model	Part Number	Description	List Price
R91SU581	90000536	Startup 5x8 and 1 year on-site warranty	\$2,450.00
R91SU582	90000537	Startup 5x8 and 2 year on-site warranty	\$3,950.00

R91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Percentage load	20%	40%	60%	80%	100%
R91-20K + (1)BP-XR4U480A	52	23	14	9	7
R91-20K + (2)BP-XR4U480A	116	53	33	23	18
R91-20K + (3)BP-XR4U480A	170	87	53	38	29
R91-20K + (4)BP-XR4U480A	234	117	75	53	41
R91-20K + (5)BP-XR4U480A	300	140	99	70	53
R91-20K + (6)BP-XR4U480A	368	172	117	87	66
R91-20K + (7)BP-XR4U480A	437	204	131	104	80
R91-20K + (8)BP-XR4U480A	507	237	151	117	94

For longer runtimes please contact sales@xpcc.com

R91 Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Percentage load	20%	40%	60%	80%	100%
R91-20K + (1)BP-XR4U480A	52	23	14	9	7
R91-20K + (2)BP-XR4U480A	116	53	33	23	18
R91-20K + (3)BP-XR4U480A	170	87	53	38	29
R91-20K + (4)BP-XR4U480A	234	117	75	53	41
R91-20K + (5)BP-XR4U480A	300	140	99	70	53
R91-20K + (6)BP-XR4U480A	368	172	117	87	66
R91-20K + (7)BP-XR4U480A	437	204	131	104	80
R91-20K + (8)BP-XR4U480A	507	237	151	117	94
R91-20K + (1)BP-XR2U480A	28	13	7.2	4.7	3.2
R91-20K + (2)BP-XR2U480A	65	28	17	13	10

For longer runtimes please contact sales@xpcc.com

J40 Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Ultra-Slim Surge PDU

Protect digital signage from spikes and surges with ultra-slim J40 surge PDU

- › Slim and light weight J40 mounts easily behind flat panel displays
- › Primary applications: digital signage, kiosks, gaming machines, and Point of Sale (POS)
- › MOV over voltage and over temperature protection
- › Power reset button to allow manual cycling of power
- › Remote power switch provides remote reset on/off, and scheduling on J40SP
- › SNMP protocol (J40SP)
- › Easily mounts to wall or ceiling in any orientation
- › Optional detachable offset, right angle 5–15P power cord provides flexible installation
- › 5 year warranty (USA and Canada)



J40 Series

Model	Part Number	Description	List Price	Input	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
J40	90000463	10A 120V Surge PDU	\$210.00	IEC C14 inlet	(3) 5–15R	2.0 lbs	8.07" x 3.35" x 1.22"
J40SP	90000765	10A 120V Switched Surge PDU with Ethernet Switch	\$549.00	IEC C14 inlet	(3) 5–15R	3.75 lbs	8.07" x 7.87" x 1.22"
J40i	90000477	10A 230V Surge PDU	\$210.00	IEC C14 inlet	(3) IEC C13	2.0 lbs	8.07" x 7.87" x 1.22"

J40 Input Cords

Model	Description	List Price	Unit Weight
XPC-515P-3RA	3ft line cord with offset, right angle 5–15P	\$22.00	0.5 lbs
XPC-515P-6RA	6ft line cord with offset, right angle 5–15P	\$22.00	0.5 lbs

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

Standard 3 Year Factory Warranty – (Outside USA & Canada) 3 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

JX Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolation Transformer Power Conditioner 120VAC

Power conditioning for critical electronic equipment

- › Toroidal Isolation Transformer Technology
- › Complete Line Isolation
- › Common Mode and Normal Mode Noise Filtering
- › Enhanced Surge Suppression
- › Easily mounts to wall or ceiling in any orientation
- › Optional detachable offset, right angle 5–15P power cord provides flexible installation
- › UL 60950-1 RoHS
- › 5 years warranty (USA & Canada)



JX Series Power Conditioner 120V 50/60Hz

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
JX-200	90000742	J60 200W Isolation Transformer 120V/120V	\$220.00	IEC C13 to 5-15P, 3 ft	(3) 5–15R	7 lbs	6.9" x 8.5" x 1.25"

JX Accessories

Model	Part Number	Description	List Price	Unit Weight
XPC-515P-3RA	N/A	3ft line cord with offset, right angle 5–15P for use with JX-200	\$22.00	1 lbs
XPC-515P-6RA	N/A	6ft line cord with offset, right angle 5–15P for use with JX-200	\$22.00	1 lbs

Standard 5 Year Factory Warranty – (USA & Canada) 5 years electronics/battery. Telephone technical support. Depot exchange. Ground shipment one way.

XBDM Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Bypass Distribution Module

Repair or replace your UPS without power interruption by manually transferring critical loads from UPS power to utility power using the XBDM

The following features apply to all XBDM except XBDM-MINI

- › Available in: 15A, 20A, and 30A models
- › Simplifies UPS repair or replacement and reduces costly downtime
- › Easy cord connection to UPS
- › Offers surge protection during UPS and utility mode
- › Bypass switch provides transfer within 4–8ms
- › Supports horizontal 1U rack mount and vertical rack mount installation
- › UPS and utility power are connected to the XBDM with the supplied cords



XBDM Series

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-1015LV	90000090	Bypass Distribution Module 15A/120VAC	\$379.00	5–15P, 12ft	(6) 5–15R front (4) 5–15R back	5–15R	3.5 lbs	19.3" x 3.5" x 1.75"
XBDM-1020LV	90000091	Bypass Distribution Module 20A/120VAC	\$419.00	5–20P, 12ft	(6) 5–20R front (4) 5–20R back	5–20R	3.5 lbs	19.3" x 3.5" x 1.75"
XBDM-1030LV	90000093	Bypass Distribution Module 30A/120VAC	\$659.00	L5–30P, 6ft	(5) 5–20R front (5) 5–20R back	L5–30R	3.5 lbs	19.3" x 3.5" x 1.75"
XBDM1020HV1	90000095	Bypass Distribution Module 1U/0U with 16A Capacity (Includes IEC C20 C13 Cord Kit)	\$369.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"
XBDM1020HV2	90000094	Bypass Distribution Module 1U/0U with 16A Capacity (Includes (2) IEC C20 C19 Cord Kit)	\$419.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back	IEC C20	3.5 lbs	19.3" x 3.5" x 1.75"

XBDM HW Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Bypass Distribution Module

XBDM HW provides UPS maintenance bypass with input and output hardwired terminal block connections

- › Available in: 15A, 20A, 30A, and 63A models
- › Simplifies UPS repair or replacement and reduces costly downtimes
- › Hardwired input and output with easy cord connection to UPS
- › Bypass switch provides transfer within 8ms
- › 63A model provides make before break transfer and interlock UPS for static switch
- › Wall and rack mounting hardware include



XBDM HW Series

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM-15RHW	90000949	15A/120VAC Bypass Distribution Module	\$369.00	Hardwire terminal block	Hardwire terminal block + (6) 5-15R	5-15P 5-20R	4 lbs	17" x 3.5" x 1.75"
XBDM-20RHW	90000950	20A/120VAC Bypass Distribution Module	\$369.00	Hardwire terminal block	Hardwire terminal block + (6) 5-15R	5-20P 5-20R	4 lbs	17" x 3.5" x 1.75"
XBDM-HW30	90000947	30A/120VAC Bypass Distribution Module	\$620.00	Hardwire or optional L5-30P cable kit	Hardwire terminal block or optional L5-30R cable kit	L5-30P L5-30R	7.3 lbs	17.3" x 5.3" x 3.5"
XBDM-HW63	90000934	63A/230VAC Bypass Distribution Module	\$570.00	Hardwire or optional cable kit	Hardwire terminal block	Hardwire or optional cable kit	7.1 lbs	17.3" x 5.3" x 3.5"

*Optional cable kit pricing available up request

XPDU Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Power Distribution Unit

Rack power distribution solutions designed to meet the needs of any data center or wiring closet

- › On/off control of individual receptacles
- › Total power monitoring software
- › User defined alarm thresholds and event alerts
- › Branch circuit protection
- › Rack, tower, or wall mount
- › UL, cUL, FCC, CE (varies by model)
- › 3 year full warranty (USA and Canada)



XPDU Series

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
Basic PDU – 15A & 20A Models							
XP815HV	90000040	15A 120V 1U 19" Basic Rack PDU	\$120.00	5–15P, 12ft	(8) 5–15R	2.6 lbs	19.0" x 3.5" x 1.75"
XP815HV	90000041	15A 120V 1U 19" Basic Rack PDU	\$138.00	5–15P, 12ft	(14) 5–15R	3.5 lbs	19.0" x 3.5" x 1.75"
XP81420HV	90000045	20A 120V 1U 19" Basic Rack PDU	\$190.00	L5–20P, 12ft**	(14) 5–15/20R	4.8 lbs	19.0" x 3.5" x 1.75"
XPDU-IEC	90000053	15/20A 230V 1U 19" Basic Rack PDU	\$190.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
Basic PDU – 30A & 50A Models							
XP824C13V	90000374	30A 208V Basic PDU	\$340.00	L6–30P, 6ft	(24) C13	12.0 lbs	66.0" x 1.75" x 1.75"
XP831	90000251	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (2) L6–20R + (4) 6–15/20R	9.0 lbs	19.0" x 4.7" x 3.5"
XP832	90000252	30A 240V 2U 19" Basic Rack PDU	\$580.00	L6–30P, 6ft	(2) L6–30R + (4) L6–20R	7.5 lbs	19.0" x 2.4" x 3.5"
XP833	90000253	30A 240V 2U 19" Basic Rack PDU	\$450.00	L6–30P, 6ft	(4) IEC C19 + (8) IEC C13	6.0 lbs	19.0" x 2.4" x 3.5"
XP834	90000254	30A 240/120V 2U 19" Basic Rack PDU	\$690.00	L14–30P, 6ft	(2) L6–30R + (4) L6–20R + (12) 5–15/20R	9.5 lbs	19.0" x 4.7" x 3.5"
XP835	90000255	50A 240V 2U 19" Basic Rack PDU	\$580.00	Pigtail 2W+G	(2) L6–30R + (4) L6–20R	7.0 lbs	19.0" x 2.4" x 3.5"
XP836	90000256	50A 240V 2U 19" Basic Rack PDU	\$460.00	Pigtail 2W+G	(4) IEC C19 + (8) IEC C13	6.8 lbs	19.0" x 2.4" x 3.5"
XP837	90000257	50A 240/120V 2U 19" Basic Rack PDU	\$690.00	Pigtail 3W+G	(2) L6–30R + (4) L6–20R + (12) 5–15/20R	10.0 lbs	19.0" x 4.7" x 3.5"
XP838	90001037	30A 120V 2U 19" Basic Rack PDU	\$690.00	L14–30P, 6ft	(4) L5–30R + (4) L5–20R	9.5 lbs	19.0" x 4.7" x 3.5"
XP839	90001038	50A 120V 2U 19" Basic Rack PDU	\$690.00	Pigtail 3W+G	(4) L5–30R + (4) L5–20R	10.0 lbs	19.0" x 4.7" x 3.5"

XPDU Surge Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Surge Power Distribution Unit

Rack power distribution solutions designed to meet the needs of any audio or wiring closet application

- › Available 120V models: 15A and 20A
- › Surge protection function is monitored by front LED
- › Branch circuit protection
- › 1U Rack mounting or 0U vertical mounting
- › UL 1449, cUL, CE listed (Varies by model)
- › 3 year full warranty (USA and Canada)



XPDU Series

Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
Surge PDU							
XPDS1015HV	90000048	15A 120V 1U 19" Rack Surge PDU rated for 342 joules	\$159.00	5-15P, 6ft	(10) 5-15R	4.4 lbs	19.0" x 3.5" x 1.75"
XPDS1020HV	90000049	20A 120V 1U 19" Rack Surge PDU rated for 342 joules	\$179.00	5-20P, 6ft**	(10) 5-15/20R	4.6 lbs	19.0" x 3.5" x 1.75"


Isolation PDU Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Isolation Power Distribution Unit

Rack isolation transformer solutions designed to meet the voltage and power quality requirements

- › 208/240V input and 120/208/240V output
- › Vertical and horizontal mounting
- › UL, cUL, FCC, CE (varies by model)
- › 3 year full warranty (USA and Canada)



XPDU Series

Model	Part Number	Description	List Price	Input Connection	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
Transformer PDU							
XPD-IT15A	90000739	1.5kW Transformer PDU 208V to 120V	\$980.00	Detachable 3 ft, C14 to C13 Cord	(16) 5-15R	43 lbs	17.3 x 10.5 x 3.5 in (2U)
XPD-IT60A	90000407	6kW Transformer PDU 208V to 208/120V 240V to 240/120V	\$2,170.00	3 ft, L6-30P	(1) L6-30R* and (12) 5-15/20R	137 lbs	17.3 x 18.0 x 3.5 in (2U)
XPD-IT6kW	90000781	6kW Transformer PDU 208V to 240/120V 240V to 240/120V	\$2,310.00	Input terminal block	Output terminal block (2) L14-30R (8) 5-15/20R	199 lbs	17.3" x 32.8" x 4.7 (3U)
XPD-IT10kW	90000740	10kW Transformer PDU 208V to 240/120V 240V to 240/120V	\$2,760.00	Input terminal block	Output terminal block (2) L14-30R (8) 5-15/20R	209 lbs	17.3 x 32.8 x 4.7 in (3U)

*L6-30R output voltage is passed through (not isolated) and the same as input.

SPD Series Price List

*For the most current pricing, visit www.xpcc.com/pricing

Switched PDU

Rack power distribution solutions designed to meet the needs of any data center or wiring closet

- › Local and remote current checking and display
- › Event timers / clock for each power outlet
- › RS232, IE, telnet, SNMP access for users to easily view or change settings
- › DHCP or static IP configure
- › Current alarm by locale, email, trap methods
- › Integrated SNMP agent/Trap notification message capability
- › UL listed
- › 2 year warranty (USA and Canada)



SPD Series							
Model	Part Number	Description	List Price	Input	Output Receptacles	Unit Weight	Unit Dimensions (W x D x H)
SPD-0215	90000460	15A 120V Switched PDU	\$519.00	IEC C14 inlet	(2) 5–15R	4.4 lbs	6.0" x 6.8" x 1.9"

Battery Price List

*For the most current pricing, visit www.xpcc.com/pricing

Individual Battery Replacements Only

Model	Original Battery Size	Qty	Replacement Battery Part Number	List Price (each)	List Price (total)	Case Dimensions (W x D x H)	Notes
S71-700	12V 9AH	1	HRL1234WF2	\$59.00	\$59.00	2.6" x 5.9" x 3.9"	Must open unit to replace battery
S71-1000	12V 7AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
S71-1500	12V 9AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
A60-550	12V 5AH	1	HR1227WF2FR	\$50.00	\$50.00	3.5" x 2.8" x 4"	Must open unit to replace batteries
A60-850	12V 5AH	1	HR1227WF2FR	\$50.00	\$50.00	3.5" x 2.8" x 4"	Must open unit to replace batteries
TX91-3.8K	12V 9AH	20	HRL1234WF2	\$59.00	\$1180.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-5K	12V 9AH	20	HRL1234WF2	\$59.00	\$1180.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-6K	12V 9AH	20	HRL1234WF2	\$59.00	\$1180.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-10K	12V 9AH	20	HRL1234WF2	\$59.00	\$1180.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-3.8KXR	12V 580W	20	UPS12580	\$65.00	\$1300.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-5KXR	12V 580W	20	UPS12580	\$65.00	\$1300.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-6KXR	12V 580W	20	UPS12580	\$65.00	\$1300.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-10KXR	12V 580W	20	UPS12580	\$65.00	\$1300.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-EBP960-1	12V 9AH	20	HRL1234WF2	\$59.00	\$1180.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-EBP960-2	12V 9AH	40	HRL1234WF2	\$59.00	\$2360.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
TX91-EBP960-3	12V 9AH	60	HRL1234WF2	\$59.00	\$3540.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
E91-10k	12V 9AH	40	HRL1234WF2	\$59.00	\$2360.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
E91-15k	12V 9AH	60	HRL1234WF2	\$59.00	\$3540.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
E91-20k	12V 9AH	60	HRL1234WF2	\$59.00	\$3540.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
E91-30k	12V 580W	60	UPS12580	\$65.00	\$3900.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
E91-40k	12V 580W	80	UPS12580	\$65.00	\$5200.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
EBP09-2	12V 9AH	40	HRL1234WF2	\$59.00	\$2360.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
EBP09-5	12V 9AH	100	HRL1234WF2	\$59.00	\$5900.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
EBP10-5	12V 580W	100	UPS12580	\$65.00	\$6500.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries

Individual Battery Replacements Only

Model	Original Battery Size	Qty	Replacement Battery Part Number	List Price (each)	List Price (total)	Case Dimensions (W x D x H)	Notes
T91-700	12V 9AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-1000	12V 9AH	3	HRL1234WF2	\$59.00	\$177.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-1500	12V 9AH	3	HRL1234WF2	\$59.00	\$177.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-2000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91i-2000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91i-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-BP36A	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
T91-BP72A	12V 9AH	12	HRL1234WF2	\$59.00	\$708.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
P80-800	12V 7AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-1100	12V 9AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-1500	12V 7AH	4	HRL1234WF2	\$59.00	\$236.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-2000	12V 7AH	4	HRL1234WF2	\$59.00	\$236.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-2200	12V 7AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80G-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80g-5000	12V 580W	6	UPS12580	\$65.00	\$390.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P80-BP72X	12V 580W	12	UPS12580	\$65.00	\$780.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91-1000	12V 9AH	2	HRL1234WF2	\$59.00	\$118.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91-1500	12V 9AH	3	HRL1234WF2	\$59.00	\$177.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91-2000	12V 9AH	4	HRL1234WF2	\$59.00	\$236.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91g-1500	12V 9AH	3	HRL1234WF2	\$59.00	\$177.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91g-3000	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries
P91-BP36E	12V 9AH	12	HRL1234WF2	\$59.00	\$708.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
P91-BP36	12V 9AH	6	HRL1234WF2	\$59.00	\$354.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
P91-BP48	12V 9AH	8	HRL1234WF2	\$59.00	\$472.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
P91-BP72	12V 9AH	12	HRL1234WF2	\$59.00	\$708.00	2.6" x 5.9" x 3.9"	Must open unit to replace batteries
BPXR2U240A	12V 5AH	20	HR1227WF2FR	\$50.00	\$1000.00	3.5" x 2.8" x 4"	Batteries in trays: remove tray to replace batteries
BPXR3U240A	12V 580W	20	UPS12580	\$65.00	\$1300.00	2.6" x 5.9" x 3.9"	Batteries in trays: remove tray to replace batteries

Internal Battery Trays With Batteries Installed

Model	Original Battery Size	Qty	Replacement Battery Part Number	List Price (each)	List Price (total)	Case Dimensions (W x D x H)	Notes
P91-1000	12V 9AH	1	P90-BAT1-90000370	\$245.00	\$245.00	6.5" x 8.0" x 2.6"	Tray replacement only: 1 tray required
P91-1500	12V 9AH	1	P90-BAT2-90000371	\$295.00	\$295.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
P91-2000	12V 9AH	1	P90-BAT3-90000372	\$350.00	\$350.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
P91-3000	12V 9AH	1	P90-BAT4-90000373	\$465.00	\$465.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P90g-1500	12V 9AH	1	P90-BAT2-90000371	\$295.00	\$295.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P90g-3000	12V 9AH	1	P90-BAT4-90000373	\$465.00	\$465.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80-800	12V 7AH	1	P90-BAT1-90000370	\$245.00	\$245.00	6.5" x 8.0" x 2.6"	Tray replacement only: 1 tray required
P80-1100	12V 9AH	1	P90-BAT1-90000370	\$245.00	\$245.00	6.5" x 8.0" x 2.6"	Tray replacement only: 1 tray required
P80-1500	12V 7AH	1	P90-BAT3-90000372	\$350.00	\$350.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
P80-2000	12V 7AH	1	P90-BAT3-90000372	\$350.00	\$350.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80-2200	12V 7AH	1	P90-BAT4-90000373	\$429.00	\$429.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80-3000	12V 9AH	1	P90-BAT4-90000373	\$429.00	\$429.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80G-3000	12V 9AH	1	P90-BAT4-90000373	\$429.00	\$429.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80g-5000	12V 580W	1	P80-BAT580-90000478	\$495.00	\$459.00	8.5" x 18.5" x 2.6"	Tray replacement only: 1 tray required
P80-BP72X	12V 580W	2	P80-BAT580-90000478	\$495.00	\$990.00	8.5" x 18.5" x 2.6"	Tray replacement only: 2 tray required
J60	2200mAh	1	J60-BAT1- 90000549	\$195.00	\$195.00	2.75" x 6.0" x 1.0"	Must open unit to replace batteries
J60-OE350	2200mAh	1	J60-BAT1- 90000549	\$195.00	\$195.00	2.75" x 6.0" x 1.0"	Must open unit to replace batteries
J60i-350	2200mAh	1	J60-BAT1- 90000549	\$195.00	\$195.00	2.75" x 6.0" x 1.0"	Must open unit to replace batteries
J60-600	4400mAh	1	J60-BAT2 - 90001046	\$432.00	\$432.00	2.75" x 8.75" x 1.25"	Must open unit to replace batteries
J60i-600	4400mAh	1	J60-BAT2 - 90001046	\$432.00	\$432.00	2.75" x 8.75" x 1.25"	Must open unit to replace batteries
J60-OE600	4400mAh	1	J60-BAT2 - 90001046	\$432.00	\$432.00	2.75" x 8.75" x 1.25"	Must open unit to replace batteries
V80-700	12V 9AH	1	V80-BAT1 - 90000987	\$195.00	\$195.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80-1000	12V 9AH	1	V80-BAT2 - 90000988	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80-1500	12V 9AH	1	V80-BAT3 - 90000989	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80-2000	12V 9AH	1	V80-BAT4 - 90000990	\$315.00	\$315.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80HT-700	12V 9AH	1	V80HT-BAT1 - 90000991	\$195.00	\$195.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80HT-1000	12V 9AH	1	V80HT-BAT2 - 90000992	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80HT-1500	12V 9AH	1	V80HT-BAT3 - 90000993	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80HT-2000	12V 9AH	1	V80HT-BAT4 - 90000994	\$315.00	\$315.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-700-1	12V 9AH	1	V80XR-BAT1 - 90000995	\$195.00	\$195.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-700-2	12V 9AH	1	V80XR-BAT2 - 90000996	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-700-3	12V 9AH	1	V80XR-BAT3 - 90000997	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-700-4	12V 9AH	1	V80XR-BAT4 - 90000998	\$315.00	\$315.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-1000-1	12V 9AH	1	V80XR-BAT5 - 90000999	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-1000-2	12V 9AH	1	V80XR-BAT6 - 90001000	\$315.00	\$315.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-1500-1	12V 9AH	1	V80XR-BAT7 - 90001001	\$250.00	\$250.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
V80XR-1500-2	12V 9AH	1	V80XR-BAT8 - 90001002	\$315.00	\$315.00	8.5" x 12.6" x 2.6"	Tray replacement only: 1 tray required
P91-1.5kLi	15S2P	1	P91-BATLi1 - 90001068	\$1,199.00	\$1,199.00	7" x 6.5" x 3"	Tray replacement only: 1 tray required
P91-2kLi	15S2Px2	1	P91-BATLi2 - 90001069	\$2,398.00	\$2,398.00	8.5" x 13.4" x 2.6"	Tray replacement only: 1 tray required
P91-3kLi	24S1Px3	1	P91-BATLi3 - 90001070	\$2,799.00	\$2,799.00	8.5" x 20" x 2.6"	Tray replacement only: 1 tray required



Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2021 Xtreme Power Conversion Corporation. All Rights Reserved. (MPB - O1U - 9/20/21)