

P90g Series UPS Price List

*For the most current pricing, visit www.xpcc.com/pricing

Online 1500VA,3000VA 208/230VAC

Slim 2U form factor UPS delivers clean and continuous power to IT equipment during power disturbances

- > 0.9 output power factor
- > 98% efficient operation
- > Extended battery packs available for extended runtimes
- > Multiple communications capability
- > Auto restart
- > Programmable outlets
- > \$50,000 load protection policy
- > RoHS, CE, TAA compliant (UPS only)
- > 3 years electronics, 3 years battery warranty (USA and Canada)

3000VA/2700W 208/230V UPS

with 1A Charger, 2U

P90g Series 208/230V 50/60

0	P90g Series 208/230V 50/60Hz P90g models have a 1A charger with internal batteries.										
Model	Part Number	Description	List Price	Input Power Cord	Output Receptacles	Unit Weight	Unit & Shipping Dimensions* (W x D x H)				
P90g-1500	90000318	1500VA/1350W 208/230V UPS with 1A Charger, 2U	\$1,269.00	IEC C13 to L6-20P. 8ft	(8) IEC C13	41.7 lbs	17.2" x 18.9" x 3.5" 22.2" x 27.6" x 9.45"				

(1) IEC C19 +

(6) IEC C13

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. **Includes P90-RAIL in bundle.

\$1,999.00

P90g Battery Packs

P90g-3000 90000920

Model	Part Number	Description	List Price	Unit Weight	Unit & Shipping Dimensions* (W x D x H)
P90-BP36	90000915	36V Battery Pack for P90g-1500, 2U	\$829.00	58.1 lbs	17.2" x 18.9" x 3.5" 27.6" x 22.2" x 9.45"
P90-BP36E	90000923	36V 4 String Extended Battery Pack for P90g-1500, 2U	\$1.189.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"
P90-BP72	90000917	72V Battery Pack for P90g-3000, 2U	\$1,239.00	104.4 lbs	17.2" x 23.6" x 3.5" 23.6" x 29.9" x 9.45"

IEC C19 to

L6-20P, 8ft

*Rack depth is front bracket to unit panel. Add 1" for depth including front bezel. **Includes P90-RAIL in bundle.

P90g Output Cords

Model	Description	Cord Length	Input Voltage	List Price	Unit Weight
XPC-C14-615R	IEC C14 to 6–15R for use with P90g-1500, P90g-3000	1ft	208/230V	\$45.00	3 lbs
XPC-ZLC20-620R	Locking IEC C20 to 6–15/20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$59.00	3 lbs
XPC-ZLC20-L620R	Locking IEC C20 to L6–20R for use with P80g-3000, P80g-5000	1ft	208/230V	\$59.00	3 lbs
XPC-ZLC20-L630R	Locking IEC C20 to L6-30R for use with P80g-3000, P80g-5000	1ft	208/230V	\$59.00	3 lbs

P90g Mounting Kits

Model	Part Number	Description	List Price	Unit Weight	Unit Dimensions (W x D x H)
P90-RAIL	90000909	4-Post Rail Kit	\$116.00	5 lbs	3.8" x 19.8" x 2.8"
XPC-2PRAIL	90000406	2-Post Rail Kit; Rated for 125 lbs	\$96.00	5 lbs	4.0" x 20.0" x 3.0"
XPC-2POSTL	90000116	2-Post Shelf Kit; Rated for 150 lbs	\$150.00	9 lbs	21.5" x 23.3" x 3.5"
PV-WMB	90000392	Wall Mount Bracket	\$75.00	5 lbs	4.0" x 24.0" x 4.0"
P90-FRMB	90000377	Front Rackmount Bracket for P90g-1500	\$32.00	1 lb	0.9" x 2.0" x 3.4"



65.7 lbs

17.2" x 25.8" x 3.5"

23.6" x 29.9" x 9.45"



P90g Connectivity

Part Number	Description	List Price	Unit Weight	Shipping Dimensions (W x D x H)
90000741	Two Port Internal SNMP Card	\$279.00	1 lb	7.25" x 6" x 2.5"
90000674	Environmental Monitoring Sensor	\$199.00	1 lb	7.25" x 6" x 2.5"
90000267	Modbus Card	\$299.00	1 lb	7.25" x 6" x 2.5"
90000265	General Relay Contacts with DB9 & Terminal Block Adapter	\$110.00	1 lb	7.25" x 6" x 2.5"
	Number 90000741 90000674 90000267	NumberDescription90000741Two Port Internal SNMP Card90000674Environmental Monitoring Sensor90000267Modbus Card	NumberDescriptionList Price90000741Two Port Internal SNMP Card\$279.0090000674Environmental Monitoring Sensor\$199.0090000267Modbus Card\$299.00	NumberDescriptionList PriceWeight90000741Two Port Internal SNMP Card\$279.001 lb90000674Environmental Monitoring Sensor\$199.001 lb90000267Modbus Card\$299.001 lb

*SNMP-EMPV2 to be used with SNMP-2PV3

Bypass Distribution Modules

Model	Part Number	Description	List Price	Utility Input	Output Connections	UPS Connections	Unit Weight	Unit Dimensions (W x D x H)
XBDM1020HV2	90000094	Bypass 16A capacity for use with P90g-3000 (includes (2) IEC C20 C19 cord kit)	\$345.00	IEC C20 inlet	(2) IEC C19 + (4) IEC C13 front (4) IEC C13 back		3.5 lbs	19.3" x 3.5" x 1.75"

Power Distribution Units & Transformers

Model	Part Number	Description	List Price	Input Power Cord	Outlets	Unit Weight	Unit Dimensions (W x D x H)
XPDU-IEC	90000053	230V Basic Power Distribution Unit for use with P90g-3000	\$160.00	IEC C20 inlet	(10) IEC C13 + (2) IEC C19	2.6 lbs	19.0" x 3.5" x 1.75"
XPD-IT15A	90000739	2U 1500VA Isolation transformer 208V in to 120V out with 3' C14 to C13 input cord	\$629.00	IEC C14 inlet	(16) 5-15	43 lbs	17.25" x 15" x 3.5"
XAT-400	90000269	400VA Step Down Transformer 208V to 120V for use with P90g-1500, P90g-3000	\$465.00	208V IEC C14, 2ft	120V 5–15R, 2ft	8 lbs	7.0" x 6.8" x 5.9"

P90g Service Plans (USA and Canada)

Model	Part Number	Description	List Price				
P905SP15	90000522	Extended 5 Year Factory Warranty for P90g-1500, P90c-1000, P90-1000, P90-1500, P80-800, P80-1100, P80-1500, UPS	\$375.00				
P905SP23	90000523	Extended 5 Year Factory Warranty for P90g-3000, P90-2000, P90-3000, P80-2000, P80-2200, P80-3000(V2), P80g-3000 UPS	\$610.00				
P90L5SPBP	90000524	Extended 5 Year Factory Warranty for P90-BP36, P90-BP36E, P90-BP48, P90-BP72	\$320.00				
Standard 3 Year Fa	Standard 3 Year Factory Warranty – 3 years electronics/battery. Telephone Extended 5 Year Factory Warranty – 5 year electronics/battery. Telephone						

 Standard 3 Year Factory Warranty – 3 years electronics/battery. Ielephone
 Ext

 technical support. Depot exchange. Ground shipment one way.
 technical support.

technical support. Advanced exchange. Pricing is limited to the continental USA. Ground shipment both ways.

P90g Battery Runtimes

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.

Model	P90g-1500 (BP36)		P90g-1500 (BP36E)		P90g-3000 (BP72)	
Percentage load:	50%	100%	50%	100%	50%	100%
Internal batteries	8	3	8	3	8	3
(1) Battery pack	34	20	66	38	34	20
(2) Battery packs	66	38	N/A	N/A	66	38

Maximum of two battery packs per P90g-1500 or P90g-3000. P90-BP36E is limited to one.